PerIClass.com's Perl Training Materials

Christopher Hicks and Kirrily Robert

PerlClass.com for ACT Students 20-23 Feb 2007

Perl Training Materials

by Christopher Hicks

Copyright ©

1999-2000, Netizen Pty Ltd

2000 by Kirrily Robert

2001-2007 by Christopher Hicks

<u>License</u>

This book is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License version 2as published by the Free Software.. This book is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this book; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA or go to http://www.gnu.org/.

This book was based on material under the Open Publications License available at http://www.content.org/openpub/.

File and Version Info

02/15/07 12:10:35 PM 397 pages

C:\Documents and Settings\Administrator\My Documents\perlClass\perlClass-0.49.odt

Table of Contents

Chapter 1: Introduction	17
1.1 Assumed knowledge	
1.2 Day 1 rough outline	
1.3 Day 1 objectives	
1.4 Day 2 outline	21
1.5 Day 2 objectives	
1.6 Day 3 outline	
1.7 Day 3 objectives	
1.8 Day 4 outline	
1.9 Day 4 objectives	
1.10 Other topics we can discuss	
1.11 Platform and version details	
1.12 The course notes	
1.13 Other materials	
Chapter 2: What is Perl	
2.1 Perl's name	
2.2 Typical uses of Perl	
2.2.1 Text processing	
2.2.2 System administration tasks	
2.2.3 CGI and web programming	
2.2.4 Database interaction.	
2.2.5 Other Internet programming	
2.2.6 Less typical uses of Perl	
2.3 What is Perl like?	

2.4 The Perl Philosophy	
2.4.1 There's more than one way to do it	
2.4.2 A correct Perl program	
2.4.3 Three virtues of a programmer	
2.4.3.1 Laziness	
2.4.3.2 Impatience	
2.4.3.3 Hubris	
2.4.4 Three more virtues	
2.4.5 Share and enjoy!	
2.5 Parts of Perl.	40
2.5.1 The Perl interpreter	
2.5.2 Manuals	40
2.5.3 Perl Modules	
2.6 Chapter summary	
	10
Chapter 3: Creating and running a Peri program	
3.1 Logging into your account	
3.2 Using perldoc	
3.3 Using the editor	56
3.4 Our first Perl program	
3.5 Running a Perl program from the command line	
3.6 The "shebang" line	
3.7 Comments	60
3.8 Command line options	61
3.9 Chapter summary	
Chapter 4: Perl variables	63
4.1 What is a variable?	
4.2 Variable names	
4.3 Variable scoping and the strict pragma	
4.3.1 Arguments in favour of strictness	
4.3.2 Arguments against strictness	
4.4 Using the strict pragma	
4.5 Scalars	
4.6 Double and single quotes	
4.6.1 Exercises	
4./ Arrays	
4.7.1 A quick look at context	
4.7.2 What's the difference between a list and an array?	
4.7.3 Exercises	

4.7.4 Advanced exercises	
4.8 Hashes	77
4.8.1 Initialising a hash	77
4.8.2 Reading hash values	
4.8.3 Adding new hash elements	
4.8.4 Other things about hashes	
4.8.5 What's the difference between a hash and an associative array?	79
4.8.6 Exercises	79
4.9 Special variables	80
4.10 The first special variable, \$	
4.10.1.1 Exercises	
4.11 @ARGV - a special array	
4.11.1.1 Exercises	
4.12 %ENV - a special hash	
4.12.1.1 Exercises	
4.13 Chapter summary	
Chapter 5: Operators and functions	
5.1 What are operators and functions?	88
5.2 A rithmetic operators	
5.2 Artificite operators	90 90
5.5 String operators	
5 4 File operators	
5.5 Other operators	92
5.6 Functions	93
5.6.1 Types of arguments	93
5.6.2 Return values	94
5 7 More about context	95
5.8 String manipulation	96
5.8.1.1 Finding the length of a string	
5.8.1.2 Case conversion.	
5.8.1.3 chop() and chomp()	
5.8.1.4 String substitutions with substr()	
5.9 Numeric functions	
5.10 Type conversions	
5.11 Manipulating lists and arrays	
5.11.1 Stacks and queues	
5.11.2 Sorting lists	
5.11.3 Converting lists to strings, and vice versa	101
5.12 Hash processing.	

5.13 Reading and writing files	
5.14 Time	104
5.15 Exercises	105
5.16 Chapter summary	
Chapter 6: Conditional constructs	107
6.1 What is a block?	
6.2 Scope	
6.3 What is a conditional statement?	
6.4 What is truth?	111
6.5 Comparison operators	
6.5.1 Existence and Defined-ness	113
6.5.2 Boolean logic operators	
6.5.3 Using boolean logic operators as short circuit operators	116
6.6 Types of conditional constructs	
6.6.1 if statements	
6.6.2 while loops	119
6.6.3 for and foreach.	119
6.6.4 Exercises	
6.7 Practical uses of while loops: taking input from STDIN	121
6.8 Best practices template for file manipulation	
6.9 Named blocks	
6.10 Breaking out of loops	
6.11 Chapter summary	126
Chapter 7: Subroutines	127
7.1 Introducing subroutines	
7.2 Calling a subroutine	
7.3 Passing arguments to a subroutine	130
7.4 Returning values from a subroutine	131
7.5 Exercises	
7.6 Chapter summary	133
Chapter 8: Regular expressions	135
8.1 What are regular expressions?	136
8.2 Regular expression operators and functions	130
8.2.1 m/PATTERN/ - the match operator	
8.2.2 s/PATTERN/REPLACEMENT/ - the substitution operator	137
8 3 Binding operators	139
8.4 Metacharacters.	
······································	

8.4.1 Some easy metacharacters	
8.5 Quantifiers	
8.6 Greediness	143
8.7 Exercises	144
8.8 Character classes	
8.8.1 Exercises as a group	145
8.9 Alternation	146
8.10 The concept of atoms	147
8.11 Exercises	
8.12 split() function	149
8.13 Exercises	150
8.14 Chapter summary	151
	4 = 0
Chapter 9: Practical exercises	153
9.1 Exercises	
Chapter 10: File I/O	
10.1 Assumed knowledge	
10.2 Angle brackets - the line input and globbing operators	
10.2.1 Exercises	159
10.2.1.1 Advanced exercises	
10.3 open() and friends - the gory details	
10.3.1 Opening a file for reading, writing or appending	
10.3.1.1 Exercises	
10.3.2 Reading directories	
10.3.2.1 Exercises	
10.3.3 Opening files for simultaneous read/write	
10.3.3.1 Exercises	164
10.3.4 Opening pipes	
10.3.4.1 Exercises	166
10.4 Finding information about files	
10.4.1 Exercises	
10.5 Recursing down directories	
10.5.1 Exercises	171
10.6 File locking	
10.7 Handling binary data	
10.8 Chapter summary	175

Chapter 11: Advanced regular expressions	177
11.1 Assumed knowledge	
11.2 Review exercises.	179
11.3 More metacharacters	
11.4 Working with multiline strings	
11.4.1 Exercises	
11.5 Regexp modifiers for multiline data	
11.6 Backreferences	186
11.6.1 Special variables	
11.7 Exercises	
11.7.1 Advanced	
11.8 Section summary	189
Chapter 12: More functions	
12.1 The grep() function	
12.1.1 Exercises	
12.2 The map() function	
12.2.1 Exercises	
12.3 Chapter summary	
Chapter 13: System interaction	
13.1 system() and exec()	
13.1.1 Exercises	
13.2 Using backticks	
13.2.1 Exercises	
13.3 Platform dependency issues	
13.4 Security considerations	
13.4.1 Exercises	
13.5 Section summary	204
Chapter 14: References and data structures	205
14.1 Assumed knowledge	
14.2 Introduction to references	
14.3 Uses for references	
14.3.1 Creating complex data structures	
14.3.2 Passing arrays and hashes to subroutines and functions	
14.3.3 Object oriented Perl	
14.4 Creating and dereferencing references	209
14.5 Passing multiple arrays/hashes as arguments	

14.6 Complex data structures	
14.7 Anonymous data structures	
14.8 Exercises	
14.9 Section summary	
Chapter 15: About databases	219
15.1 What is a database?	
15.2 Types of databases	
15.3 Database management systems	
15.4 Uses of databases	
15.5 Chapter summary	
Chapter 16: Textfiles as databases	225
16.1 Delimited text files	
16.1.1 Reading delimited text files	
16.1.2 Searching for records	
16.1.3 Sorting records	
16.1.4 Writing to delimited text files	
16.2 Comma-separated variable (CSV) files	
16.3 Problems with flat file databases	
16.3.1 Locking	
16.3.2 Complex data	
16.3.3 Efficiency	
16.4 Chapter summary	
Chapter 17: Relational databases	
17.1 Tables and relationships	
17.2 Structured Query Language	
17.2.1 General syntax	
17.2.1.1 SELECT	
17.2.1.2 INSERT	
17.2.1.3 DELETE	
17.2.1.4 UPDATE	
17.2.1.5 CREATE	
17.2.1.6 DROP	
17.3 Chapter summary	
Chapter 18: MySQL	245
18.1 MySQL features	

• • • •
250
250
255
257
259
267 268 269 269

 20.4 Entering a sale into the system. 20.5 Creating sales reports. 20.5.1 Advanced exercises. 20.6 Searching for stock items. 20.6.1 Advanced exercises. 	
Chapter 21: References	
21.1 Uses for Perl references	280
21.1 Oses for references	280
21.2 Complex data structures	283
21.5 Comptex duta strategies	284
21.5 Anonymous data structures	285
21.6 Chapter summary	
Chapter 22: What is CGI?	
22.1 Definition of CGI	288
22.1 Definition of COL 22.2 Introduction to HTTP	289
22.3 Terminology	291
22.4 HTTP status codes	293
22.5 HTTP Methods	
22.5.1.1 GET	
22.5.1.2 HEAD	
22.5.1.3 POST	
22.6 Exercises	
22.7 What is needed to run CGI programs?	
22.8 Chapter summary	
Chapter 23: Generating web pages with Perl	299
23.1 Your public html directory	
23.2 The CGI directory	
23.3 The HTTP headers	
23.4 HTML output	
23.5 Running and debugging CGI programs	
23.5.1 Exercises	
23.6 Quoting made easy	
23.6.1 Here documents	
23.7 Pick your own quotes	
23.8 Exercises	
23.9 Environment variables	

23.9.1 Exercises	
23.10 Chapter summary	
Chapter 24: Processing form input	311
24.1 A quick look at HTML forms	
24.2 The FORM element	
24.3 Input fields	
24.3.1 TEXT	
24.3.2 CHECKBOX	
24.3.3 SELECT	
24.3.4 SUBMIT	
24.4 The CGI module	
24.4.1 What is a module?	
24.4.2 Using the CGI module	
24.4.3 Accepting parameters with CGI	
24.4.4 Debugging with the CGI module's offline mode	
24.4.5 Exercises	
24.5 Practical Exercise: Data validation	
24.5.1 Exercises	
24.6 Practical Exercise: Multi-form "Wizard" interface	
24.6.1 Exercises	
24.7 Practical Exercise: File upload	
24.8 Chapter summary	
Chapter 25. Coourity issues	207
Chapter 25: Security issues	
25.1 Authentication and access control for CGI scripts	
25.1.1 Why is CGI authentication a bad idea?	
25.2 HTTP authentication	
25.3 Access control	
25.3.1 Exercises	
25.4 Tainted data	
25.4.1 Exercises	
25.5 cgiwrap	
25.6 Secure HTTP	
25.7 Chapter summary	
Chapter 26: Other related Perl modules	337
26.1 Useful Perl modules	338
26.1 Oberar Ferrinoucles	330
26.2.1 Exercise	340
20.2.1 L/X010100	

26.3 Encoding URIs with URI::Escape	
26.3.1 Exercise	
26.4 Creating templates with Text::Template	342
26.4.1 Introduction to object oriented modules	
26.4.2 Using the Text::Template module	
26.4.3 Exercise	343
26.5 Sending email with Mail::Mailer	
26.5.1 Exercises	
26.6 Chapter Summary	
Chapter 27: Con-clusion	347
27.1 Day 1: What you've learned.	
27.2 Day 2: What you've learned.	
27.3 Day 3: What you've learned	
27.4 Day 4: What you've learned	
27.5 Where to now?	
27.6 Further reading	
27.6.1 Books	
27.6.2 Online	353
Chapter 28: Win32::EventLog	355
28.1 Win32::EventLog Examples	
28.2 Win32::EventLog Reference	
28.2.1 The EventLog Object and its Methods	
28.2.2 Other Win32::EventLog functions	361
Chapter 29: Win32::NetAdmin	363
29.1 Example	364
29.2 Win32::NetAdmin provided functions	
Chapter 30: Other Perl Win32 Modules	371
30.1 Win32. NetResource	372
30.1 1 Examples	
30.1.2 Data Types	
30.1.2.1 %NETRESOURCE	373
30 1 2 2 %SHARE_INFO	374
30 1 3 Functions	374
30.2 Win32::Service.	
30.2.1 Examples	

30.2.2 Functoins.	
30.3 Win52.:Sound	
Chapter 31: *NIX cheat sheet	
31.1 Some UNIX commands	
Chapter 32: Editor cheat sheet	
32.1 vi	
32.1.1 Running	
32.1.2 Using	
32.1.3 Exiting	
32.1.4 Gotchas	
32.1.5 Help	
32.2 pico	
32.2.1 Running	
32.2.2 Using	
32.2.3 Exiting	
32.2.4 Gotchas	
32.2.5 Help	
32.3 joe	
32.3.1 Running	
32.3.2 Using	
32.3.3 Exiting	
32.3.4 Gotchas	
32.3.5 Help	
32.4 jed	
32.4.1 Running	
32.4.2 Using	
32.4.3 Exiting	
32.4.4 Gotchas	
32.4.5 Help	
Chapter 33: ASCII Pronunciation Guide	
Chapter 34: HTML Cheat Sheet	
Chapter 35: Acknowledgements	
35.1 Folks	396
35.2 Projects	397
<i>55.2</i> 1 10 50 00	

Chapter 1: Introduction

This chapter will...

Welcome to PerlClass.com's Perl training module. This is a training course in which you will learn how to program in the Perl programming language.

1.1 Assumed knowledge

To gain the most from this course, you should:

- Be able to use the UNIX operating system
 - Move around the file system
 - Create and edit files
 - Run programs

1

- Have programmed in least one other language and
 - Understand variables, including data types and arrays
 - Understand conditional and looping constructs
 - Understand the use of subroutines and/or functions
- Basic database theory tables, records, fields
- Basic HTML paragraphs, headings, ordered and unordered lists, anchor tags, images, etc.

If you need help with editing files under UNIX, a cheat-sheet is available in Appendix A and an editor command summary in Appendix B.

The UNIX operating system commands you will need are mentioned and explained very briefly throughout the course - please feel free to ask if you need more help. The required Perl knowledge was covered in PerlClass.com's "Introduction to Perl" course, which many of you will have attended recently. Lastly, an HTML cheat-sheet is provided in Appendix D for those who need reminding.

1.2 Day 1 rough outline

- What is Perl? (30 minutes)
- Creating and running a Perl program (45 minutes)
- *Morning tea* (15 minutes)
- Variable types (45 minutes)
- Operators and Functions (60 minutes)
- *Lunch break* (60 minutes)
- Conditional constructs (45 minutes)
- Subroutines (30 minutes)
- Afternoon tea (15 minutes)
- Regular expressions (45 minutes)
- Practical exercises (until finish)

1.3 Day 1 objectives

1

- Understand the history and philosophy behind the Perl programming language
- Know where to find additional information about Perl
- Write simple Perl scripts and run them from the UNIX command line
- Use Perl's command line options to enable warnings
- Understand Perl's three main data types and how to use them
- Use Perl's strict pragma to enforce lexical scoping and better coding
- Understand Perl's most common operators and functions and how to use them
- Understand and use Perl's conditional and looping constructs
- Understand and use subroutines in Perl
- Understand and use simple regular expressions for matching and substitution

1.4 Day 2 outline

- Revise introduction to Perl material
- File I/O
 - · Line input and globbing operators
 - Opening files, directories, and pipes
 - Finding information about files
 - Recursing down directories
 - File locking
 - · Handling binary data
- Advanced regular expressions
 - Review of basic regexps
 - Multiline strings
 - Backreferences
- More functions
 - grep() and map() functions
 - printf() and sprintf()
 - pack() and unpack()
 - List manipulation with splice()
- System interaction
 - system() and exec()
 - Backticks
 - Interacting with the file system
 - · Dealing with users, groups and permissions
 - Interacting with processes
 - Security considerations
- · References and complex data structures
 - Creating and dereferencing
 - Complex data structures

• Anonymous data structures

1.5 Day 2 objectives

- Be able to open files and directories to read and write data, using various techniques
- Perform tests on files and directories
- Open pipes to read or write data through another program
- Use regular expressions to handle multiline data
- Use backreferences to create complex regular expressions
- Use and understand more complex Perl functions such as grep() and map()
- Use Perl functions to call system commands
- Use Perl to interact with the file system, users, and processes
- Understand the security implications of running system commands from Perl, and how to increase security
- Understand and use Perl references to create complex data structures and anonymous data structures

1.6 Day 3 outline

- About databases
- Text based ("flat file") databases
- Relational databases
- Tables and relationships
- Structured Query Language (SQL)
- MySQL and other database servers
- Features of MySQL
- Getting MySQL
- Setting up MySQL databases
- The MySQL client
- The DBI and DBD modules
- What is DBI?
- DBI syntax
- DBI exercises
- Extended exercises
- References (optional topic)

1.7 Day 3 objectives

- Understand what a database is and use correct terminology to describe types of databases and parts of databases
- Understand and use flat file or textual databases with Perl
- Understand the advantages and limitations of flat file or textual databases and relational databases
- Understand and use Structured Query Language (SQL) to manipulate data in a relational database
- Know about MySQL and other relational databases suitable for small to medium applications
- Use the MySQL command line client to perform SQL queries
- · Understand and use Perl's DBI module to interact with databases
- Use the skills and knowledge learned in this module to create a sample application

1.8 Day 4 outline

- What is CGI? (60 minutes)
- Generating web pages with a Perl script (45 minutes)
- Practical exercises (45 minutes)
- Accepting and processing form input with the CGI module (60 minutes)
- Lunch break
- Practical examples (60 minutes)
- Security issues (45 minutes)
- Other related features and Perl modules (60+ minutes)

1.9 Day 4 objectives

- Understand the meaning of CGI and the HyperText Transfer Protocol (http)
- Know how to generate simple web pages using Perl
- Understand how to accept and process data from web forms using the CGI module
- Understand security issues pertaining to CGI programming and how to avoid security problems
- Recognise and use a number of Perl modules for purposes related to CGI programming

1.10 Other topics we can discuss

- Win32 Perl programming in Windows
- XML there seems to be a lot of XML data lately
- Tk GUI toolkit
- mod_perl Perl integration with apache
- Inline seamless inclusion of non-Perl in Perl
- Data::Dumper a convenient way to print out complex data structures
- DBIx::Class a friendy OOP-style layer on top of DBI
- Storable persistance of complex Perl object across processes, systems, etc.
- ???
- ???
- ???

1.11 Platform and version details

This course is taught using Linux, a UNIX-like operating system. Most of what is learned will work equally well on Microsoft Windows, MacOS or other operating systems. Your instructor will inform you throughout the course of any areas which differ.

All PerlClass.com's Perl training courses use Perl 5.8. Perl 5 is the most recent major release of the Perl language. Perl 5 differs significantly from previous versions of Perl, so you will need a Perl 5 interpreter to use what you learn. However, nearly all older Perl programs should work fine under Perl 5.

1.12 The course notes

1

These course notes contain material which will guide you through the topics listed above, as well as appendices containing other useful information.

The following typographical conventions are used in these notes:

System commands appear in this typeface

Literal text which you should type in to the command line or editor appears as monospaced font.

Keystrokes which you should type appear like this: **ENTER**. Combinations of keys appear like this: **CTRL-D**

Program listings and other literal listings of what appears on the screen appear in a monospaced font like this.

Parts of commands or other literal text which should be replaced by your own specific values appears *like this*

Notes and tips appear offset from the text like this.

Advanced

Notes which are marked "Advanced" are for those who are racing ahead or who already have some knowledge of the topic at hand. The information contained in these notes is not essential to your understanding of the topic, but may be of interest to those who want to extend their knowledge.

RT FM!

Notes marked with "RTFM!" are pointers to more information which can be found in your textbook or in online documentation such as manual pages or websites.

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd			Perl in a Nutshell
Camel 2 nd			Programming Perl
Camel 3 rd			Programming Perl
perldoc			perldoc online
Cookbook 2 nd			Perl Cookbook
Learning 3 rd			Learning Perl
Learning 4 th			Learning Perl

Most RTFM boxes will appear with a table like this. The "src" column refers to a variety of standard Perl references. "Chap" is the chapter which for electronic contexts like man and perldoc would refer to the "man page" or "whole pod".

1.13 Other materials

In addition to these notes, you should have a copy of the required text book for this course: *Perl in a Nutshell* 2nd Ed. by Nathan Patwardhan, Ellen Siever and Stephen Spainhour. The Nutshell will be used throughout the course, and will be a valuable reference to take home and keep next to your computer.

Chapter 2: What is Perl

In this chapter...

This section describes Perl and its uses. You will learn about this history of Perl, the main areas in which it is commonly used, and a little about the Perl community and philosophy. Lastly, you will find out how to get Perl and what software comes as part of the Perl distribution.

2.1 Perl's name

Perl has been said to stand for "Practical Extraction and Reporting Language" (by it's fans) or "Pathologically Eclectic Rubbish Lister" (by its detractors). In fact, Perl is not an acronym; it's a shortened version of the program's original name, "pearl", and when you're talking about the language it's spelled with a capital "P" and lowercase "erl", not all capitals as is sometimes seen (especially in job advertisements posted by contract agencies). When you're talking about the Perl interpreter, it's spelled in all lower case: **perl**.

Perl has been described as everything from "line noise" to "the Swiss-army chainsaw of programming languages". The latter of these nicknames gives some idea of how programmers see Perl - as a very powerful tool that does just about everything.

2.2 Typical uses of Perl

2.2.1 Text processing

Perl's original main use was text processing. It is exceedingly powerful in this regard, and can be used to manipulate textual data, reports, email, news articles, log files, or just about any kind of text, with great ease.

2.2.2 System administration tasks

System administration is made easy with Perl. It's particularly useful for tying together lots of smaller scripts, working with file systems, networking, and so on.

2.2.3 CGI and web programming

Since HTML is just text with built-in formatting, Perl can be used to process and generate HTML. Perl is probably the most popular language around for web development, and there are many tools and scripts available for free.

2.2.4 Database interaction

Perl's DBI module makes interacting with all kinds of databases --- from Oracle down to comma-separated variable files --- easy and portable. Perl is increasingly being used to write large database applications, especially those which provide a database back end to a website.

2.2.5 Other Internet programming

Perl modules are available for just about every kind of Internet programming, from Mail and News clients, interfaces to IRC and ICQ, right down to lower level Socket programming.

2.2.6 Less typical uses of Perl

Perl is used in some unusual places as well. The Human Genome Project relies on Perl for DNA sequencing, NASA uses Perl for satellite control, PDL (Perl Data Language, pron. "piddle") makes number-crunching easy, and there is even a Perl Object Environment (POE) which is used for event-driven state machines.

2.3 What is Perl like?

The following (somewhat paraphrased) article, entitled "What is Perl", comes from The Perl Journal (http://www.tpj.com/) (Used with permission.)

Perl is a general purpose programming language developed in 1987 by Larry Wall. It has become the language of choice for WWW development, text processing, Internet services, mail filtering, graphical programming, and every other task requiring portable and easily-developed solutions.

Perl is interpreted. This means that as soon as you write your program, you can run it - there's no mandatory compilation phase. The same Perl program can run on UNIX, Windows, NT, MacOS, DOS, OS/2, VMS and the Amiga.

Perl is collaborative. The CPAN software archive contains free utilities written by the Perl community, so you save time.

Perl is free. Unlike most other languages, Perl is not proprietary. The source code and compiler are free, and will always be free.

Perl is fast. The Perl interpreter is written in C, and a decade of optimizations have resulted in a fast executable.

Perl is complete. The best support for regular expressions in any language, internal support for hash tables, a built-in debugger, facilities for report generation, networking functions, utilities for CGI scripts, database interfaces, arbitrary-precision arithmetic - are all bundled with Perl.

Perl is secure. Perl can perform "taint checking" to prevent security breaches. You can also run a program in a "safe" compartment to avoid the risks inherent in executing unknown code.

Perl is open for business. Thousands of corporations rely on Perl for their information processing needs.

Perl is simple to learn. Perl makes easy things easy and hard things possible. Perl handles tedious tasks for you, such as memory allocation and garbage collection.

Perl is concise. Many programs that would take hundreds or thousands of lines in other programming languages can be expressed in a pageful of Perl.

Perl is object oriented. Inheritance, polymorphism, and encapsulation are all provided by Perl's object oriented capabilities.

Perl is flexible The Perl motto is "there's more than one way to do it." The language doesn't force a particular style of programming on you. Write what comes naturally.

Perl is fun. Programming is meant to be fun, not only in the satisfaction of seeing our well-tuned programs do our bidding, but in the literary act of creative writing that yields those programs. With Perl, the journey is as enjoyable as the destination.
2.4 The Perl Philosophy

2.4.1 There's more than one way to do it

The Perl motto is "there's more than one way to do it" - often abbreviated TM-TOWTDI. What this means is that for any problem, there will be multiple ways to approach it using Perl. Some will be quicker, more elegant, or more readable than others, but that doesn't make them *wrong*.

2.4.2 A correct Perl program...

"... is one that does the job before your boss fires you." That's in the preface to the Camel book, which is highly recommended reading.

Of course, some Perl programs are more correct than others, but while elegance is a fine thing to strive for, most Perl people realize that sometimes you just have to write a quick and dirty hack that'll keep things running for the mean time. If you get the time to make it beautiful later, so much the better.

2.4.3 Three virtues of a programmer

The Camel book contains the following entries in its glossary:

2.4.3.1 Laziness

The quality that makes you go to great effort to reduce overall energy expenditure. It makes you write labor-saving programs that other people will find useful, and document what you wrote so you don't have to answer so many questions about it. Hence, the first great virtue of a programmer.

2.4.3.2 Impatience

The anger you feel when the computer is being lazy. This makes you write programs that don't just react to your needs, but actually anticipate them. Or at least pretend to. Hence, the second great virtue of a programmer.

2.4.3.3 Hubris

Excessive pride, the sort of thing Zeus zaps you for. Also the quality that makes you write (and maintain) programs that other people won't want to say bad things about. Hence, the third great virtue of a programmer.

2.4.4 Three more virtues

In his "State of the Onion" keynote speech at The Perl Conference 2.0 in 1998, Larry Wall described another three virtues, which are the virtues of a community of programmers. These are:

- Diligence
- Patience
- Humility

You may notice that these are the opposites of the first three virtues. However, they are equally necessary for Perl programmers who wish to work together, whether on a software project for their company or on an Open Source project with many contributors around the world.

2.4.5 Share and enjoy!

Perl is Open Source software, and most of the modules and extensions for Perl are also released under Open Source licenses of various kinds (Perl itself is released under dual licenses, the GNU General Public License and the Artistic License, copies of which are distributed with the software).

The culture of Perl is fairly open and sharing, and thousands of volunteers worldwide have contributed to the current wealth of software and knowledge available to us. If you have time, you should try and give back some of what you've received from the Perl community. Contribute a module to CPAN, help a new Perl programmer to debug her programs, or write about Perl and how it's helped you. Even buying books written by the Perl gurus (like many of the O'Reilly Perl books) helps give them the financial means to keep supporting Perl.

2.5 Parts of Perl

2.5.1 The Perl interpreter

The main part of Perl is the interpreter. The interpreter is available for UNIX, Windows, and many other platforms.

The current version of Perl is 5.8.8, which is available from the Perl website (http://www.perl.com/) or any of a number of mirror sites. Work has been moving slowly on Perl 6 and it is still early in the test stage. You can check <u>http://www.perl.org/</u> for current version status.

A Windows version is available from ActiveState (<u>http://www.activestate.-</u> <u>com/</u>) or as part of Cygwin tool kit (<u>http://www.cygwin.com/</u>).

2.5.2 Manuals

Along with the interpreter come the manuals for Perl. These are accessed via the **perldoc** command or, on UNIX systems, also via the **man** command. More than 30 manual pages come with the current version of perl. These can be found by typing **man perl** (or **perldoc perl** on non-UNIX systems). The Perl FAQs (Frequently Asked Questions files) are available in perldoc format, and can be accessed by typing **perldoc perlfaq**

Watch while this is demonstrated; you'll get a chance to try it soon.

2.5.3 Perl Modules

Perl also comes with a collection of modules. These are Perl programs which carry out certain common tasks, and can be included as common libraries in any Perl script. Less commonly used modules aren't included with the distribution, but can be downloaded from (CPAN (http://www.perl.com/CPAN)) and installed separately.

2.6 Chapter summary

- · Common uses of Perl include
 - text processing
 - system administration
 - · CGI and web programming
 - other Internet programming
- Perl is a general purpose programming language, distributed for free via the Perl website (http://www.perl.com/) and mirror sites
- Perl includes excellent support for regular expressions, object oriented programming, and other features
- Perl allows a great degree of programmer flexibility "There's more than one way to do it".
- The three virtues of a programmer are Laziness, Impatience and Hubris. Perl will help you foster these virtues
- The three virtues of a programmer in a group environment are Diligence, Patience, and Humility.
- Perl is a collaborative language everyone is free to contribute to the Perl software and the Perl community
- Parts of Perl include:
 - the Perl interpreter
 - · documentation in several formats
 - library modules

Chapter 3: Creating and running a Perl program

In this chapter...

In this chapter we will be creating a very simple "Hello, world" program in Perl and exploring some of the basic syntax of the Perl programming language.

3.1 Logging into your account

Your username and password will have been given to you with these course notes.

Fable 3-1. Details re	quired to connect	to the PerlClass.com	n training server
------------------------------	-------------------	----------------------	-------------------

Hostname or IP address	perlclass.fini.net 192.168
Your username	
Your password	

1. Open putty

- 2. Connect to the training server at the hostname or IP number given above
- 3. Login using the username and password you were given

You will find yourself at a UNIX shell prompt. Hopefully (if you met the prerequisites of this course) you will now be able to see that your account has a subdirectory called *exercises*/ which are the example scripts and exercises given in these course notes. If you're not quite up to speed with UNIX, there's a cheat-sheet in Appendix A of these notes. 3

3.2 Using peridoc

On the command line, type **perldoc perl**. You will find yourself in the Perl documentation pages. Here's how to get around inside the documentation:

Action	Keystroke
Page down	SPACE
Page up	b
Quit	q

 Table 3-2. Getting around in peridoc

\$ perldoc perl

PERL(1)	User	Contributed	Perl	Documentation
PERL(1)				

NAME

perl - Practical Extraction and Report Language

SYNOPSIS

perl [-sTuU] [-hv] [-V[:configvar]]
 [-cw] [-d[:debugger]] [-D[number/list]]
 [-pna] [-Fpattern] [-1[octal]] [-0[octal]]
 [-Idir] [-m[-]module] [-M[-]'module...']
 [-P] [-S] [-x[dir]]
 [-i[extension]] [-e 'command']
 [--] [program-file] [argument]...

If you're new to Perl, you should start with perlintro, which is a general intro for beginners and provides some background to help you navigate the rest of Perl's extensive documentation.

For ease of access, the Perl manual has been split up into several sections.

Overview

perl perlintro perltoc	Perl overview (this section) Perl introduction for beginners Perl documentation table of contents
Tutorials	
perlreftut	Perl references short introduction
perldsc	Perl data structures intro
perllol	Perl data structures: arrays of arrays
perlrequick	Perl regular expressions quick start
perlretut	Perl regular expressions tutorial
perlboot	Perl OO tutorial for beginners
perltoot	Perl OO tutorial, part 1
perltooc	Perl OO tutorial, part 2
perlbot	Perl OO tricks and examples
perlstyle	Perl style guide
perlcheat	Perl cheat sheet
perltrap	Perl traps for the unwary
perldebtut	Perl debugging tutorial
perlfaq	Perl frequently asked questions
perlfaq1	General Questions About Perl
perlfaq2	Obtaining and Learning about Perl
perlfaq3	Programming Tools
perlfaq4	Data Manipulation
perlfaq5	Files and Formats
perlfaq6	Regexes
perlfaq7	Perl Language Issues
perlfaq8	System Interaction
perlfaq9	Networking

Reference Manual

perlsyn	Perl	syntax
perldata	Per]	data structures
perlop	Per]	operators and precedence

Creating and running a Perl program

3

perlsub	Perl subroutines
perlfunc	Perl built-in functions
perlopentut	Perl open() tutorial
perlpacktut	Perl pack() and unpack() tutorial
perlpod	Perl plain old documentation
perlpodspec	Perl plain old documentation format
	specification
perlrun	Perl execution and options
perldiag	Perl diagnostic messages
perllexwarn	Perl warnings and their control
perldebug	Perl debugging
perlvar	Perl predefined variables
perlre	Perl regular expressions, the rest of the
	story
perlreref	Perl regular expressions quick reference
perlref	Perl references, the rest of the story
perlform	Perl formats
perlobj	Perl objects
perltie	Perl objects hidden behind simple variables
perldbmfilter	Perl DBM filters
perlipc	Perl interprocess communication
perlfork	Perl fork() information
perlnumber	Perl number semantics
perlthrtut	Perl threads tutorial
perlothrtut	Old Perl threads tutorial
perlport	Perl portability guide
perllocale	Perl locale support
perluniintro	Perl Unicode introduction
perlunicode	Perl Unicode support
perlebcdic	Considerations for running Perl on EBCDIC platforms
perlsec	Perl security
perlmod	Perl modules: how they work

perlmodlib perlmodstyle	Perl modules: how to write and use Perl modules: how to write modules with style
perlmodinstall perlnewmod	Perl modules: how to install from CPAN Perl modules: preparing a new module for distribution
perlutil	utilities packaged with the Perl distribution
perlcompile	Perl compiler suite intro
perlfilter	Perl source filters

Internals and C Language Interface

	perlembed	Perl ways to embed perl in your C or C++ application
	perldebguts	Perl debugging guts and tips
	perlxstut	Perl XS tutorial
	perlxs	Perl XS application programming interface
	perlclib	Internal replacements for standard C
library		
		functions
	perlguts	Perl internal functions for those doing
		extensions
	perlcall	Perl calling conventions from C
	perlapi	Perl API listing (autogenerated)
	perlintern	Perl internal functions (autogenerated)
	perliol	C API for Perl's implementation of IO in Layers
	perlapio	Perl internal IO abstraction interface
	perlhack	Perl hackers guide
Mis	cellaneous	
	perlbook	Perl book information

Creating and running a Perl program

3

perltodo	Perl things to do
perldoc	Look up Perl documentation in Pod format
perlhist	Perl history records
perldelta	Perl changes since previous version
perl584delta	Perl changes in version 5.8.4
perl583delta	Perl changes in version 5.8.3
perl582delta	Perl changes in version 5.8.2
perl581delta	Perl changes in version 5.8.1
perl58delta	Perl changes in version 5.8.0
perl573delta	Perl changes in version 5.7.3
perl572delta	Perl changes in version 5.7.2
perl571delta	Perl changes in version 5.7.1
perl570delta	Perl changes in version 5.7.0
perl561delta	Perl changes in version 5.6.1
perl56delta	Perl changes in version 5.6
perl5005delta	Perl changes in version 5.005
per15004delta	Perl changes in version 5.004
perlartistic	Perl Artistic License
perlgpl	GNU General Public License
Language-Specific	
perlcn	Perl for Simplified Chinese (in EUC-CN)
perljp	Perl for Japanese (in EUC-JP)
perlko	Perl for Korean (in EUC-KR)
perltw	Perl for Traditional Chinese (in Big5)
Platform-Specific	
perlaix	Perl notes for AIX
perlamiga	Perl notes for AmigaOS
perlapollo	Perl notes for Apollo DomainOS

nerlheos	Per]	notes	for	ReOS
per meus	FELL	notes	101	DEUS

perlbs2000 Perl notes for POSIX-BC BS2000

perlce	Perl	notes	for	WinCE
perlcygwin	Perl	notes	for	Cygwin
perldgux	Perl	notes	for	DG/UX
perldos	Perl	notes	for	DOS
perlepoc	Perl	notes	for	EPOC
perlfreebsd	Perl	notes	for	FreeBSD
perlhpux	Perl	notes	for	HP-UX
perlhurd	Perl	notes	for	Hurd
perlirix	Perl	notes	for	Irix
perlmachten	Perl	notes	for	Power MachTen
perlmacos	Perl	notes	for	Mac OS (Classic)
perlmacosx	Perl	notes	for	Mac OS X
perlmint	Per]	notes	for	MiNT
perlmpeix	Perl	notes	for	MPE/iX
perlnetware	Perl	notes	for	NetWare
perlos2	Perl	notes	for	OS/2
perlos390	Perl	notes	for	OS/390
perlos400	Perl	notes	for	OS/400
perlplan9	Perl	notes	for	Plan 9
perlqnx	Perl	notes	for	QNX
perlsolaris	Perl	notes	for	Solaris
perltru64	Perl	notes	for	Tru64
perluts	Per]	notes	for	UTS
perlvmesa	Per]	notes	for	VM/ESA
perlvms	Perl	notes	for	VMS
perlvos	Per]	notes	for	Stratus VOS
perlwin32	Per]	notes	for	Windows

By default, the manpages listed above are installed in the //www.usr/local/man/ directory.

Extensive additional documentation for Perl modules is available. The default configuration for perl will place this additional documentation in the <u>/usr/local/lib/perl5/man</u> directory (or else in the <u>man</u> subdirectory of the Perl library directory). Some of this additional documentation is distributed standard with Perl, but you'll also find documentation for third-party modules there.

You should be able to view Perl's documentation with your <u>man(1)</u> program by including the proper directories in the appropriate

start-up files, or in the MANPATH environment variable. To find out where the configuration has installed the manpages, type:

perl -V:man.dir

If the directories have a common stem, such as <u>/usr/local/man/man1</u> and <u>/usr/local/man/man3</u>, you need only to add that stem (<u>/usr/local/man</u>) to your <u>man(1)</u> configuration files or your MANPATH environment variable. If they do not share a stem, you'll have to add both stems.

If that doesn't work for some reason, you can still use the supplied <u>perldoc</u> script to view module information. You might also look into getting a replacement man program.

If something strange has gone wrong with your program and you're not sure where you should look for help, try the -w switch first. It will often point out exactly where the trouble is.

DESCRIPTION

Perl is a language optimized for scanning arbitrary text files, extracting information from those text files, and printing reports based on that information. It's also a good language for many system management tasks. The language is intended to be practical (easy to use, efficient, complete) rather than beautiful (tiny, elegant, minimal).

Perl combines (in the author's opinion, anyway) some of the best features of C, **sed**, **awk**, and **sh**, so people familiar with those languages should have little difficulty with it. (Language historians will also note some vestiges of **csh**, Pascal, and even BASIC-PLUS.) Expression syntax corresponds closely to C expression syntax. Unlike most UNIX utilities, Perl does not arbitrarily limit the size of your data-if you've got the memory, Perl can slurp in your whole file as a single string. Recursion is of unlimited depth. And the tables used by hashes (sometimes called "associative arrays") grow as necessary to prevent degraded performance. Perl can use sophisticated pattern matching techniques to scan large amounts of data quickly. Although optimized for scanning text, Perl can also deal with binary data, and can make dbm files look like hashes. Setuid Perl scripts are safer than C programs through a dataflow tracing mechanism that prevents many stupid security holes.

If you have a problem that would ordinarily use **sed** or **awk** or **sh**, but it exceeds their capabilities or must run a little faster, and you don't want to write the silly thing in C, then Perl may be for you. There are also translators to turn your **sed** and **awk** scripts into Perl scripts.

But wait, there's more...

Begun in 1993 (see perlhist), Perl version 5 is nearly a complete rewrite that provides the following additional benefits:

• modularity and reusability using innumerable modules

Described in perlmod, perlmodlib, and perlmodinstall.

• embeddable and extensible

Described in perlembed, perlxstut, perlxs, perlcall, perlguts, and xsubpp.

roll-your-own magic variables (including multiple simultaneous DBM implementations)

Described in perltie and AnyDBM_File.

- subroutines can now be overridden, autoloaded, and prototyped
 Described in perlsub.
- arbitrarily nested data structures and anonymous functions Described in perlreftut, perlref, perldsc, and perllol.
- object-oriented programming

Described in perlobj, perlboot, perltoot, perltooc, and

3

perlbot.

support for light-weight processes (threads)

Described in perlthrtut and threads.

- support for Unicode, internationalization, and localization
 Described in perluniintro, perllocale and Locale::Maketext.
- · lexical scoping

Described in perlsub.

• regular expression enhancements

Described in perlre, with additional examples in perlop.

enhanced debugger and interactive Perl environment, with integrated editor support

Described in perldebtut, perldebug and perldebguts.

• POSIX 1003.1 compliant library

Described in POSIX.

Okay, that's <u>definitely</u> enough hype.

AVAILABILITY

Perl is available for most operating systems, including virtually all UNIX-like platforms. See "Supported Platforms" in perlport for a listing.

ENVIRONMENT

See perlrun.

AUTHOR

PerlClass.com for ACT Students 20-23 Feb 2007

Larry Wall <larry@wall.org>, with the help of oodles of other folks.

If your Perl success stories and testimonials may be of help to others who wish to advocate the use of Perl in their applications, or if you wish to simply express your gratitude to Larry and the Perl developers, please write to perl-thanks@perl.org .

FILES

"@INC"

locations of perl libraries

SEE ALSO

a2p	awk to perl transla	tor
s2p	sed to perl transla	tor
http:/	/www.perl.com/	the Perl Home Page
http:/	/www.cpan.org/	the Comprehensive Perl Archive
http://	/www.perl.org/	Perl Mongers (Perl user groups)

DIAGNOSTICS

The "use warnings" pragma (and the -w switch) produces some lovely diagnostics.

See peridiag for explanations of all Peri's diagnostics. The "use diagnostics" pragma automatically turns Peri's normally terse warnings and errors into these longer forms.

Compilation errors will tell you the line number of the error, with an indication of the next token or token type that was to be examined. (In a script passed to Perl via -e switches, each -e is counted as one line.)

Setuid scripts have additional constraints that can produce error messages such as "Insecure dependency". See perlsec.

Did we mention that you should definitely consider using the -w switch?

BUGS

The -w switch is not mandatory.

3

Perl is at the mercy of your machine's definitions of various operations such as type casting, <u>atof()</u>, and floating-point output with <u>sprintf()</u>.

If your stdio requires a seek or eof between reads and writes on a particular stream, so does Perl. (This doesn't apply to <u>sysread()</u> and <u>syswrite()</u>.)

while none of the built-in data types have any arbitrary size limits (apart from memory size), there are still a few arbitrary limits: a given variable name may not be longer than 251 characters. Line numbers displayed by diagnostics are internally stored as short integers, so they are limited to a maximum of 65535 (higher numbers usually being affected by wraparound).

You may mail your bug reports (be sure to include full configuration information as output by the myconfig program in the perl source tree, or by "perl -V") to perlbug@perl.org . If you've succeeded in compiling perl, the **perlbug** script in the <u>utils/</u> subdirectory can be used to help mail in a bug report.

Perl actually stands for Pathologically Eclectic Rubbish Lister, but don't tell anyone I said that.

NOTES

The Perl motto is "There's more than one way to do it." Divining how many more is left as an exercise to the reader.

The three principal virtues of a programmer are Laziness, Impatience, and Hubris. See the Camel Book for why.

perl v5.8.5	2005-12-21	PERL(1)
-------------	------------	---------

As you can see, there is a lot of documentation included with Perl.

3.3 Using the editor

A Perl script is just a normal text file, which means that you can edit it using a normal text editor.

The system you are using has several editors available for your use, including **vi**, **pico**, or its work-alike **nano** and others. Those who are not already familiar with **vi** should probably use **pico**, as it has a simpler interface. If you're an **emacs** user, sorry, feel free to use it, but the instructor isn't inclined to support **emacs**.

To edit a file using pico, type:

\$ pico filename

(Note that the dollar sign is your UNIX/Linux command line prompt - you don't have to type it.)

To edit a file using vi, type:

\$ vi filename

For other editors, just type the name of the editor followed by the name of the file you wish to edit.

A summary of editor commands appears in Appendix B in the back of these course notes, just in case you need them.

Incidentally, Appendix C contains a guide to pronouncing ASCII characters, especially punctuation. This will help you translate perl into spoken language, for ease of communication with other programmers.

3

3.4 Our first Perl program

We're about to create our first, simple Perl script: a "hello world" program. There are a couple of things you should know in advance:

- Perl programs (or scripts --- the words are interchangeable) consist of a series of statements
- When you run the program, each statement is executed in turn, from the top of your script to the bottom. (There are two special cases where this doesn't occur, one of which --- subroutine declarations --- we'll be looking at later today)
- Each statement ends in a semi-colon
- Statements can flow over several lines
- Whitespace (spaces, tabs and newlines) are ignored most places in a Perl script.

Now, just for practice, open a file called hello.pl in your text editor. Type in the following one-line Perl program:

print "Hello, world!\n";

This one-line program calls the print function with a single parameter, the *string literal* "Hello, world!" followed by a newline character.

Save it and exit.

3.5 Running a Perl program from the command line

We can run the program from the command line by typing in:

perl hello.pl

You should see this output:

Hello, world!

This program should, of course, be entirely self-explanatory. The only thing you really need to note is the n ("backslash N") which denotes a new line.

3

3.6 The "shebang" line

So what if we want to run our program from the command line without having to type in the name of the Perl interpreter first?

You can make a file executable by typing:

```
$ chmod +x hello.pl
```

at the command line. (For more information about the **chmod** command, type **man chmod**).

In order to let the shell know what to do with our program when we try to run it with ./hello.pl from the command line, we put the following line at the top of our program:

#!/usr/bin/perl

That's what we call a "shebang" line (because the # is a "hash" sign, and the ! is referred to as a "bang", hence "hashbang" or "shebang"). It tells the system what to use to interpret our script. Of course, if the Perl interpreter were somewhere else on our system, we'd have to change the shebang line to reflect that.

3.7 Comments

Incidentally, comments in Perl start with a hash sign (#), either on a line on their own or after a statement. Anything after a hash is a comment.

```
# This is a hello world program
print "Hello, world!\n";  # print the message
```

3

3.8 Command line options

Perl has a number of command line options, which you can specify on the command line by typing **perl** options hello.pl or which you can include in the shebang line. Let's say you want to use the -w command line option to turn on warnings:

```
#!/usr/bin/perl -w
```

(Incidentally, it's always a good idea to turn on warnings while you're developing something.)

ADVANCED

Setting the special variable *s*^w to a true value will locally disable warnings (i.e. in the current block).

RI FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	3	35-38	
Camel 2 nd	6	330-337	"Switches"
Camel 3 rd	19	486-505	
perldoc	perlrun		
Cookbook 2 nd			
Learning 3 rd	2	26-27	
Learning 4 th			

3.9 Chapter summary

Here's what you know about Perl's operation and syntax so far:

- Perl programs typically start with a "shebang" line
- statements (generally) end in semicolons
- statements may span multiple lines; it's only the semicolon that ends a statement
- comments are indicated by a hash (#) sign. Anything after a hash sign on a line is a comment.
- \n is used to indicate a new line
- whitespace is ignored almost everywhere
- · command line arguments to Perl can be indicated on the shebang line
- the -w command line argument turns on warnings

Chapter 4: Perl variables

In this chapter...

In this section we will explore Perl's three main variable types --scalars, arrays, and hashes --- and learn to assign values to them, retrieve the values stored in them, and manipulate them in certain ways.

4.1 What is a variable?

A variable is a place where we can store data. Think of it like a pigeonhole with a name on it indicating what data is stored in it.

The Perl language is very much like human languages in many ways, so you can think of variables as being the "nouns" of Perl. For instance, you might have a variable called "total" or "employee".

4.2 Variable names

Variable names in Perl may contain alphanumeric characters in upper or lower case, and underscores. A variable name may not start with a number, though - that means something special, which we'll encounter later. Likewise, variables that start with anything non-alphanumeric are also special, and we'll discuss that later, too.

It's standard Perl style to name variables in lower case, with underscores separating words in the name. For instance, employee_number. Upper case is usually used for constants, for instance LIGHT_SPEED or PI. Following these conventions will help make your Perl more maintainable and more easily understood by others.

Lastly, variable names all start with a punctuation sign depending on what sort of variable they are:

Variable type	Starts with	Pronounced	
Scalar	\$	dollar	
Array	Q	at	
Hash	ę	Percent	

Table 4-1. Variable punctuation

(Don't worry if those variable type names don't mean anything to you. We're about to cover it.)

4.3 Variable scoping and the strict pragma

Many programming languages require you to "pre-declare" variables -- that is, say that you're going to use them before you use them. Variables can either be declared as global (that is, they can be used anywhere in the program) or local (they can only be used in the same part of the program in which they were declared).

In Perl, it is not necessary to declare your variables before you begin. You can summon a variable into existence simply by using it, and it will be globally available to any routine in your program. If you're used to programming in C or any of a number of other languages, this may seem odd and even dangerous to you. This is, in fact, the case.

4.3.1 Arguments in favour of strictness

- avoids accidental creation of unwanted variables when you make a typing error
- avoids scoping problems, for instance when a subroutine uses a variable with the same name as a global variable
- · allows for warnings if values are assigned to variables and never used

4.3.2 Arguments against strictness

- takes a while to get used to, and may slow down development until it becomes instinctual
- enforces a nasty, fascist style of coding which isn't nearly as much fun

Sometimes a little bit of fascism is a good thing, like when you want the trains to run on time. Because of this, Perl lets you turn strictness on if you want it, using something called the *strict pragma*. A pragma, in Perl-speak, is a set of rules for how your code is to be dealt with.

RIFM!			
Src	Chap	Pgs	#
Nutshell 2 nd	8	335-336	
Camel 2 nd	7	500	
Camel 3 rd	4	137-138	
perldoc	strict		
Cookbook 2 nd			
Learning 3 rd	В	289	
Learning 4 th			

4.4 Using the strict pragma

In the interests of bug-free code and teaching better Perl style, we're going to use the strict pragma throughout this training course. Here's how it's invoked:

```
#!/usr/bin/perl -w
```

```
use strict;
```

That typically goes at the top of your program, just under your shebang line and introductory comments.

Once we use the strict pragma, we have to explicitly declare new variables using my. You'll see this in use below, and it will be discussed again later when we talk about blocks and subroutines.

Try running the program exercises/strictfail.pl and see what happens. What needs to be done to fix it? Try it and see if it works. By the way, get used to this error message - it's one of the most common Perl programming mistakes, though it's easily fixed.

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	4 5	74 117	
Camel 2 nd	3	189	
Camel 3 rd	4	130-136	
perldoc	-f my perlsub		
Cookbook 2 nd	10	376-376	
Learning 3 rd	4	67	
Learning 4 th			

4.5 Scalars

The simplest form of variable in Perl is the scalar. A scalar is a single item of data such as:

- Arthur
- · Just Another Perl Hacker
- 42
- · 0.000001
- 3.27e17

Here's how we assign values to scalar variables:

```
my $name = "Arthur";
my $whoami = 'Just Another Perl Hacker';
my $meaning_of_life = 42;
my $number_less_than_1 = 0.000001;
my $very_large_number = 3.27e17; # 3.27 by 10 to the power of 17
```

ADVANCED

There are other ways to assign things apart from the = operator, too. They're covered on pages 92-93 of the Camel.

As you can see, a scalar can be text of any length, and numbers of any precision (machine dependent, of course). Perl magically converts between them when it needs to. For instance, it's quite legal to say:

```
# adding an integer to a floating point number
my $sum = $meaning_of_life + $number_less_than_1;
# here we're putting the int in the middle of a string we
# want to print
print "$name says, 'The meaning of life is $meaning_of_life.'\n";
```

This may seem extraordinarily alien to those used to strictly typed languages, but believe it or not, the ability to transparently convert between variable types is one of the great strengths of Perl. Some people say that it's also one of the great weaknesses.

ADVANCED

You can explicitly cast scalars to various specific data types. Look up int() on page 180 of the camel, for instance.

4.6 Double and single quotes

RTFM!			
Src	Chap	Pgs	#
Nutshell 2 nd	4	45-47	String interpolation
Camel 2 nd		52 41	Input Operators Pick your own quotes
Camel 3 rd	2	60-65	String literals
perldoc	perldata perlop		Scalar values Quote and Quote-like operators
Cookbook 2 nd	1	3	
Learning 3 rd	2	23-24	
Learning 4 th			

While we're here, let's look at the assignments above. You'll see that some have double quotes, some have single quotes, and some have no quotes at all.

In Perl, quotes are required to distinguish strings from the language's reserved words or other expressions. Either type of quote can be used, but there is one important difference: double quotes can include other variable names inside them, and those variables will then be interpolated - as in the last example above - while single quotes do not interpolate.

```
# single quotes don't interpolate...
my $price = '$9.95';
# double quotes interpolate...
my $invoice_item = "24 widgets at $price each\n";
print $invoice_item;
```

The above example is available in your directory as exercises/interpolate.pl so you can experiment with different kinds of quotes.

Note that special characters such as the n newline character are only available within double quotes. Single quotes will fail to expand these special characters just as they fail to expand variable names.

When using either type of quotes, you must have a matching pair of opening and closing quotes. If you want to include a quote mark in the actual quoted text, you can escape it by preceding it with a backslash:

```
print "He said, \"Hello!\"\n";
```

You can also use a backslash to escape other special characters such as dollar signs within double quotes:

print "The price is \\$300\n";

To include a literal backslash in a double-quoted string, use two backslashes: \\

4.6.1 Exercises

- 1. Write a script which sets some variables:
 - a. your name
 - b. your street number
 - c. your favorite colour
- 2. Print out the values of these variables using double quotes for variable interpolation
- 3. Change the quotes to single quotes. What happens?
- 4. Write a script which prints out C:\WINDOWS\SYSTEM\ twice -- once using double quotes, once using single quotes. How do you have to escape the backslashes in each case?

You'll find answers to the above in exercises/answers/scalars.pl.
4.7 Arrays

If you think of a scalar as being a singular thing, arrays are the plural form. Just as you have a flock of sheep or a bunch of bankers, you can have an array of scalars.

An array is a list of (usually related) scalars all kept together. Arrays start with an @ (at sign), and are initialized thus:

As you can see, arrays can contain any kind of scalars. They can have just about any number of elements, too, without needing to know how many before you start. *Really* any number - tens or hundreds of thousands, if you've got the memory.

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	4	47-49	
Camel 2 nd	1 2	6 47-49	
Camel 3 rd	1 2	8-10 72-76	
perldoc	perldata		
Cookbook 2 nd	4	110-149	
Learning 3 rd	3	40-55	
Learning 4 th			

So if we don't know how many items there are in an array, how can we find out? Well, there are a couple of ways.

First of all, Perl's arrays are indexed from zero. We can access individual elements of the array like this:

print	<pre>\$fruits[0];</pre>	#	prints	"apples	5''	
print	<pre>\$random_scalars[2];</pre>	#	prints	"willy	the	wombat"

Wait a minute, why are we using dollar signs in the example above, instead of at signs? The reason is this: we only want a scalar back, so we show that we want a scalar. There's a useful way of thinking of this, which is explained in chapter 1 of the Camel: if scalars are the singular case, then the dollar sign is like the word "the" - "the name", "the meaning of life", etc. The @ sign on an array, or the % sign on a hash, is like saying "those" or "these" - "these fruit", "those magic numbers". However, when we only want one element of the array, we'll be saying things like "the first fruit" or "the last magic number" - hence the scalar-like dollar sign.

If we wanted what we call an *array slice* we could say:

```
@fruits[1,2,3];  # oranges, guavas, passionfruit
@magic_numbers[0..1]; # 23, 42
```

You just learned something new, by the way: the ... ("dot dot") range operator (see pages 90-91 of your Camel or **perldoc perlop**) which creates a temporary list of numbers between the two you specify - in this case 0 and 1, but it could have been 1 and 100 if we'd had an array big enough to use it on. You'll run into this operator again and again, so remember it.

Another thing you can do with arrays is insert them into a string, the same as for scalars:

```
print "My favorite fruits are @fruits\n";  # whole array
print "Two types of fruit are @fruits[0,2]";  # array slice
```

Returning to the point, how do we find the last element in an array? Well, there's a special variable called *\$#array* which is the index of the last element, so you can say:

```
@fruit[0..$#fruit];
```

and you'll get the whole array. If you print *s#fruit* you'll find it's 4, which is

not the same as the number of elements - 5. Remember that it's the *index of the last element* and that the index *starts at zero*, so you have to add one to it to find out how many elements in the array.

But wait! There's More Than One Way To Do It - and an easier way, at that. If you evaluate the array in a scalar context - that is, do something like this:

my \$fruit_count = @fruits;

... you'll get the number of elements in the array.

There's more than two ways to do it, as well - scalar(@fruits) and int(@fruits) will also tell us how many elements there are in the array.

ADVANCED

Using **\$count = scalar** @fruits is the clearest way to express "how many are in fruits?" and is considered a best practice.

4.7.1 A quick look at context

There's a term you've heard used just recently but which hasn't been explained: *context*.

All Perl expressions are evaluated in a context. The two main contexts are:

- scalar context, and
- list context

Here's an example of an expression which can be evaluated in either context:

my	\$howmany = @array;	#	scalar	context
my	@newarray = @array;	#	list co	ontext

If you look at an array in a scalar context, you'll see how many elements it has; if you look at it in list context, you'll see the contents of the array itself.

4.7.2 What's the difference between a list and an array?

Not much, really. A list is just an unnamed array. Here's a demonstration of the difference:

```
# printing a list of scalars
print ("Hello", " ", $name, "\n");
# printing an array
@hello = ("Hello", " ", $name, "\n");
print @hello;
```

If you come across something that wants a LIST, you can either give it the elements of list as in the first example above, or you can pass it an array by name. If you come across something that wants an ARRAY, you have to actually give it the name of an array.

4.7.3 Exercises

- 1. Create an array of your friends' names
- 2. Print out the first element
- 3. Print out the last element
- 4. Print out the array from within a double-quoted string using variable interpolation
- 5. Print out an array slice of the 2nd to 4th items using variable interpolation

Answers to the above can be found in exercises/answers/arrays.pl

4.7.4 Advanced exercises

- 1. Print the array without putting quotes around its name. What happens?
- 2. Set the special variable \$, to something appropriate and try the previous step again (see page 132 of your Camel for this variable's documentation)
- 3. What happens if you have a small array and then you assign a value to \$array[1000]?

Answers to the above can be found in exercises/answers/arrays_advanced.pl

4.8 Hashes

A hash is a two-dimensional array which contains keys and values. Instead of looking up items in a hash by an array index, you can look up values by their keys.

Src	Chap	Pgs	#		
Nutshell 2 nd	4	49			
Camel 2 nd	1 2	7-8 50			
Camel 3 rd	1 2	10-12 76-78			
perldoc	perlldata				
Cookbook 2 nd	5	150-178			
Learning 3 rd	5	73-85			
Learning 4 th					

4.8.1 Initialising a hash

Hashes are initialized in exactly the same way as arrays, with a comma separated list of values:

```
my %monthdays = ("January", 31, "February", 28, "March", 31, ...);
```

Of course, there's more than one way to do it:

my	%monthdays = (
	"January"	=>	31,
	"February"	=>	28,
	"March"	=>	31,

...

The spacing in the above example is commonly used to make hash assignments more readable.

The => operator is syntactically the same as the comma, but is used to distinguish hashes more easily from normal arrays. Also, you don't need to put quotes on the item which comes immediately before the => operator:

my	%monthdays = (
	January	=>	31,
	February	=>	28,
	March	=>	31,
	#		
):			

4.8.2 Reading hash values

You get at elements in a hash by using the following syntax:

```
print $monthdays{"January"};  # prints 31
```

Again you'll notice the use of the dollar sign, which you should read as "the monthdays belonging to January".

4.8.3 Adding new hash elements

You can also create elements in a hash on the fly:

```
my %monthdays = ();
$monthdays{"January"} = 31;
$monthdays{"February"} = 28;
...
```

4.8.4 Other things about hashes

- · Hashes have no internal order
- There is no equivalent to *s#array* to get the size of a hash

);

• However, there are functions such as each(), keys() and values() which will help you manipulate hash data. We look at these later, when we deal with functions.

ADVANCED

You may like to look up the following functions which related to hashes: keys(), values(), each(), delete(), exists(), and defined().

4.8.5 What's the difference between a hash and an associative array?

Back in the days of Perl version 4 (and earlier), hashes were called associative arrays. The name "hash" is now preferred because it's much quicker to type. If you consider all the times that hashes are talked about in the newsgroup complang.perl.misc (news:comp.lang.perl.misc) and other Perl newsgroups, the renaming of associative arrays to hashes has resulted in a major saving of bandwidth.

4.8.6 Exercises

- 1. Create a hash of people and something interesting about them
- 2. Print out a given person's interesting fact
- 3. Change an person's interesting fact
- 4. Add a new person to the hash
- 5. What happens if you try to print an entry for a person who's not in the hash?

Answers to these exercises are given in exercises/answers/hash.pl

4.9 Special variables

Perl has many special variables. These are used to set or retrieve certain values which affect the way your program runs. For instance, you can set a special variable to turn interpreter warnings on and off, or read a special variable to find out the command line arguments passed to your script.

Special variables can be scalars, arrays, or hashes. We'll look at some of each kind.

RT FM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	4	53-59		
Camel 2 nd	2 7	127-140 403		
Camel 3 rd	28 32	653-676 884		
perldoc	perlvar English		English provides friendlier names for special variables	
Cookbook 2 nd				
Learning 3 rd	3	49	<pre>\$_ quickly</pre>	
Learning 4 th				

4.10 The first special variable, \$_____

The first special variable, and possibly the one you'll encounter most often, is called \$ ("dollar-underscore"), and it represents the current thing that your Perl script's working with - often a line of text or an element of a list or hash. It can be set explicitly, or it can be set implicitly by certain looping constructs (which we'll look at later).

The special variable \$ is often the default argument for functions in Perl. For instance, the print() function defaults to printing \$

\$_ = "Hello, world!\n";
print;

If you can think of Perl variables as being "nouns", then \mathfrak{s}_{i} is the pronoun "it".

4.10.1.1 Exercises

1. Set $_$ to a string like "Hello, world", then print it out by using the print() command's default argument

The answers to the above exercise are in exercises/answers/scalars2.pl.

4.11 @ARGV - a special array

Perl programs accept arbitrary arguments or parameters from the command line, like this:

perl printargs.pl foo bar baz

This passes "foo", "bar" and "baz" as arguments into our program, where they end up in an array called @ARGV. Try this script, which you'll find in your directory. It's called exercises/printargs.pl.

#!/usr/bin/perl -w

print "@ARGV\n";

To run the script, type:

% exercises/printargs.pl foo bar baz

You should see "foo bar baz" printed out.

4.11.1.1 Exercises

1. Modify your earlier array-printing script to print out the script's command line arguments instead of the names of your friends. Call your script by typing ./scriptname.pl firstarg secondarg thirdarg or similar.

The answers to the above exercise is in exercises/answers/argv.pl

4.12 %ENV - a special hash

Just as there are special scalars and arrays, there is a special hash called **%ENV**. This hash contains the names and values of environment variables. To view these variables under UNIX, simply type **env** on the command line.

4.12.1.1 Exercises

1. A user's home directory is stored in the environment variable HOME. Print out your own home directory.

The answer to the above can be found in exercises/answers/env.pl

4.13 Chapter summary

- Perl variable names typically consist of alphanumeric characters and underscores. Lower case names are used for most variables, and upper case for global constants.
- The statement use strict; is used to make Perl require variables to be predeclared and to avoid certain types of programming errors.
- There are three types of Perl variables: scalars, arrays, and hashes.
- Scalars are single items of data and are indicated by a dollar sign (\$) at the beginning of the variable name.
- Scalars can contain strings, numbers, etc
- Strings must be delimited by quote marks. Using double quote marks will allow you to interpolate other variables and meta-characters such as \n (newline) into a string. Single quotes do not interpolate.
- Arrays are one-dimensional lists of scalars and are indicated by an at sign (@) at the beginning of the variable name.
- Arrays are initialised using a comma-separated list of scalars inside round brackets.
- · Arrays are indexed from zero
- Item *n* of an array can be accessed by using <code>\$arrayname[n]</code>
- The index of the last item of an array can be accessed by using \$#arrayname.
- The number of elements in an array can be found by interpreting the array in a scalar context, eg my sitems = @array;
- Hashes are two-dimensional arrays of keys and values, and are indicated by a percent sign (%) at the beginning of the variable name.
- Hashes are initialised using a comma-separated list of scalars inside curly brackets. Whitespace and the => operator (which is syntactically identical to the comma) can be used to make hash assignments look neater.
- The value of a hash item whose key is foo can be accessed by using \$hashname{foo}
- Hashes have no internal order
- $\$ s_ is a special variable which is the default argument for many Perl functions and operators

- The special array @ARGV contains all command line parameters passed to the script
- The special hash <code>%ENV</code> contains information about the user's environment.

Chapter 5: Operators and functions

In this chapter...

In this chapter, we look at some of the operators and functions which can be used to manipulate data in Perl. In particular, we look at operators for arithmetic and string manipulation, and many kinds of functions including functions for scalar and list manipulation, more complex mathematical operations, type conversions, dealing with files, etc.

5.1 What are operators and functions?

Operators and functions are routines that are built into the Perl language to do stuff.

The difference between operators and functions in Perl is a very tricky subject. There are a couple of ways to tell the difference:

- Functions usually have all their parameters on the right hand side
- Operators can act in much more subtle and complex ways than functions
- Look in the documentation if it's in **perldoc perlop**, it's an operator; if it's in **perldoc perlfunc**, it's a function. Otherwise, it's probably a subroutine.

The easiest way to explain operators is to just dive on in, so here we go...

RTFM!			
Src	Chap	Pgs	#
Nutshell 2 nd	4	60 - 65	
Camel 2 nd	2	76 - 94	
Camel 3 rd	3	86 - 110	
perldoc	perlop		
Cookbook 2 nd			
Learning 3 rd	2	28 - 34	
Learning 4 th			

5.2 Arithmetic operators

Arithmetic operators can be used to perform arithmetic operations on variables or constants. The commonly used ones are:

Operator	Example	Description
+	\$a + \$b	Addition
-	\$a - \$b	Subtraction
*	\$a * \$b	Multiplication
/	\$a / \$b	Division
00	\$a % \$b	Modulus (remainder when a is divided by b_{2b} , eg 11 % 3 = 2)
* *	\$a ** \$b	Exponentiation (\$a to the power of \$b)

Table 5-5. Arithmetic operators

ADVANCED

Just like in C, there are some short cut arithmetic operators:

\$a	+=	1;	#	same	as	\$a	=	\$a	+	1
\$a	-=	3;	#	same	as	\$a	=	\$a	-	3
\$a	*=	42;	#	same	as	\$a	=	\$a	*	42

(In fact, you can extrapolate the above with just about any operator - see page 17 of the Camel for more about this)

You can also use a_{a++} and a_{a----} if you're familiar with such things. $a_{a++}a$ and $a_{a---}a$ are also valid, but they do some slighty different things and you won't need them today (but you can read about them on pages 17 to 18 of the Camel if you are sufficiently interested).

5.3 String operators

Just as we can add and multiply numbers, we can also do similar things with strings:

Table 5-5. String operators

Operator	Example	Description
	\$a . \$b	Concatenation (puts \$a and \$b together as one string)
х	\$a x \$b	Repeat (repeat \$a \$b times eg "foo" x 3 gives us "foofoofoo"

```
my $fullname = $first_name . $mid_initial . $last_name;
my $line = '-' x 80;
my $ruler = $line . "\n";
```

5.3.1 Exercises

- 1. Calculate the cost of 18 widgets at \$37.00 each and print the answer (Answer: exercises/answers/widgets.pl)
- 2. Print out a line of dashes without using more than one dash in your code (except for the -w). (Answer: exercises/answers/dashes.pl)
- 3. Use exercises/operate.pl to practice using arithmetic and string operators.

5.4 File operators

We can use file test operators to test various attributes of files and directories:

Operator	Example	Description
-e	-e \$a	Exists - does the file exist?
-r	-r \$a	Readable - is the file readable?
-w	-w \$a	Writable - is the file writable?
-d	-d \$a	Directory - is it a directory?
-f	-f \$a	File - is it a normal file?
- T	-T \$a	Text - is the file a text file?

 Table 5-5. File test operators

```
if (-e "~/.forward"} {
```

```
print "your email is being forwarded somewhere else";
}
```

```
unless (-w $log_file) {
    print "can't write to $log_file\n";
}
if (-T "perl.exe") {
    print "your perl.exe is a text file!\n";
}
```

5.5 Other operators

You'll encounter all kinds of other operators in your Perl career, and they're all described in the Camel from page 76 onwards. We'll cover them as they become necessary to us -- you've already seen operators such as the assignment operator (=), the => operator which behaves a bit like the comma operator, and so on.



5.6 Functions

A function is like an operator - and in fact some functions double as operators in certain conditions - but with the following differences:

- longer names
- can take any kinds of arguments
- arguments always come *after* the function name

The only real way to tell whether something is a function or an operator is to check the perlop and perlfunc manual pages and see which it appears in.

RTFM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	5	92 - 146		
Camel 2 nd	1 3	8 141-242	Verbs	
Camel 3 rd	29	677-830		
perldoc	perlfunc			
Cookbook 2 nd				
Learning 3 rd	4	56		
Learning 4 th				

5.6.1 Types of arguments

Functions typically take the following kind of arguments:

SCALAR -- Any scalar variable - 42, "foo", or \$a

LIST -- Any named or unnamed list (remember that a named list is an array)

ARRAY -- A named array; usually results in the array being modified

HASH -- Any named or unnamed hash

PATTERN -- A pattern to match on - we'll talk more about these later on, in

Regular Expressions

FILEHANDLE -- A filehandle indicating a file that you've opened or one of the pseudo-files that is automatically opened, such as STDIN, STDOUT, and STDERR

There are other types of arguments, but you're not likely to need to deal with them in this module.

5.6.2 Return values

Just as a function can take arguments of various kinds, they can return various things for you to use - though they don't have to, and you don't have to use them if you don't want.

If a function returns a scalar, and we want to use it, we can say something like:

```
my $age = 29.75;
my $years = int($age);
```

and y_{gars} will be assigned the returned value of the int() function when given the argument gage - in this case, 29, since int() truncates instead of rounding.

If we just wanted to do something to a variable and didn't care what value was returned, we could just say:

```
my $input = <STDIN>;
chomp($input);
```

While we're at it, you should also know that the brackets on functions are optional if it's not likely to cause confusion. What's likely to cause confusion varies from one person to the next, but it's a pretty safe bet to use brackets as much as possible when you're starting out, and then drop them off if you see that other people are usually doing it. Seriously. You can learn a lot about Perl style by looking at other people's code, especially code found on CPAN or given as examples in Perl books, newsgroups, etc.

5.7 More about context

Many different functions and operators behave differently depending on whether they're called in *scalar context* or *list context*. Each one will be noted in its documentation, either in the Camel or in the manual pages.

Here are some Perl operators and functions that care about context:

What?	Scalar context	List context Reverses the order of the elements in an array	
reverse()	Reverses characters in a string		
each()	Returns the next key in a hash	Returns a two-element list consisting of the next key and value pair in a hash	
gmtime() and localtime()	Returns the time as a string in common format	Returns a list of second, minute, hour, day, etc	
keys()	Returns the number of keys (and hence the number of elements) in a hash	Returns a list of all the keys in a hash	
readdir()	Returns the next filename in a directory, or undef if there are no more	Returns a list of all the filenames in a directory	

 Table 5-4. Context-sensitve functions

There are many other cases where an operation varies depending on context. Take a look at the notes on context at the start of **perldoc perlfunc** to see the official guide to this: "anything you want, except consistency".

You can also use **perldoc -f** *functionname* to get the documentation for just a single function.

5.8 String manipulation

5.8.1.1 Finding the length of a string

The length of a string can be found using the <code>length()</code> function:

```
#!/usr/bin/perl -w
use strict;
my $string = "This is my string";
print length($string);
```

5.8.1.2 Case conversion

You can convert Perl strings from upper case to lower case, or vice versa, using the lc() and uc() functions, respectively.

```
#!/usr/bin/perl -w
print lc("Hello, World!");  # prints "hello, world!"
print uc("Hello, World!");  # prints "HELLO, WORLD!"
```

The lcfirst() and ucfirst() functions can be used to change only the first letter of a string.

```
#!/usr/bin/perl -w
print lcfirst("Hello, World!");  # prints "hello, World!"
print lcfirst(uc("Hello, World!"));  # prints "hELLO, WORLD!"
```

Notice how, in the last line of the example above, the lcfirst() operates on the result of the uc() function.

5.8.1.3 chop() and chomp()

The chop() function removes the last character of a string and returns that character.

```
#!/usr/bin/perl -w
use strict;
```

```
my $char = chop("Hello");  # $char is now equal to "o"
my $string = "Goodbye";
$char = chop $string;
print $char . "\n";  # "e"
print $string . "\n";  # "Goodby"
```

The chomp() works similarly, but *only* removes the last character if it is a newline. This is very handy for removing extraneous newlines from user input.

5.8.1.4 String substitutions with substr()

The substr() function can be used to return a portion of a string, or to change a portion of a string.

```
#!/usr/bin/perl -w
use strict;
my $string = "Hello, world!";
print substr($string, 0, 5);  # prints "Hello"
substr($string, 0, 5) = "Greetings";
print $string;  # prints "Greetings, world!"
```

5.9 Numeric functions

There are many numeric functions in Perl, including trig functions and functions for dealing with random numbers. These include:

- abs() (absolute value)
- cos(), sin(), and atan2()
- exp() (exponentiation)
- log() (logarithms)
- rand() and srand() (random numbers)
- sqrt() (square root)

5.10 Type conversions

The following functions can be used to force type conversions (if you really need them):

oct() turns an octal number into its decimal equivalent.

int() truncates a number. It does not round.

hex() turns a hexadecimal number into its decimal equivalent.

chr() turns a decimal number into its character equivalent

ord() turns a character into its decimal equivalent

scalar() provides a scalar context.

```
my $fatty_decimal = hex("BEEF");
my $secret_agent = oct(007);
my $backspace = ord(127); # ASCII BS
my $m = asc('m');
```

5.11 Manipulating lists and arrays

5.11.1 Stacks and queues

Stacks and queues are special kinds of lists.

A stack can be thought of like a stack of paper on a desk. Things are put onto the top of it, and taken off the top of it.

A queue, on the other hand, has things added to the end of it and taken out of the start of it. Queues are also referred to as "FIFO" lists (for "First In, First Out").

We can simulate stacks and queues in Perl using the following functions:

- push() -- add items to the end of a list
- pop() -- remove items from the end of a list
- shift() -- remove items from the start of a list
- unshift() -- add items to the start of a list

A queue can be created by pushing items onto the end of a list and shifting them off the front.

A stack can be created by pushing items on the end of a list and popping them off.

```
# act like a stack
push(@stack,"item","item 2");
my $item = pop(@stack);
# act like a queue
push(@queue,"1","2","3","4","5,"6","7","8");
my $item = shift(@queue); # get 1, 2..8 left
my $newitem = shift(@queue); # get 2, 3..8 left
push(@queue,"9","10","11"); # add three more
my $thirditem = shift(@queue); # get 3, 4..11 left
```

unshift(@queue,\$thirditem) # put 3 back at the top of the queue

5.11.2 Sorting lists

The sort() function, when used on a list, returns a sorted version of that list. It *does not* sort the list in place.

The reverse() function, when used on a list, returns the list in reverse order. It *does not* reverse the list in place.

```
#!/usr/bin/perl -w
my @list = ("a", "z", "c", "m");
my @sorted = sort(@list);
my @reversed = reverse(sort(@list));
```

5.11.3 Converting lists to strings, and vice versa

The join() function can be used to join together the items in a list into one string. Conversely, split() can be used to split a string into elements for a list. To fully appreciate split() will have to wait for regular expressions, but join is straightforward:

my \$glommed_thing = join(":",\$user,\$pass,\$uid,\$gid);

5.12 Hash processing

The delete() function deletes an element from a hash.

The exists() function tells you whether a certain key exists in a hash.

The ${\tt keys}()$ and ${\tt values}()$ functions return lists of the keys or values of a hash, respectively.

```
my @keys = keys %hash;
delete $hash{getgone};
if (exists $hash{getgone}) {
    print "your Perl is sick";
}
```

5.13 Reading and writing files

The open() function can be used to open a file for reading or writing. The close() function closes a file after you're done with it.

We will cover file-related functions more in _____

5.14 Time

The time() function returns the current time in UNIX format (that is, the number of seconds since 1 Jan 1970).

The gmtime() and localtime() functions can be used to get a more friendly representation of the time, either in Greenwich Mean Time or the local time zone. Both can be used in either scalar or list context.

5.15 Exercises

These exercises range from easy to difficult. Answers are provided in the exercises directory (filenames are given with each exercise).

- 1. Create a scalar variable containing the phrase "There's more than one way to do it" then print it out in all upper-case (Answer: exercises/answers/tmtowtdi.pl)
- 2. Print a random number
- 3. Print a random item from an array (Answer: exercises/answers/quotes.pl)
- 4. Print out the third character of a word entered by the user as an argument on the command line (There's a starter script in exercises/thirdchar.pl and the answer's in exercises/answers/thirdchar.pl)
- 5. Print out the date for a week ago (the answer's in exercises/answers/lastweek.pl
- 6. Print out a sentence in reverse

a. reverse the whole sentence

b. reverse just the words

```
(Answer: exercises/answers/reverse.pl)
```

5.16 Chapter summary

- Perl operators and functions can be used to manipulate data and perform other necessary tasks
- The difference between operators and functions is blurred; most can behave in either way
- Chapter 3 of your Camel book, peridoc periop, peridoc perifunc, and peridoc -f *functionname* can be used to find out detailed information about operators and functions.
- Functions can accept arguments of various kinds
- Functions may return scalars, lists etc
- Return values may differ depending on whether a function is called in scalar or list context

Chapter 6: Conditional constructs

In this chapter...

In this section, we look at Perl's various conditional constructs and how they can be used to provide flow control to our Perl programs. We also learn about Perl's meaning of Truth and how to test for truth in various ways.

6.1 What is a block?

The simplest block is a single statement, for instance:

```
print "Hello, world!\n";
```

Sometimes you'll want several statements to be grouped together logically. That's what we call a block. A block can be executed either in response to some condition being met, or as an independent chunk of code that's given a name.

Blocks always have curly brackets ($\{and\}$) around them. In C and Java, curly brackets are optional in some cases - not so in Perl.

```
{
    $fruit = "apple";
    $howmany = 32;
    print "I'd like to buy $howmany $fruit" . "s.\n";
}
```

You'll notice that the body of the block is indented from the brackets; this is to improve readability. Make a habit of doing it.

RI FM!						
Src	Chap	Pgs	#			
Nutshell 2 nd		50-52 73-74				
Camel 2 nd	2	97				
Camel 3 rd	4	113				
perldoc	perlsyn perlsyn		Compound statements Basic BLOCKs			
Cookbook 2 nd	10	373-374				
Learning 3 rd	2 4	34-37 56-57				
Learning 4 th						
6.2 Scope

Something that needs mentioning again at this point is the concept of variable scoping. You will recall that we use the my function to declare variables when we're using the strict pragma. The my also scopes the variables so that they are local to the *current block*

Now, onto the situations in which we'll encounter blocks.

6.3 What is a conditional statement?

A conditional statement is one which allows us to test the truth of some condition. For instance, we might say "If the ticket price is less than ten dollars..." or "While there are still tickets left..."

You've almost certainly seen conditional statements in other programming languages, so we'll just assume that you get the general idea.

RTFM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	4	51-53		
Camel 2 nd	2	95-106		
Camel 3 rd	4	114-125		
perldoc	perlsyn			
Cookbook 2 nd				
Learning 3 rd	2	34-37		
Learning 4 th				

6.4 What is truth?

Conditional statements invariably test whether something is true or not. Perl thinks something is true if it doesn't evaluate to zero (0), an empty string (""), or undefined.

42	# true
0	# false
"0"	<pre># false, because perl switches it to a number when</pre>
it	
	# needs to
"wibble"	# true
\$new_variable	<pre># false (if we haven't set it to anything, it's</pre>
	<pre># undefined)</pre>

RTFM!			
Src	Chap	Pgs	#
Nutshell 2 nd			
Camel 2 nd	1	20-21	What is truth?
Camel 3 rd	1	29-30	What is truth?
perldoc			
Cookbook 2 nd			
Learning 3 rd	2	34-35	
Learning 4 th			

6.5 Comparison operators

We can compare things, and find out whether our comparison statement is true or not. The operators we use for this are:

Operator	Example	Meaning
==	\$a == \$b	Equality (same as in C and other C-like languages)
!=	\$a != \$b	Inequality (again, C-like)
<	\$a < \$b	Less than
>	\$a > \$b	Greater than
<=	\$a <= \$b	Less than or equal to
>=	\$a >= \$b	Greater than or equal to

Table 6-1. Comparison operators

If we're comparing strings, we use a slightly different set of comparison operators, as follows:

Operator	Meaning
eq	Equality
ne	Inequality
lt	Less than (in "asciibetical" order)
gt	Greater than
le	Less than or equal to
ge	Greater than or equal to

Table 6-2. String comparison operators

Some examples:

69 > 42	# true
"0" == 3 - 3	# true
'apple' gt 'banana'	<pre># false; apple is alphabetically before</pre>
	# banana
1 + 2 == "3com"	<pre># true - 3com is evaluated in numeric</pre>
	<pre># context because we used == not eq</pre>

Assigning undef to a variable name undefines it again, as does using the undef function with the variable's name as its argument.

6.5.1 Existence and Defined-ness

We can also check whether things are defined (something is defined when it's had a value assigned to it), or whether an element of a hash exists.

To find out if something is defined, use Perl's defined function. You can't just use the name of the variable because the variable can be defined an still evaluate to false - for example, if you assign it the value 0.

```
$skippy = "bush kangaroo";
if (defined($skippy)) {
        print "Skippy is defined.\n";
} else {
        print "Skippy is undefined.\n";
}
```

	RTFM!			
Src	Chap	Pgs	#	
Nutshell 2 nd	5	99		
Camel 2 nd	3	155		
Camel 3 rd	29	697		
perldoc	-f defined			
Cookbook 2 nd				
Learning 3 rd	2	38		
Learning 4 th				

To find out if an element of a hash exists, use the exists function:

```
my %animals = (
"Skippy" => "bush kangaroo",
"Flipper" => "faster than lighting",
```

```
);
if (exists($animals{"Blinky Bill"}) {
        print "Blinky Bill exists.\n";
} else {
        print "Blinky Bill doesn't exist.\n";
```

}

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	5	103	
Camel 2 nd	3	164	
Camel 3 rd	29	710	
perldoc	-f exists		
Cookbook 2 nd	5	153 - 154	
Learning 3 rd	5	83	
Learning 4 th			

One last quick example to clarify existence, definedness and truth:

```
my %miscellany = (
       "apple"
                         "red", # exists, defined, true
                    =>
                                    # exists, defined, false
       "howmany"
                   =>
                         0,
       "koala"
                         undef, # exists, undefined, false
                    =>
);
if ( exists( $miscellany{"wombat"} ) ) {  # doesn't exist
       print "Wombat exists\n";
} else {
       print "We have no wombats here.n"; # this will happen
}
```

6.5.2 Boolean logic operators

Boolean logic operators can be used to combine two or more Perl statements, either in a conditional test or elsewhere.

The short circuit operators come in two flavours: line noise, and English. Both do similar things but have different precedence. This causes great confusion. There are two ways of avoiding this: use lots of brackets, or read page 89 of the Camel book very, very carefully.

ADVANCED

Alright, if you insist: and or operators have very low precedence (i.e. they will be evaluated after all the other operators in the condition) whereas && and || have quite high precedence and may require parentheses in the condition to make it clear which parts of the statement are to be evaluated first.

English-like	C-style	Example	Result
and	& &	\$a && \$b	True if both sa and sb are
			true; acts on \$a then 1f \$a 1s
			true, goes on to act on \$b.
or	11	\$a \$b	True if either of sa and sb are
			true; acts on <i>şa</i> then if <i>şa</i> is
			false, goes on to act on \$b.

Table 6-3. Boolean logic operators

Here's how you can use them to combine conditions in a test:

```
$a = 1;
$b = 2;
$a == 1 and $b == 2  # true
```

6.5.3 Using boolean logic operators as short circuit operators

These operators aren't just for combining tests in conditional statements --- they can be used to combine other statements as well.

Here's a real, working example of the ++ short circuit operator:

open(INFILE, "input.txt") or die("Can't open input file: \$!");

What is it doing?

RTFM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	5	118		
Camel 2 nd	3	191		
Camel 3 rd	29	747		
perldoc	-f open			
Cookbook 2 nd				
Learning 3 rd	11	150 - 151		
Learning 4 th				

The && operator is less commonly used outside of conditional tests, but is still very useful. Its meaning is this: If the first operand returns true, the second will also happen. As soon as you get a false value returned, the expression stops evaluating.

(\$day eq 'Friday') and print "Have a good weekend! $\n"$;

The typing saved by the above example is not necessarily worth the loss in readability, especially as it could also have been written:

... or any of a dozen other ways. That's right, there's more than one way to do it.

The most common usage of the short circuit operators, especially ++ (or or) is to trap errors, such as when opening files or interacting with the operating system.

RTFM!				
Src	Chap	Pgs	#	
Nutshell 2 nd				
Camel 2 nd	2	89	short circuit operators	
Camel 3 rd	3	102		
perldoc				
Cookbook 2 nd				
Learning 3 rd	10	143		
Learning 4 th				

6.6 Types of conditional constructs

You'll have noticed that we snuck in something new in the last section -- the *if* construct. It probably didn't surprise you much - you'll have seen something similar in just about every programming language. (Bonus points will *not* be given for naming programming languages which have no "if" construct.)

6.6.1 if statements

The if construct goes like this:

```
if (conditional statement) {
    # BLOCK
} elsif (conditional statement) {
    # BLOCK
} else {
    # BLOCK
}
```

Both the elsif and else parts of the above are optional, and of course you can have more than one elsif. elsif is also spelt differently to other languages' equivalents - C programmers should take especial note to not use else if.

If you're testing for something negative, it can sometimes make sense to use the similar-but-opposite construct, unless.

```
unless (conditional statement) {
    # BLOCK
}
```

There is no such thing as an "elsunless" (thank the gods!), and if you find yourself using an else with unless then you should probably have written it as an if test in the first place.

There's also a shorthand, and more English-like, way to use if and unless:

```
print "We have apples\n" if $apples;
print "Yes, we have no bananas\n" unless $bananas;
```

6.6.2 while loops

We can repeat a block while a given condition is true:

```
while (conditional statement) {
    # BLOCK
}
my $hunger = 5;
while ($hunger) {
    print "Feed me!\n";
    $hunger--;
}
```

The logical opposite of this is the "until" construct:

```
my $full = 0;
until ($full) {
    print "Feed me!\n";
    $full++;
}
```

6.6.3 for and foreach

Perl has a for construct identical to C and Java:

However, since we often want to loop through the elements of an array, we have a special "shortcut" looping construct called foreach, which is similar to the construct available in some UNIX shells. Compare the following:

```
# using a for loop
for ($i = 0; $i <= $#array; $i++) {
    print $array[$i] . "\n";</pre>
```

There are some examples of foreach in exercises/foreach.pl

foreach(n..m) can be used to automatically generate a list of numbers between n and m.

We can loop through hashes easily too, using the keys function to return the keys of a hash as an list that we can use:

```
foreach $key (keys %monthdays) {
    print "There are $monthdays{$key} days in $key.\n";
}
```

We'll look at hash functions later.

6.6.4 Exercises

- 1. Set a variable to a numeric value, then create an *if* statement as follows:
 - a. If the number is less than 3, print "Too small"
 - b. If the number is greater than 7, print "Too big"
 - c. Otherwise, print "Just right"
- 2. Set two variables to your first and last names. Use an *if* statement to print out whichever of them comes first in the alphabet.
- 3. Use a while loop to print out a numbered list of the elements in an array
- 4. Now do it with a foreach loop
- 5. Now do it with a hash, printing out the keys and values for each item (hint: look up the keys function in your Camel book)

Answers are given in exercises/answers/loops.pl

6.7 Practical uses of while loops: taking input from STDIN

STDIN is the standard input stream for any UNIX program. If a program is interactive, it will take input from the user via STDIN. Many UNIX programs accept input from STDIN via pipes and redirection. For instance, the UNIX **cat** utility prints out any file it has redirected to its STDIN:

\$ cat < hello.pl</pre>

UNIX also has STDOUT (the standard output) and STDERR (where errors are printed to).

We can get a Perl script to take input from STDIN (standard input) and do things with it by using the line input operator, which is a set of angle brackets with the name of a filehandle in between them:

```
my $user_input = <STDIN>;
```

The above example takes a single line of input from STDIN. The input is terminated by the user hitting Enter. If we want to repeatedly take input from STDIN, we can use the line input operator in a while loop:

```
#!/usr/bin/perl -w
while ($_ = <STDIN>) {
    # do some stuff here, if you want...
    print; # NOTE: print takes $_ as its default argument
]
```

Conveniently enough, the while statement can be written more succinctly, because in these circumstances, the line input operator assigns to \$ by default:

Better yet, the default filehandle used by the line input operator is STDIN, so we can shorten the above example yet further:

```
while (<>) {
    print;
}
```

As always, there's more than one way to do it.

The above example script (which is available in your directory as <code>exercises/cat.pl</code>) will basically perform the same function as the UNIX **cat** command; that is, print out whatever's given to it through STDIN.

Try running the script with no arguments. You'll have to type some stuff in, line by line, and type **CTRL-D** (a.k.a. \neg D) when you're ready to stop. \neg D indicates end-of-file (EOF) on most UNIX systems.

Now try giving it a file by using the shell to redirect its own source code to it:

```
perl exercises/cat.pl < exercises/cat.pl</pre>
```

This should make it print out its own source code.

6.8 Best practices template for file manipulation

Its a good idea to follow this template when reading and writing from files:

```
my $filename = 'filename'; # the filename
my $fh;
open($fh, "<", $filename) or die "couldn't open $filename for read
($!)";
while(my $line = <$fh>) {
    chomp($line);
    # do whatever else you want to do with it
}
close($fh) or die "couldn't close $filename ($!)";
```

There are a couple of points to note about this. The first would be the use of the 3-argument open(). Another would be stooring the filename in a scalar for use in error messages. die()ing on open() and close() is considered good form and the system-provided error (\$!) can be very helpful.

6.9 Named blocks

Blocks can be given names, thus:

```
#!/usr/bin/perl -w
LINE: while (<STDIN>) {
    ...
}
```

By tradition, the names of blocks are in upper case. The name should also reflect the type of thing you are iterating over -- in this case, a line of text from STDIN.

6.10 Breaking out of loops

You can break out of loops using next, last and similar statements.

The LINE indicating the block to break out of is optional (it defaults to the current smallest loop), but can be very useful when you wish to break out of a loop higher up the chain:

6.11 Chapter summary

- A block in Perl is a series of statements grouped together by curly brackets. Blocks can be used in conditional constructs and subroutines.
- A conditional construct is one which executes statements based on the truth of a condition
- Truth in Perl is determined by testing whether something is NOT any of: numeric zero, the null string, or undefined
- The if elsif else conditional construct can be used to perform certain actions based on the truth of a condition
- The while, for, and foreach constructs can be used to repeat certain statements based on the truth of a condition.
- A common practical use of the while loop is to read each line of a file.
- Blocks may be named using the NAME: convention
- You can break out of blocks using next, last and similar statements

Chapter 7: Subroutines

In this chapter...

In this chapter, we look at subroutines and how they can be used to simplify your code.

7.1 Introducing subroutines

If you have a long Perl script, you'll probably find that there are parts of the script that you want to break out into subroutines. In particular, if you have a section of code which is repeated more than once, it's best to make it a subroutine to save on maintenance (and, of course, linecount).

A subroutine is basically a little self-contained mini-program in the form of block which has a name, and can take arguments and return values:

```
# the general case
sub name {
    BLOCK
}
# the specific case
sub print_headers {
    print "Programming Perl, 2nd ed\n";
    print "by\n";
    print "Larry Wall et al.\n";
}
```

7.2 Calling a subroutine

A subroutine can be called in either of the following ways:

&print_headers;
print_headers();

If (for some reason) you've got a subroutine that clashes with a reserved function or something, you will need to prefix your function name with & (ampersand) to be perfectly clear. You should avoid doing this anyway; overloading built-in functions can cause more confusion than it's worth.

Advanced

There are other times when you need to use an ampersand on your subroutine name, such as when a function needs a SUBROUTINE type of parameter, or when making an anonymous subroutine reference.

7.3 Passing arguments to a subroutine

You can pass arguments to a subroutine by including them in the brackets when you call it. The arguments end up in an array called @_which is only visible inside the subroutine.

```
print_headers("Programming Perl, 2nd ed", "Larry Wall et al");
# we can also pass variables to a subroutine by name...
my $fiction_title = "Lord of the Rings";
my $fiction_author = "J.R.R. Tolkein";
print_headers($fiction_title, $fiction_author);
sub print_headers {
    my ($title, $author) = @_;
    print "$title\n";
    print "$title\n";
    print "by\n";
    print "$author\n";
}
```

You can take any number of scalars in as arguments - they'll all end up in $@_$ in the same order you gave them.

RTFM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	5	132		
Camel 2 nd	3	215	shift()	
Camel 3 rd	1 9 29	33 268 785	shift()	
perldoc	-f shift			
Cookbook 2 nd	4	143	circular lists	
Learning 3 rd	3	47		
Learning 4 th				

7.4 Returning values from a subroutine

To return a value from a subroutine, simply use the return function.

```
sub print_headers {
    my ($title, $author) = @_;
    return "$title\nby\n$author\n\n";
}
sub sum {
    my $total;
    foreach my $x (@_) {
        $total = $total + $x;
    }
    return $total;
}
```

You can also return lists from your subroutine:

```
# subroutine to return the first three arguments passed to it
sub firstthree {
        return @_[0..2];
}
my @three_items = firstthree("x", "y", "z", "a", "b");
# sets @three_items to ("x", "y", "z");
```

7.5 Exercises

- 1. Write a subroutine which prints out its first argument
- 2. Modify the above subroutine to also print out the last argument
- 3. Now change it to compare the first and last arguments and return the one which is numerically larger (you'll want to use an *if* statement for that)

7.6 Chapter summary

- A subroutine is a named block which can be called from anywhere in your Perl program
- Subroutines can accept parameters, which are available via the special array ${}^{\ensuremath{\mathbb{G}}}_{-}$
- Subroutines can return scalar or list values.

Chapter 8: Regular expressions

In this chapter...

In this chapter we begin to explore Perl's powerful regular expression capabilities, and use regular expressions to perform matching and substitution operations on text.

8.1 What are regular expressions?

The easiest way to explain this is by analogy. You will probably be familiar with the concept of matching filenames under DOS and UNIX by using wild-cards - *.txt or /usr/local/* for instance. When matching filenames, an aster-isk can be used to match any number of unknown characters, and a question mark matches any single character. There are also less well-known filename matching characters.

Regular expressions are similar in that they use special characters to match text. The differences are that any kind of text can be matched, and that the set of special characters is different.

Regular expressions are also known as REs, regexes, and regexps.

Advanced

If you have a mathematical background, you may like to think of a regexp as a definition of a set of strings. For instance, a regexp may describe the set of all strings which begin with the letter "a".

8.2 Regular expression operators and functions

8.2.1 m/PATTERN/ - the match operator

The most basic regular expression operator is the matching operator, m/PAT-TERN/.

- Works on *\$_* by default.
- In scalar context, returns true (1) if the match succeeds, or false (the empty string) if the match fails.
- In list context, returns a list of any parts of the pattern which are enclosed in parentheses. If there are no parentheses, the entire pattern is treated as if it were parenthesized.
- The $\ensuremath{\mathtt{m}}$ is optional if you use slashes as the pattern delimiters.
- If you use the m you can use any delimiter you like instead of the slashes. This is very handy for matching on strings which contain slashes, for instance directory names or URLs.
- Using the /i modifier on the end makes it case insensitive.

```
while (<>) {
    print if m/foo/;    # prints if a line contains "foo"
    print if m/foo/i;    # prints if it contains "foo", "FOO", etc
    print if /foo/i;    # exactly the same; the m is optional
    print if m!http://!; # using ! as an alternative delimiter
}
```

8.2.2 s/PATTERN/REPLACEMENT/ - the substitution operator

This is the substitution operator, and can be used to find text which matches a pattern and replace it with something else.

- Works on \$ by default.
- In scalar context, returns the number of matches found and replaced.
- In list context, behaves the same as in scalar context and returns the number of matches found and replaced.

- You can use any delimiter you want, the same as the m// operator.
- Using /g on the end of it matches globally, otherwise matches (and replaces) only the first instance of the pattern.
- Using the /i modifier makes it case insensitive.

```
# fix some misspelt text
while (<>) {
        s/freind/friend/g;
        s/teh/the/g;
        s/jsut/just/g;
        print;
```

}

The above example can be found in exercises/spellcheck.pl.

8.3 Binding operators

If we want to use m// or s/// to operate on something other than s_w need to use binding operators to bind the match to another string.

Table 8-1. Binding operators

Operator	Meaning
=~	True if the pattern matches
!~	True if the pattern doesn't match

```
print "Please enter your homepage URL: ";
my $url = <STDIN>;
if ($url =~ /geocities/) {
        print "Ahhh, I see you have a geocities homepage!\n";
}
```

8.4 Metacharacters

The special characters we use in regular expressions are called *metacharacters*, because they are characters that describe other characters.

8.4.1 Some easy metacharacters

Metacharacter(s)	Matches
^	Start of string
\$	End of string
	Any single character except n (though special things can happen in multiline mode)
\n	Newline (subtly different to \$ - when working in multiline mode, there may be newlines embedded in the multiline string you're working with.
\t	Matches a tab
\s	Any whitespace character, such as space or tab
\S	Any non-whitespace character
\d	Any digit (0 to 9)
\D	Any non-digit
\w	Any "word" character - alphanumeric plus underscore (_)
W/	Any non-word character
\b	A word break - the zero-length point between a word character (as defined above) and a non-word character.

 Table 8-2. Regular expression metacharacters

RTFM!			
Src	Chap	Pgs	#
Nutshell 2 nd	4	67 - 73	
Camel 2 nd	2	58 - 68	
Camel 3 rd	5	158 - 164	
perldoc	perlre		
Cookbook 2 nd			
Learning 3 rd	7	100	
Learning 4 th			

Any character that isn't a metacharacter just matches itself. If you want to match a character that's normally a metacharacter, you can escape it by preceding it with a backslash

Some quick examples:

```
# Perl regular expressions are usually found within slashes - the
# matching operator/function which we will see soon.
```

/cat/	<pre># matches the three characters</pre>
	# c, a, and t in that order.
/^cat/	<pre># matches c, a, t at start of line</pre>
/\scat\s/	<pre># matches c, a, t with spaces on either side</pre>
/\bcat\b/	<pre># same as above, but won't include the</pre>
	<pre># spaces in the text it matches</pre>
<pre># we can interp my \$animal = "c /\$animal/ /\$animal\$/</pre>	olate variables just like in strings: log"
/\\$\d\.\d\d/	# matches a dollar sign, then a digit, # then a dot, then another digit, then # another digit, eg \$9.99

8.5 Quantifiers

What if, in our last example, we'd wanted to say "Match a dollar, then any number of digits, then a dot, then two more digits"? What we need are quantifiers.

Quantifier	Meaning	
?	0 or 1	
*	0 or more	
+	1 or more	
{n}	match exactly n times	
{n,}	match n or more times	
{n,m}	match between n and m times	

Table 8-3. Regular expression quantifiers

Some examples of quantifiers:

x?	# 0 or 1 "x"
X*	# 0 or more "x"
X+	# 1 or more "x"
x{5}	# exactly 5 "x"
x{5,}	# 5 or more "x"
x{5,10}	# 5-10 "x"
bore*d	# "bor", 0 or more "e", "d"
.*	# 0 or more of anything
.+	# 1 or more of anything
[]*=[]*	<pre># match an "=" with optional spaces on either side</pre>

8

8.6 Greediness

Regular expressions are, by default, "greedy". This means that any regular expression, for instance .*, will try to match the biggest thing it possibly can. Greediness is sometimes referred to as "maximal matching".

To change this behavior, follow the quantifier with a question mark, for example .*?. This is sometimes referred to as "minimal matching".

8.7 Exercises

- 1. You now know enough to work out the price example above. Work it through.
- 2. Another example: what regular expression would match the word "colour" with either British or American spellings?
- 3. How can we match any four-letter word?
8.8 Character classes

A character class can be used to find a single character that matches any one of a given set of characters.

Let's say you're looking for occurences of the word "grey" in text, then remember that the American spelling is "gray". The way we can do this is by using character classes. Character classes are specified using square brackets, thus: /gr[ea]y/

We can also use character sequences by saying things like [A-Z] or [0-9]. The sequences d and w can easily be expressed as character classes: [0-9] and [a-ZA-ZO-9] respectively.

We can negate a character class by putting a caret at the start of it. That's right, the same character that we used to match the start of the line. Larry Wall has written that Perl does anything you want -- unless you want consistency, and it has also been said that consistency is the hobgoblin of small minds. Therefore, we'll learn about these character class inconsistencies, learn to love them, and flatter ourselves that we do not have small minds.

Here are some of the special rules that apply inside character classes. I make no guarantee that this is a complete list; additions are always welcome.

- ^ at the start of a character class negates the character class, rather than specifying the start of a line.
- - specifies a range of characters.
- . () (+ and other metacharacters taken literally.

8.8.1 Exercises as a group

Your trainer will help you do the following exercises as a group.

- 1. How would we find any word starting with a letter in the first half of the alphabet, or with X, Y, or Z?
- 2. What regular expression could be used for any word that starts with letters *other* than those listed in the previous example.
- 3. There's almost certainly a problem with the regular expression we've just created can you see what it might be?

8.9 Alternation

The problem with character classes is that they only match one character. What if we wanted to match any of a set of longer strings, like a set of words?

The way we do this is to use the pipe symbol | for alternation:

```
/cat|dog|budgie/  # matches any of our pets
```

Now we come up against another problem. If we write something like:

```
/^cat|dog|budgie$/
```

...to match any of our pets on a line by itself, what we're actually matching is: "the start of the string followed by cat; or dog; or budgie followed by the end of the string". This is not what we originally intended. To fix this, we enclose our alternation in round brackets:

```
/^(cat|dog|budgie)$/
# a simple matching program to get some email headers and print them
out
while (<>) {
    print if /^(From|Subject|Date):\s/;
}
```

The above email example can be found in exercises/mailhdr.pl.

8.10 The concept of atoms

Round brackets bring us neatly into the concept of atoms. The word "atom" derives from the Greek *atomos* meaning "indivisible" (little did they know!). What we use it to mean is "something that is a chunk of regular expression in its own right" -- as opposed to "something that can wipe out cities with a single blast".

Atoms can be arbitrarily created by simply wrapping things in round brackets handy for indicating grouping, using quantifiers for the whole group at once, and for indicating which bit(s) of a matching function should be the returned value (but we'll deal with that later).

In the example above, there are three atoms:

- 1. start of line
- 2. cat or dog or budgie
- 3. end of line

How many atoms were there in our dollar prices example earlier?

Atomic groupings can have quantifiers attached to them. For instance:

```
# match a consonant followed by a vowel twice in a row
# eg "tutu"
/([^aeiou][aeiou]){2}/
# match three or more words starting with "a" in a row
# eg "all angry animals"
/(\ba\w+\b\s*){3,}
```

8.11 Exercises

- 1. Determine whether your name appears in a string (an answer's in exercises/answers/namere.pl).
- 2. Remove footnote references (like [1]) from some text (see exercises/footnote.txt for some sample text, and exercises/answers/footnote.pl for an answer).
- 3. Split tab-separated data into an array then print out each element using a foreach loop.

8.12 split() function

The split() function provides a convenient way to take a scalar and use a regular expression to represent some definition of separator and it gives back the data between those seperators. Some examples will make this seem much easier:

```
# split a sentence based on spaces
my $words = "This is a sentence.";
my @words = split(/ /,$words);
# split the time on the colons
my $time = "01:23:45";
my @timeparts = split(/:/,$time);
```

8.13 Exercises

- 1. Use split() to turn a full name into name parts.
- 2. Use split() to turn a string containing the alphabet (\$alpha="abcedfghijklmnopqrstuvwxyz) to produce an array containing one letter per cell.

150

8.14 Chapter summary

- Regular expressions are used to perform matches and substitutions on strings
- Regular expressions can include meta-characters (characters with a special meaning, which describe sets of other characters) and quantifiers
- Character classes can be used to specify any single instance of a set of characters
- Alternation may be used to specify any of a set of sub-expressions
- The matching operator is m/PATTERN/ and acts on \$_ by default
- The substitution operator is s/PATTERN/REPLACEMENT/ and acts on \$_ by default
- Matches and substitutions can be performed on strings other than \$_ by using the =~ binding operator
- Functions such as split() and grep() use regular expression patterns as one
 of their arguments

Chapter 9: Practical exercises

This chapter provides you with some broader exercises to test your new Perl skills. Each exercise requires you to use a mixture of variables, operators, functions, conditional and looping constructs, and regular expressions.

9.1 Exercises

There are no right or wrong answers. Remember, "There's More Than One Way To Do It."

- 1. Write a simple menu system where the user is repeatedly asked to choose a message to display or Q to quit.
 - a. Consider case-sensitivity
 - b. Handle errors cleanly
- 2. Write a "chatterbox" program that holds a conversation with the user by matchings patterns in the user's input.
- 3. Write a program that gives information about files.
 - a. use file test operators
 - b. offer to print the file out if it's a text file
 - c. how will you cope with files longer than a screenful?

Chapter 10: File I/O

In this chapter...

In this section, we learn how to open and interact with files and directories in various ways.

10.1 Assumed knowledge

You should already have encountered the open() function and the <> line input operator in a previous Perl training session or in your previous Perl experience.

10.2 Angle brackets - the line input and globbing operators

You will have encountered the line input operator <> before, in situations such as these:

```
# reading lines from STDIN
while (<>) {
    ...
    ...
}
# reading a single line of user input from STDIN
my $input = <STDIN>
```

RT FM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	4	78	read it now	
Camel 2 nd	2	53		
Camel 3 rd	2	80 - 83		
perldoc	perlop		I/O Operators	
Cookbook 2 nd	8	300 - 302		
Learning 3 rd	11	155 - 156		
Learning 4 th	5	70 - 72		

<> is also known as the diamond operator.

- In scalar context, the line input operator yields the next line of the file referenced by the filehandle given.
- In list context, the line input operator yields all remaining lines of the file referenced by the filehandle.
- The default filehandle is STDIN, or any files listed on the command line of the Perl script (eg myscript.pl file1 file2 file3).

The *globbing* operator is nearly, but not quite, identical to the line input operator. It looks the same, and it acts partly in a similar way, but it really is a separate operator.

RTFM!			
Src	Chap	Pgs	#
Nutshell 2 nd	5	111	
Camel 2 nd	2	55 - 57	
Camel 3 rd	2	83 - 85	
perldoc	perlop		I/O Operators
Cookbook 2 nd	9	358 - 359	
Learning 3 rd	12	169 - 170	
Learning 4 th	12	165 - 166	

If the angle brackets have anything in them other than a filehandle or nothing, it will work as a globbing operator and whatever is between the angle brackets will be treated as a filename wildcard. For instance:

my @files = <*.txt>

The filename glob *.txt is matched against files in the current directory, then either they are returned as a list (in list context, as above) or one scalar at a time (in scalar context).

If you get a list of files this way, you can then open them in turn and read from them.

```
while (<*.txt>) {
    open (FILEHANDLE, $_) || die ("Can't open $_: $!");
    ...
    ...
    close FILEHANDLE;
}
```

The glob() function behaves in a very similar manner to the angle bracket globbing operator.

```
my @files = glob("*.txt")
foreach (glob "*.txt") {
    ...
}
```

The glob() is considered much cleaner and better to use than the angle-brackets globbing operator.

10.2.1 Exercises

- 1. Use the line input operator to accept input from the user then print it out
- 2. Modify your previous script to use a while loop to get user input repeatedly, until they type "Q" (or "q" check out the lc() and uc() functions in chapter 3 of your Camel book) (Answer: exercises/answers/userinput.pl)
- 3. Use the file globbing function or operator to find all Perl scripts in your home directory and print out their names (assuming they are named in the form *.pl) (Answer: exercises/answers/findscripts.pl)

10.2.1.1 Advanced exercises

1. Use the above example of globbing to print out all the Perl scripts one after the other. You will need to use the open() function to read from each file in turn. (Answer: exercises/answers/printscripts.pl)

10.3 open() and friends - the gory details

10.3.1 Opening a file for reading, writing or appending

The open() function is used to open a file for reading or writing (or both, or as a pipe - more on that later).

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	5	118 - 119	
Camel 2 nd	3	191 - 195	
Camel 3 rd	29	747 - 755	
perldoc	-f open		read it now
Cookbook 2 nd	7	247 - 252	
Learning 3 rd	11	150 - 151	
Learning 4 th	5	79 - 81	

In a typical situation, we might use open() to open and read from a file:

```
open(LOGFILE, "/var/log/httpd/access.log")
```

Note that the < (less than) used to indicate reading is assumed; we could equally well have said "</var/log/httpd/access.log".

You should *always* check for failure of an open() statement:

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	4	55	
Camel 2 nd	2	134	
Camel 3 rd			
perldoc	perlvar		aka \$ERRNO
Cookbook 2 nd			
Learning 3 rd	11	153 - 154	
Learning 4 th	5	82 - 84	

Once a file is opened for reading or writing, we can use the filehandle we specified (in this case LOGFILE) for a variety of useful purposes:

Note that you should always close a filehandle when you're finished with it (though admittedly any open filehandles will be automatically closed when your script exits).

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	5	138	
Camel 2 nd	3	229	
Camel 3 rd	29	808 - 809	
perldoc	-f sysopen		
Cookbook 2 nd	7	247 - 252	
Learning 3 rd			
Learning 4 th			

10.3.1.1 Exercises

- 1. Write a script which opens a file for reading. Use a while loop to print out each line of the file.
- 2. Use the above script to open a Perl script. Use a regular expression to print out only those lines not beginning with a hash character (i.e. non-comment lines). (Answer: exercises/answers/delcomments.pl)
- 3. Create a new script which opens a file for writing. Write out the numbers 1 to 100 into this file. (Answer: exercises/answers/100count.pl)
- 4. Create a new script which opens a logfile for appending. Create a while loop which accepts input from STDIN and appends each line of input to the logfile. (Answer: exercises/answers/logfile.pl)
- 5. Create a script which opens two files, reads input from the first, and writes it out to the second. (Answer: exercises/answers/readwrite.pl)

10.3.2 Reading directories

It is also possible to open directories (using <code>opendir()</code> and read from them. However, it is not possible to read the contents of files in that directory simply by opening it and looping through it. Opening a directory simply makes the filenames in that directory accessible via functions such as <code>readdir()</code>.

RTFM!			
Src	Chap	Pgs	#
Nutshell 2 nd	5 5	119 125	opendir readdir
Camel 2 nd	33	195 202	opendir readdir
Camel 3 rd	29 29	755 770	opendir readdir
perldoc	-f opendir -f readdir		
Cookbook 2 nd	9	356 - 358	
Learning 3 rd	12	171 - 173	
Learning 4 th	12	167 - 168	

```
opendir(HOMEDIR, $ENV{HOME});
```

```
my @files = readdir(HOMEDIR);
closedir HOMEDIR;
foreach (@files) {
        open(THISFILE, "<$_") || die "Can't open file $_: $!");
        ...
        close THISFILE;
}
```

10.3.2.1 Exercises

- 1. Use opendir() and readdir() to obtain a list of files in a directory. What order are they in?
- 2. Use the sort() function to sort the list of files asciibetically (Answer: exercises/answers/dirlist.pl)

10.3.3 Opening files for simultaneous read/write

Files can be opened for simultaneous read/write by putting a + in front of the > or < sign. +< is almost always preferable, however, as +> would overwrite the

file before you had a chance to read from it.

Read/write access to a file is not as useful as it sounds --- you can't write into the middle of the file using this method, only onto the end. The main use for read/write access is to read the contents of a file and then append lines to the end of it.

A more flexible way to read and write a file is to import the file into an array, manipulate the array, then output each element again.

- close OUTFILE;
- One thing to watch out for here is memory usage. If you have a ten megabyte file, it will use at least that much memory as a Perl data structure.

10.3.3.1 Exercises

1. Open a file, reverse its contents (line by line) and write it back to the same filename (Answer: exercises/answers/reversefile.pl)

10.3.4 Opening pipes

If the filename given to open() begins with a pipe symbol (1), the filename is interpreted as a command to which output is to be piped, and if the filename ends with a 1, the filename is to be interpreted as a filename which pipes input to us.

This is often used when you want to take input from the system a line at a time. Here's an example which reads from the **rot13** filter (a simple routine which rotates the letters of its input by 13 letters, providing a very simple cipher for encoding the answers to jokes, spoilers to movies, or other low-security information):

164

```
#!/usr/bin/perl -w
use strict;
open (ROT13, "rot13 < /etc/motd |") || die "Can't open pipe: $!";
while (<ROT13>) {
        print;
}
close ROT13;
```

Conversely, we can output something through rot13:

```
#!/usr/bin/perl -w
use strict;
open (ROT13, "|rot13") || die "Can't open pipe: $!";
print "This is some rot13'd text:\n";
print ROT13 "This is some rot13'd text.\n";
```

close ROT13;

RTFM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	4	59	\$	
Camel 2 nd	2	130		
Camel 3 rd	28	670		
perldoc	perlvar		\$	
Cookbook 2 nd	7	281 - 284		
Learning 3 rd	6	92	light	
Learning 4 th				

10.3.4.1 Exercises

- 1. Modify the second example above (provided for you as exercises/rot13.pl in your exercises directory to accept user input and print out the **rot13**'d version.
- 2. Change your script to accept input from a file using open() (Answer: exercises/answers/rot13.pl)
- 3. Change your script to pipe its input through the **strings** command, so that if you get a file that's not a text file, it will only look at the parts of the file which are strings. (Answer: exercises/answers/strings.pl)

10.4 Finding information about files

We can find out various information about files by using file test operators and functions such as ${\tt stat}()$

Operator	Meaning
-e	File exists.
-r	File is readable
-w	File is writable
-x	File is executable
-0	File is owned by you
- Z	File has zero size.
-s	File has nonzero size (returns size).
-f	File is a plain file.
-d	File is a directory.
-1	File is a symbolic link.
-p	File is a named pipe (FIFO), or Filehandle is a pipe.
-S	File is a socket.
-b	File is a block special file.
-c	File is a character special file.
-t	Filehandle is opened to a tty.
-u	File has setuid bit set.
-g	File has setgid bit set.
-k	File has sticky bit set.
-T	File is a text file.
-B	File is a binary file (opposite of -T).
-M	Age of file in days when script started.
-A	Same for access time.
-C	Same for inode change time.

Table 10-1. File test operators

	1/11		
Src	Chap	Pgs	#
Nutshell 2 nd	4	63 - 64	
Camel 2 nd	2	85	
Camel 3 rd	3	98	
perldoc	perlfunc		
Cookbook 2 nd			
Learning 3 rd	11	157 - 163	
Learning 4 th			

Here's how the file test operators are usually used:

```
#!/usr/bin/perl -w
use strict;
unless (-e "config.txt") {
    die "Config file doesn't exist";
}
# or equivalently...
die "Config file doesn't exist" unless -e config.txt;
```

The stat() function returns similar information for a single file, in list form. lstat() can also be used for finding information about a file which is pointed to by a symbolic link.

10.4.1 Exercises

- 1. Write a script which asks a user for a file to open, takes their input from STDIN, checks that the file exists, then prints out the contents of that file. (Answer: exercises/answers/fileexists.pl)
- 2. Write a script to find zero-byte files in a directory. (Answer:

exercises/answers/zerobyte.pl)

3. Write a script to find the largest file in a directory: exercises/answers/largestfile.pl

10.5 Recursing down directories

The built-in functions described above do not enable you to easily recurse through subdirectories. Luckily, the **File::Find** module is part of the standard library distributed with Perl 5.

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	8	254	
Camel 2 nd	7	439	
Camel 3 rd	31	867	
perldoc	File::Find		
Cookbook 2 nd	9	359 - 361	
Learning 3 rd	12	173	pretty light
Learning 4 th			

File::Find emulates UNIX's **find** command. It takes as its arguments a block to execute for each file found, and a list of directories to search.

```
#!/usr/bin/perl -w
use strict;
use File::Find;
print "Enter the directory to search: ";
chomp(my $dir = <STDIN>);
find (\&wanted, $dir);
sub wanted {
        print "$_\n";
}
```

For each file found, certain variables are set. \$File::Find::dir is set to the current directory name, \$File::Find::name contains the full name of the file, i.e.
\$File::Find::dir/\$_.

10.5.1 Exercises

- 1. Modify the simple script above (in your scripts directory as exercises/find.pl) to only print out the names of plain text files only (hint: use file test operators)
- 2. Now use it to print out the contents of each text file. You'll probably want to pipe your output through **more** so that you can see it all. (Answer: exercises/answers/find.pl)

10.6 File locking

File locking can be achieved using the flock() function. This can be used to guard against race conditions or other problems which occur when two (or more) users open the same file in read/write mode.

RTFM!			
Src	Chap	Pgs	#
Nutshell 2 nd	5	104	
Camel 2 nd	3	166 - 167	
Camel 3 rd	29	714 - 715	
perldoc	-f flock		
Cookbook 2 nd	7	279-281	
Learning 3 rd			
Learning 4 th			

10.7 Handling binary data

If you are opening a file which contains binary data, you probably don't want to read it in a line at a time using while (<>) { }, as there's no guarantee that there will be any line breaks in the data.

Instead, we use read() to read a certain number of bytes from a file handle.

RTFM!			
Src	Chap	Pgs	#
Nutshell 2 nd	5	125	
Camel 2 nd	3	202	
Camel 3 rd	29	769	
perldoc	-f read		
Cookbook 2 nd	8	304, 325	
Learning 3 rd	16	225 - 227	fixed-length record databases
Learning 4 th			

read() takes the following arguments:

- The filehandle to read from
- The scalar to put the binary data into
- The number of bytes to read
- The byte offset to start from (defaults to 0)

#!/usr/bin/perl -w
use strict;

```
my $image = "picture.gif";
```

open (IMAGE, \$image) or die "Can't open image file: \$!";

```
open (OUT, ">backup/$image") or die "Can't open backup file: $!";
my $buffer;
binmode IMAGE;
while (read IMAGE, $buffer, 1024) {
        print OUT $buffer;
}
close IMAGE;
close OUT;
```

If you are using Windows, DOS, or some other types of systems, you may need to use binmode() to make sure that certain linefeed characters aren't translated when Perl reads a file in binary mode. While this is not needed on UNIX systems, it's a good idea to use it anyway to enhance portability.

10.8 Chapter summary

- Angle brackets <> can be used for simple line input. In scalar context, they return the next line; in list context, all remaining lines; the default filehandle is **STDIN** or any files mentioned in the command line (ie @ARGV).
- Angle brackets can also be used as a globbing operator if anything other than a filehandle name appears between the angle brackets. In scalar context, returns the next file matching the glob pattern; in list context, returns all remaining matching files.
- The open() and close() functions can be used to open and close files. Files can be opened for reading, writing, appending, read/write, or as pipes.
- The opendir(), readdir() and closedir() functions can be used to open, read from, and close directories.
- The File::Find module can be used to recurse down through directories.
- File test operators or stat() can be used to find information about files
- File locking can be achieved using flock()
- Binary data can be read using the read() function. The binmode() function should be used to ensure platform independence when reading binary data.

Chapter 11: Advanced regular expressions

In this section...

This section builds on the basic regular expressions taught in day 1 of PerlClass.com's *Introduction to Perl* course. We will learn how to handle data which consists of multiple lines of text, including how to input data as multiple lines and different ways of performing matches against that data.

11.1 Assumed knowledge

You should already be familiar with the following topics:

- Regular expression metacharacters
- Quantifiers
- · "Greediness" in regular expressions, aka maximal and minimal matching
- Character classes and alternation
- The m// matching function
- The s/// substitution function
- Matching strings other than \$ with the =~ matching operator
- Assigning matched strings to lvalues

RTFM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	4	66- 72		
Camel 2 nd	2	57 - 75		
Camel 3 rd	5	139 - 216		
perldoc	perlre			
Cookbook 2 nd	6	179 - 238		
Learning 3 rd	7 8 9	98 - 104 105 - 114 115 - 127	Concepts More Using	
Learning 4 th				

11.2 Review exercises

The following exercises are intended to refresh your memory of basic regular expressions:

- 1. Write a script to search a file for any of the names "Yasser Arafat", "Boris Yeltsin" or "Monica Lewinsky". Print out any lines which contain these names. (Answer: exercises/answers/namesre.pl)
- 2. What pattern could be used to match any of: Elvis Presley, Elvis Aron Presley, Elvis A. Presley, Elvis Aaron Presley. (Answer: exercises/answers/elvisre.pl)
- 3. What pattern could be used to match a blank line? (Answer: exercises/answers/blanklinere.pl)
- 4. What pattern could be used to match an IP address such as 203.20.104.241, where each part of the address is a number from 0 to 255? (Answer: exercises/answers/ipre.pl)

11.3 More metacharacters

Here are some more advanced metacharacters, which build on the ones already covered in the Introduction to Perl module:

Metacharacter	Meaning	
\B	Match anything other than a word boundary	
\cX	Control character, i.e. CTRL-x	
\0 <i>nn</i>	Octal character represented by nn	
\xnn	Hexadecimal character represented by <i>nn</i>	
\1	Lowercase next character	
\u	Uppercase next character	
\L	Lowercase until \E	
\U	Uppercase until \E	
\Q	quote (disable) metacharacters until \E	
\E	End of lowercase/uppercase	

Table 11-1. More metacharacters

search for the C++ computer language:

/C++/	<pre># wrong! regexp engine complains about the plus signs</pre>
/C\+\+/	# this works
/C\Q++\E/	# this works too
<pre># search for</pre>	"bell" control characters, eg CTRL-G
/\cG/	# this is one way
/\007/	<pre># this is another CTRL-G is octal 07</pre>
/\x07/	<pre># here it is as a hex code</pre>
11.4 Working with multiline strings

Often, you will want to read a file several lines at a time. Consider, for example, a typical UNIX fortune cookie file, which is used to generate quotes for the **fortune** command:

```
%
Let's call it an accidental feature.
        -- Larry Wall
%
Linux: the choice of a GNU generation
%
When you say "I wrote a program that crashed Windows", people just
stare at you blankly and say "Hey, I got those with the system, *for
free*".
        -- Linus Torvalds
%
I don't know why, but first C programs tend to look a lot worse than
first programs in any other language (maybe except for fortran, but
then I suspect all fortran programs look like `firsts')
        -- Olaf Kirch
%
All language designers are arrogant. Goes with the territory...
        -- Larry Wall
%
We all know Linux is great... it does infinite loops in 5 seconds.
        -- Linus Torvalds
%
Some people have told me they don't think a fat penguin really
embodies the grace of Linux, which just tells me they have never
seen a angry penguin charging at them in excess of 100mph.
                                                            Thev'd
be a lot more careful about what they say if they had.
        -- Linus Torvalds, announcing Linux v2.0
%
```

The fortune cookies are separated by a line which contains nothing but a percent sign. To read this file one item at a time, we would need to set the delimiter to something other than the usual n - in this case, we'd need to set it to something like

```
\n%\n.
```

To do this in Perl, we use the special variable .

/ = '' n% n'';

Conveniently enough, setting $\frac{1}{2}$ to "" will cause input to occur in "paragraph mode", in which two or more consecutive newlines will be treated as the delimiter. Undefining $\frac{1}{2}$ will cause the entire file to be slurped in.

```
undef $/;
```

\$_ = <FH>; # whole file now here

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	4	53-59	
Camel 2 nd	2 7	127-140 403	
Camel 3 rd	28 32	653-676 884	
perldoc	perlvar English		English provides friendlier names for special variables
Cookbook 2 nd			
Learning 3 rd	3	49	<pre>\$_ quickly</pre>
Learning 4 th			

Since \$/ isn't the easiest name to remember, we can use a longer name by using the **English** module:

use English;

```
$INPUT_RECORD_SEPARATOR = "\n%\n";  # long name for $/
$RS = "\n%\n";  # same thing, awk-like
```

11.4.1 Exercises

1. In your directory is a file called exercises/linux.txt which is a set of Linux-related fortunes, formatted as in the above example. Use multiline regular expressions to find only those quotes which were uttered by Larry Wall. (Answer: exercises/answers/larry.pl)

11.5 Regexp modifiers for multiline data

The /s and /m modifiers can be used to treat the string you're matching against as either a single or multiple lines. In single line mode, $^$ will match only at the start of the entire string, and \$ will match only at the end of the entire string. In multiline mode, they will match at embedded newlines as well.

In single line mode, the dot metacharacter will match n. In multiline mode, it won't.

The differences between default, single line, and multiline mode are set out very succinctly by Jeffrey Friedl in *Mastering Regular Expressions* (see the Bibliography at the back of these notes for details). The following table is paraphrased from the one on page 236 of that book.

His term "clean multiline mode" refers to a mode which is similar to multi-line, but which does not strip the newline character from the end of each line.

Mode	Specified with	 matches start of 	ঃ matches end of	Dot matches newline
default	neither /s nor /m	string	string	No
single-line	/ s	string	string	Yes
multi-line	/m	line	line	No
clean multi-line	/ms	line	line	Yes

Table 3-2. Effects of single and multiline options

11.6 Backreferences

11.6.1 Special variables

There are several special variables related to regular expressions.

- $s_{\&}$ is the matched text
- \$` is the unmatched text to the left of the matched text
- \$' is the unmatched text to the right of the matched text
- \$1, \$2, \$3, etc. The text matched by the 1st, 2nd, 3rd, etc sets of parentheses.

All these variables are modified when a match occurs, and can be used in any way that other scalar variables can be used.

```
# this...
my ($match) = m/^(\d+)/;
print $match;
# is equivalent to this:
m/^\d+/;
print $&;
# match the first three words...
m/^(\w+) (\w+) (\w+)/;
print "$1 $2 $3\n";
```

You can also use $s_{\&}$ and other special variables in substitutions:

```
$string = "It was a dark and stormy night.";
$string =~ s/dark|wet|cold/very $&/;
```

If you want to use parentheses simply for grouping, and don't want them to set a \$1 style variable, you can use a special kind of *non-capturing* parentheses, which look like (?: ...)

```
# this only sets $1 - the first two sets
# of parentheses are non-capturing
```

m/^(?:\w+) (?:\w+) (\w+)/;

The special variables \$1 and so on can be used in substitutions to include matched text in the replacement expression:

```
# swap first and second words s/(w+) (w+)/$2 $1/;
```

However, this is no use in a simple match pattern, because \$1 and friends aren't set until after the match is complete. Something like:

my \$word = "this";
print if m/(\$word) \$1/;

... will *not* match "this this". Rather, it will match "this" followed by whatever \$1 was set to by an earlier match.

In order to match "this this" we need to use the special regular expression metacharacters 1, 2, etc. These metacharacters refer to parenthesized parts of a match pattern, just as \$1 does, but *within the same match* rather than referring back to the previous match.

```
my $word = "this";
print if m/($word) \1/;
```

11.7 Exercises

- 1. Write a script which swaps the first and the last words on each line (Answer: exercises/answers/firstlast.pl)
- 2. Write a script which looks for doubled terms such as "bang bang" or "quack quack" and prints out all occurrences. This script could be used for finding typographic errors in text. (Answer: exercises/answers/double.pl)

11.7.1 Advanced

- 1. Modify the above script to work across line boundaries (Answer: exercises/answers/multiline_double.pl)
- 2. What about case sensitivity?

11.8 Section summary

- Input data can be split into multiline strings using the special variable \$/, also known as \$INPUT_RECORD_SEPARATOR.
- The /s and /m modifiers can be used to treat multiline data as if it were a single line or multiple lines, respectively. This affects the matching of ^ and \$, as well as whether or not . will match a newline.
- The special variables \$\$, \$` and \$' are always set when a successful match occurs
- \$1, \$2, \$3 etc are set after a successful match to the text matched by the first, second, third, etc sets of parentheses in the regular expression. These should only be used *outside* the regular expression itself, as they will not be set until the match has been successful.
- Special non-capturing parentheses (?:...) can be used for grouping when you don't wish to set one of the numbered special variables.
- Special metacharacters such as \1, \2 etc may be used *within* the regular expression itself, to refer to text previously matched.

Chapter 12: More functions

In this chapter...

In this chapter, we discuss some more advanced Perl functions.

12.1 The grep() function

The grep() function is used to search a list for elements which match a certain regexp pattern. It takes two arguments - a pattern and a list - and returns a list of the elements which match the pattern.

RT FM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	5	112		
Camel 2 nd	3	178 - 179		
Camel 3 rd	24 29	605 730		
perldoc	-f grep			
Cookbook 2 nd	4	136 - 137		
Learning 3 rd	17 B	236 - 237 292		
Learning 4 th				

trivially check for valid email addresses
my @valid_email_addresses = grep /\@/, @email_addresses;

The grep() function temporarily assigns each element of the list to s_{temp} then performs matches on it.

There are many more complicated uses for the grep function. For instance, instead of a pattern you can supply an entire block which is to be used to process the elements of the list.

my $@long_words = grep \{ (length(<math>\$_) > 8$); } @words;

grep() doesn't require a comma between its arguments if you are using a block as the first argument, but does require one if you're just using an expression. Have a look at the documentation for this function to see how this is described.

12.1.1 Exercises

- 1. Use grep() to return a list of elements which contain numbers (Answer: exercises/answers/grepnumber.pl)
- 2. Use grep() to return a list of elements which are
 - a. keys to a hash (Answer: exercises/answers/grepkeys.pl)
 - b. readable files (Answer: exercises/answers/grepfiles.pl)

12.2 The map() function

The map() function can be used to perform an action on each member of a list and return the results as a list.

```
my @lowercase = map lc, @words;
my @doubled = map { $_ * 2 } @numbers;
```

map() is often a quicker way to achieve what would otherwise be done by iterating through the list with foreach.

```
foreach (@words) {
     push (@lowercase, lc($_);
}
```

Like grep(), it doesn't require a comma between its arguments if you are using a block as the first argument, but does require one if you're just using an expression.

12.2.1 Exercises

1. Create an array of numbers. Use map() to find the square of each number. Print out the results.

12.3 Chapter summary

- The grep() function can be used to find items in a list which match a certain regular expression
- The map() function can be used to perform an operation on each member of a list.

Chapter 13: System interaction

In this section...

In this section, we look at different ways to interact with the operating system. In particular, we examine the system() function, and the backtick command execution operator. We also look at security and platform-independence issues related to the use of these commands in Perl.

13.1 system() and exec()

The system() and exec() functions both execute system commands.

system() forks, executes the commands given in its arguments, waits for them to return, then allows your Perl script to continue. exec() does not fork, and exits when it's done. system() is by far the more commonly used.

```
$ perl -we 'system("/bin/true"); print "Foo\n";'
Foo
```

```
$ perl -we 'exec("/bin/true"); print "Foo\n";'
Statement unlikely to be reached at -e line 1.
(Maybe you meant system() when you said exec()?)
```

If the system command fails, the error message will be available via the special variable s_{\perp} .

\$ perl -e 'system("cat non-existant-file") || die "\$!";'
cat: non-existant-file: No such file or directory

13.1.1 Exercises

1. Write a script to ask the user for a username on the system, then perform the **finger** command to see information about that user. (Answer: exercises/answers/finger.pl

13.2 Using backticks

Single quotes can be used to specify a literal string which can be printed, assigned to a variable, et cetera. Double quotes perform interpolation of variables and certain escape sequences such as n to create a string which can also be printed, assigned, etc.

A new set of quotes, called *backticks*, can be used to interpolate variables then run the resultant string as a shell command. The output of that command can then be printed, assigned, and so forth.

Backticks are the backwards-apostrophe character (` which appears below the tilde (\sim), next to the number 1 on most keyboards.

Just as the q() and qq() functions can be used to emulate single and double quotes and save you from having to escape quotemarks that appear within a string, the equivalent function qx() can be used to emulate backticks.

Src	Chap	Pgs	#
Nutshell 2 nd			
Camel 2 nd	2 2	52 41	Backticks qx()
Camel 3 rd	2	63	
perldoc	perlop -f qx		
Cookbook 2 nd	19	770 - 772	Securely running shell commands with user input from CGI, etc.
Learning 3 rd	1 14	17 107 - 201	
Learning 4 th			

13.2.1 Exercises

- 1. Modify your earlier finger program to use backticks instead of system()
 (Answer: exercises/answers/backtickfinger.pl)
- 2. Change it to use qx() instead (Answer: exercises/answers/qxfinger.pl)
- 3. The UNIX command **whoami** gives your username. Since most shells support backticks, you can type **finger** `**whoami**` to finger yourself. Use shell backticks inside your qx() statement to do this from within your Perl program. (Answer: exercises/answers/qxfinger2.pl)

13.3 Platform dependency issues

Note that the examples given above will not work consistently on all operating systems. In particular, the use of system() calls or backticks with UNIX-specific commands will not work under Windows NT. Slightly less obviously, the use of backticks on NT can sometimes fail when the output of a command is sent explicitly to the screen rather than being returned by the backtick operation.

The same situation used to apply to MacOS, but now that MacOS is Linuxbased and tends to have much better support for free and open source software, portability has basically become a Windows versus POSIX situation. With Linux, MacOS, Solaris, and every other flavor of UNIX all living in the POSIX camp and Microsoft survives as an anomaly.

13.4 Security considerations

Many of the examples given above can result in major security risks if the commands executed are based on user input. Consider the example of a simple finger program which asked the user who they wanted to finger:

```
#!/usr/bin/perl -w
use strict;
print "Who do you want to finger? ";
my $username = <STDIN>;
print `finger $username`;
```

Imagine if the user's input had been skud; cat /etc/passwd, or worse yet, skud; rm -rf /. The system would perform both commands as though they had been entered into the shell one after the other.

Luckily, Perl's -T flag can be used to check for unsafe user inputs.

```
#!/usr/bin/perl -wT
```

RT FM!				
Src	Chap	Pgs	#	
Nutshell 2 nd				
Camel 2 nd	6	356 - 360		
Camel 3 rd	23	557 - 566		
perldoc	perlsec			
Cookbook 2 nd	19	767 - 770		
Learning 3 rd	В	294	light	
Learning 4 th				

-T stands for "taint checking". Data input by the user is considered "tainted" and until it has been modified by the script, may not be used to perform shell commands or system interactions of any kind. This includes system interactions

such as open(), chmod(), and any other built-in Perl function which interacts with the operating system.

The only thing that will clear tainting is referencing substrings from a regexp match. The perlsec online documentation contains a simple example of how to do this. Read it now, and use it to complete the following exercises.

Note that you'll also have to explicitly set \$ENV{'PATH'} to something safe (like /bin) as well.

ADVANCED

There is a Safe module available from CPAN that will let you setup sand boxes (similar to the JVM) that you can run Perl code in with arbitrary restrictions.

13.4.1 Exercises

- 1. Modify the finger program above to perform taint checking (Answer: exercises/answers/taintfinger.pl)
- 2. Take one of your scripts using open() or opendir() and modify it to accept a filename as user input. Turn taint checking on. What sort of regular expression could you use to check for valid filenames? (Answer: exercises/answers/taintfile.pl)

13.5 Section summary

- The system() function can be used to perform system commands. \$! is set if any error occurs.
- The backtick operator can be used to perform a system command and return the output. The qx() quoting function/operator works similarly to backticks.
- The above methods may not result in platform independent code.
- Data input by users or from elsewhere on the system can cause security problems. Perl's -T flag can be used to check for such "tainted" data
- Tainted data can only be untainted by referencing a substring from a pattern match.

Chapter 14: References and data structures

In this section...

In this section, we look at Perl's powerful reference syntax and how it can be used to implement complex data structures such as multi-dimensional lists, hashes of hashes, and more.

14.1 Assumed knowledge

For this section, it is assumed that you have a good understanding of Perl's data types: scalars, arrays, and hashes. Prior experience with languages which use pointers or references is helpful, but not required.

14.2 Introduction to references

Perl's basic data type is the *scalar*. Arrays and hashes are made up of scalars, in one- or two-dimensional lists. It is not possible for an array or hash to be a member of another array or hash under normal circumstances.

However, there is one thing about an array or hash which is scalar in nature -its memory address. This memory address can be used as an item in an array or list, and the data extracted by looking at what's stored at that address. This is what a reference is.

RTFM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	4	75 - 77		
Camel 2 nd	4	243 - 275		
Camel 3 rd	8	242 - 267		
perldoc	perlref			
Cookbook 2 nd	11	407 - 443		
Learning 3 rd	В	296	light	
Learning 4 th				

Also Chapter 1 in *Advanced Perl Programming* and Tom Christiansen's FMTEYEWTK (Far More Than You Ever Wanted To Know) tutorials contain information about references. They're available from the Perl website (<u>http://www.perl.com/</u>)

14.3 Uses for references

There are three main uses for Perl references.

14.3.1 Creating complex data structures

Perl references can be used to create complex data structures, for instance hashes of arrays, arrays of hashes, hashes of hashes, and more.

14.3.2 Passing arrays and hashes to subroutines and functions

Since all arguments to subroutines are flattened to a list of scalars, it is not possible to use two arrays as arguments and have them retain their individual identities.

The above example will print out a b c d e f.

References can be used in these circumstances to keep arrays and hashes passed as arguments separate.

14.3.3 Object oriented Perl

References are used extensively in object oriented Perl. In fact, Perl objects *are* references to data structures.

14.4 Creating and dereferencing references

To create a reference to a scalar, array or hash, we prefix its name with a backslash:

```
my $scalar = "This is a scalar";
my @array = qw(a b c);
my %hash = (
        'sky'
                               'blue',
                       =>
        'apple'
                               'red',
                      =>
        'grass'
                               'areen'
                       =>
);
my $scalar_ref = \$scalar;
my sarray_ref = \@array;
my hash_ref = \
```

Note that all references are scalars, because they contain a single item of information: the memory address of the actual data.

This is what a reference looks like if you print it out:

```
% perl -e 'my $foo_ref = \$foo; print "$foo_ref\n";'
SCALAR(0x80c697c)
% perl -e 'my $bar_ref = \@bar; print "$bar_ref\n";'
ARRAY(0x80c6988)
% perl -e 'my $baz_ref = \%baz; print "$baz_ref\n";'
HASH(0x80c6988)
```

You can find out whether a scalar is a reference or not by using the ref() function, which returns a string indicating the type of reference, or undef if a scalar is not a reference.

Src	Chap	Pgs	#
Nutshell 2 nd	4 5	77 126	
Camel 2 nd	3 4	204 251 - 252	Other tricks with references
Camel 3 rd	8 29	258 773	
perldoc	-f ref		
Cookbook 2 nd	11 13	409 499	
Learning 3 rd			
Learning 4 th			

Also in Advanced Perl Programming.

Dereferencing (getting at the actual data that a reference points to) is achieved by prepending the appropriate variable-type punctuation to the name of the reference. For instance, if we have a hash reference <code>\$hash_reference</code> we can dereference it by looking for <code>%\$hash_reference</code>

```
my $new_scalar = $$scalar_ref;
my @new_array = @$array_ref;
my %new_hash = %$hash_ref;
```

In other words, wherever you would normally put a variable name (like new_scalar) you can put a reference variable (like \$scalar_ref).

Here's how you access array elements or slices, and hash elements:

print	\$\$array_ref[0];	#	prints the first element of the
		#	array referenced by \$array_ref
print	@\$array_ref[02];	#	prints an array slice
print	\$\$hash_ref{'sky'};	#	prints a hash element's value

The other way to access the value that a reference points to is to use the "arrow"

notation. This notation is usually considered to be better Perl style than the one shown above, which can have precedence problems and is less visually clean.

print \$array_ref->[0];
print \$hash_ref->{'sky'};

14.5 Passing multiple arrays/hashes as arguments

If we were attempt to pass two arrays together to a subroutine, they would be flattened out to form one large array.

If we want to keep them separate, we need to pass the arrays by references:

```
myreflist(\@fruit, \@rodents);
sub myreflist {
    my ($firstref, $secondref) = @_;
    print "First list:\n";
    foreach (@$firstref) {
        print "$_\n";
    }
    print "Second list:\n";
    foreach (@$secondref) {
            print "$_\n";
    }
}
```

14.6 Complex data structures

References are most often used to create complex data structures. Since hashes and arrays only accept scalars as elements, references (which are inherently scalars) can be used to create arrays of arrays or hashes, and hashes of arrays or hashes.

```
my %categories = (
    'fruits' => \@fruits,
    'rodents' => \@rodents,
    'books' => \@books,
);
# to print out "gerbil"...
print $categories{'rodents'}->[3];
```

14.7 Anonymous data structures

We can use anonymous data structures to create complex data structures, to avoid having to declare many temporary variables. Anonymous arrays are created by using square brackets instead of round ones. Anonymous hashes use curly brackets instead of round ones.

```
# the old two-step way:
my @array = qw(a b c d);
my sarray_ref = \@array;
# if we get rid of $array_ref, @array will still hang round using
# up memory. Here's how we do it without the intermediate step,
# by creating an anonymous array:
my $array_ref = ['a', 'b', 'c', 'd'];
# look, we can still use qw() too...
my $array_ref = [qw(a b c d)];
# more useful yet, put these anon arrays straight into a hash:
my %transport = (
        'cars'
                      =>
                            [qw(toyota ford holden porsche)],
        'planes' =>
                            [qw(boeing harrier)],
        'boats'
                            [qw(clipper skiff dinghy)],
                     =>
);
```

The same technique can be used to create anonymous hashes:

```
С
                   3
        =>
);
my hash_ref = \
# the quicker way, with an anonymous hash:
my $hash_ref = {
      a
                   1,
            =>
                   2,
      b
         =>
      с
                   3
           =>
};
```

14.8 Exercises

- 1. Create a complex data structure as follows:
 - a. Create a hash called <code>%pizza_prices</code> which contains prices for small, medium and large pizzas.
 - b. Create a hash called <code>%pasta_prices</code> which contains prices for small, medium and large serves of pasta.
 - c. Create a hash called <code>%milkshake_prices</code> which contains prices for small, medium and large milkshakes.
 - d. Create a hash containing references to the above hashes, so that given a type of food and a size you can find the price of it.
 - e. Convert the above hash to use anonymous data structures instead of the original three pizza, pasta and milkshake hashes
 - f. Add a new element to your hash which contains the prices of salads

(Answer: exercises/answers/food.pl)

2. Create a subroutine which can be passed a scalar and a hash reference. Check whether there is an element in the hash which has the scalar as its key. Hint: use exists for this. (Answer: exercises/answers/exists.pl)
14.9 Section summary

- References are scalar data consisting of the memory address of a piece of Perl data, and can be used in arrays, hashes, etc wherever you would use a normal scalar
- References can be used to create complex data structures, to pass multiple arrays or hashes to subroutines, and in object-oriented Perl.
- References are created by prepending a backslash to a variable name.
- References are dereferenced by replacing the name part of a variable name (eg foo in \$foo) with a reference, for example replace foo with \$foo_ref to get \$\$foo_ref
- References to arrays and hashes can also be dereferenced using the arrow -> notation.
- References can be passed to subroutines as if they were scalars.
- References can be included in arrays or hashes as if they were scalars.
- Anonymous arrays can be made by using square brackets instead of round; anonymous hashes can be made by using curly brackets instead of round. These can be assigned directly to a reference, without any intermediate step.

Chapter 15: About databases

In this chapter...

This chapter talks about databases in general, and the different types of databases which can be used with Perl.

15.1 What is a database?

- A database is a collection of related information.
- The data stored in a database is persistent.

15.2 Types of databases

There are many different types of databases, including:

- Flat-file text databases
- Associative flat-file databases such as Berkeley DB
- Relational databases
- Object databases
- Network databases
- · Hierarchical databases such as LDAP

Relational databases are by far the most useful type commonly available, and this training module focusses largely on them, after looking briefly at flat file text databases.

15.3 Database management systems

A database management system (DBMS) is a collection of software which can be used to create, maintain and work with databases. A client/server database system is one in which the database is stored and managed by a database server, and client software is used to request information from the server or to send commands to the server.

15.4 Uses of databases

Databases are commonly used to store bodies of data which are too large to be managed on paper or through simple spreadsheets. Most businesses use databases for accounts, inventory, personnel, and other record keeping. Databases are also becoming more widely used by home users for address books, cd collections, recipe archives, etc. There are very few fields in which databases cannot be used.

15.5 Chapter summary

- A database is a collection of related information.
- Data stored in a database is persistent
- There are a number of different types of databases, including flat file, relational, and others
- Database management systems are collections of software used to manage databases
- Databases are widely used in many fields

Chapter 16: Textfiles as databases

In this chapter...

In this chapter we investigate text-based or "flat file" databases and how to use Perl to manipulate them. We also discuss some of the limitations of this database format.

16.1 Delimited text files

A delimited text file is one in which each line of text is a record, and the fields are separated by a known character.

The character used to delimit the data varies according to the type of data. Common delimiters include the tab character (\t in Perl) or various punctuation characters. The delimiter should always be one which does not appear in the data.

Delimited text files are easily produced by most desktop spreadsheet and database applications (eg Microsoft Excel, Microsoft Access). You can usually choose "File" then "Save As" or "Export", then select the type of file you would like to save as.

Imagine a file which contains peoples' given names, surnames, and ages, delimited by the pipe (1) symbol:

```
Fred|Flintstone|40
Wilma|Flintstone|36
Barney|Rubble|38
Betty|Rubble|34
Homer|Simpson|45
Marge|Simpson|39
Bart|Simpson|11
Lisa|Simpson|9
```

The file above is available in your exercises directory as delimited.txt.

16.1.1 Reading delimited text files

To read from a delimited text file:

```
#!/usr/bin/perl -w
use strict;
open (INPUT, "delimited.txt") or die "Can't open data file: $!";
while (<INPUT>) {
```

```
chomp;  # remove newline
my @fields = split(/\|/, $_);
print "$fields[1], $fields[0]: $fields[2]\n";
}
close INPUT;
This should print out:
Flintstone, Fred: 40
Flintstone, wilma: 36
...
And so on.
```

16.1.2 Searching for records

One of the common uses of databases is to search for specific records.

}

close INPUT;

16.1.3 Sorting records

Sorting records from a flat text database can be quite difficult. Simply sorting the items line by line is one simplistic approach:

```
close INPUT;
```

The above technique can only sort on the first field of the data (in the case of our example, that would be the given name) and may have difficulties when it encounters the delimiter.

To sort by any other field, we would first need to load the data into a list of lists (using references), then use the sort() function's optional first argument to specify a subroutine to use for sorting:

```
#!/usr/bin/perl -w
use strict;
open (INPUT, "delimited.txt") or die "Can't open data file: $!";
while (<INPUT>) {
```

```
chomp;
        my @this_record = split(/\|/, _);
        # build a list-of-lists containing references to each record
        push (@records, \@this_record);
}
# sort takes an optional argument of what subroutine to use to sort
# the data...
my @sorted = sort given_name_order @records;
foreach $record (@sorted) {
        # we have to print the items via a reference to the array...
        print "$record->[1], $record->[0]: $record->[2]\n";
}
# subroutine to implement sorting order
sub given_name_order {
        $a->[0] cmp $b->[0];
}
```

Obviously this can be quite tricky, especially if the programmer is not totally familiar with Perl references. It also requires loading the entire data set into memory, which would be very inefficient for large databases.

16.1.4 Writing to delimited text files

The most useful function for writing to delimited text files is join, which is the logical equivalent of split.

```
#!/usr/bin/perl -w
use strict;
open OUTPUT, ">>delimited.txt" or die "Can't open output file: $!";
my @record = qw(George Jetson 35);
```

```
print OUTPUT join("|", @record), "\n";
```

16.2 Comma-separated variable (CSV) files

Comma separated variable files are another format commonly produced by spreadsheet and database programs. CSV files delimit their fields with commas, and wrap textual data in quotation marks, allowing the textual data to contain commas if required:

```
"Fred", "Flintstone",40
"Wilma", "Flintstone",36
"Barney", "Rubble",38
"Betty", "Rubble",34
"Homer", "Simpson",45
"Marge", "Simpson",39
"Bart", "Simpson",11
"Lisa", "Simpson",9
```

CSV files are harder to parse than ordinary delimited text files. The best way to parse them is to use the Text::ParseWords module:

```
#!/usr/bin/perl -w
use strict;
use Text::ParseWords;
open INPUT, "csv.txt" or die "Can't open input file: $!";
while (<INPUT>) {
    my @fields = quotewords("," 0, $_);
}
```

The three arguments to the quotewords () routine are:

- The delimiter to use
- Whether to keep any backslashes that appear in the data (zero for no, one for yes)
- A list of lines to parse (in our case, one line at a time)

16.3 Problems with flat file databases

16.3.1 Locking

When using flat file databases without locking, problems can occur if two or more people open the files at the same time. This can cause data to be lost or corrupted.

If you are implementing a flat file database, you will need to handle file locking using Perl's flock function.

16.3.2 Complex data

If your data is more complex than a single table of scalar items, managing your flat file database can become extremely tedious and difficult.

16.3.3 Efficiency

Flat file databases are very inefficient for large quantities of data. Searching, sorting, and other simple activities can take a very long time and use a great deal of memory and other system resources.

16.4 Chapter summary

- The two main types of text database use either delimited text or comma separated variables to store data
- Delimited text can be read using Perl's split function and written using the join function
- Comma separated files are most easily read using the Text::ParseWords module
- There are several problems with flat file databases including locking, efficiency, and difficulties in handling more complex data

Chapter 17: Relational databases

In this chapter...

The first section of this training session focuses on database theory, and covers relational database systems, and SQL - the language used to talk to them.

17.1 Tables and relationships

In a relational database, data is stored in tables. Each table contains data about a particular type of entity (either physical or conceptual).

For instance, our sample database is the inventory and sales system for Acme Widget Co. It has tables containing data for the following entities:

Table	Description
stock_item	Inventory items
customer	Customer account details
saleperson	Sales people working for Acme Widget Co.
sales	Sales events which occur

Table 17-1. Acme Widget Co Tables

Tables in a database contain fields and records. Each record describes one entity. Each field describes a single item of data for that entity. You can think of it like a spreadsheet, with the rows being the records and the columns being the fields, thus:

Table 17-2. Sample table

ID number	Description	Price	Quantity in stock
1	widget	\$9.95	12
2	gadget	\$3.27	20

Every table must have a *primary key*, which is a field which uniquely identifies the record. In the example above, the Stock ID number is the primary key.

The following figures show the tables used in our database, along with their field names and primary keys (in bold type).



Illustration 17-1: UML-style ERD of the example schema

Table 17-3. the stock item table

stock_item
id
description
price
quantity

Table 17-4. the customer table

customer	
id	
name	
address	
suburb	

state postcode

Table 17-5. the salesperson table

salesperson	
id	
name	

Table 17-6. the sales table

sales
id
sale_date
salesperson_id
customer_id
stock_item_id
quantity
price

17.2 Structured Query Language

SQL is a semi-English-like language used to manipulate relational databases. It is based on an ANSI standard, though very few SQL implementations actually adhere to the standard.

SQL statements are mostly case insensitive these days. While most books and references use upper-case, these notes use lower-case throughout for readability, and because the likelihood of needing to deal with older databases which only understand upper-case is becoming increasingly slim.

The syntax given in these course notes is cut down for simplicity; for full information, consult your database system's documentation. The MySQL documentation is available on our system in /usr/doc/mysql-doc and /usr/doc/mysqlmanual, or by pointing your web browser at http://training.netizen.com.au/.

17.2.1 General syntax

SQL is case usually insensitive, apart from table and field names (which may or may not be case sensitive depending on what platform you're on -- on UNIX they are usually case sensitive, on Windows they usually aren't).

String data can be delimited with either double or single quotes. Numerical data does not need to be delimited.

Wildcards may be used when searching for string data. A % (percent) sign is used to indicated multiple characters (much as an asterisk is used in DOS or UNIX filename wildcards) while the underscore character (_) can be used to indicate a single character, similar to the ? under UNIX or DOS.

The following comparison operators may be used:

Operator	Meaning
=	Equality
>	Greater than
<	Less than
>=	Greater than or equal to
<=	Less than or equal to
\diamond	Inequality

 Table 17-7. Comparison Operators

like	Wildcard matching
	w navara mateming

In the following syntax examples, the term *condition* is used as shorthand for any expression which can be evaluated for truth, for instance 2 + 2 = 4 or name like "A%".

Conditions may be combined by using and and or; use round brackets to indicate precedence. For instance, name like "A%" or name like "B%" will find all records where the ``name" field starts with A or B.

17.2.1.1 SELECT

An SQL select statement is used to select certain rows from a table or tables. A select query will return as many rows as match the criteria.

```
select field1 [, field2, field3] from table1 [, table2]
where condition
order by field [desc]
```

select id, name from customer; select id, name from customer order by name; select id, name from customer order by name desc;

We can use a select statement to obtain data from multiple tables. This is referred to as a ``join".

select * from customer, sales where customer.id = sales.customer_id

17.2.1.2 INSERT

An insert query is used to add data to the database, a row at a time.

The columns names are optional to make typing queries easier. This is fine for interactive use, however it is very bad practice to omit them in programs. *Always* specify column names in insert statements.

insert into tablename (col_name1, col_name2, col_name3) values
(value1, value2, value3);

insert into stock_item (id, description, price, quantity) values (0, 'doodad', 9.95, 12);

Note that since the id field is an auto_increment field in the Acme inventory database we've set up, we don't need to specify a value to go in there, and just use zero instead --- whatever we specify will be replaced with the auto-incremented value. Auto-increment fields of some kind are available in most database systems, and are very useful for creating unique ID numbers.

17.2.1.3 DELETE

A delete query can be used to delete rows which match a given criteria.

delete from *tablename* where *condition*

delete from stock_item where quantity = 0;

17.2.1.4 UPDATE

The update query is used to change the values of certain fields in existing records.

update tablename set field1 = expression, field2 = expression
 where condition

update stock_item set quantity = (quantity - 1) where id = 4;

17.2.1.5 CREATE

The create statement is used to create new tables in the database.

primary key (colname)

)

Data types include (but are not limited to):

INT	an integer number
FLOAT	a floating point number
CHAR(<i>n</i>)	character data of exactly <i>n</i> characters
VARCHAR(n)	character data of up to <i>n</i> characters (field grows/shrinks to fit)
BLOB	Binary Large OBject
DATE	A date in YYYY-MM-DD format
ENUM	enumerated string value (eg "Male" or "Female")

Table 17-8. Some data types

Data types vary slightly between different database systems. The full range of MySQL data types is outlined in section 7.2 of the MySQL reference manual.

```
create table contactlist (
    id int not null auto_increment,
    name varchar(30),
    phone varchar(30),
    primary key (id)
```

)

17.2.1.6 DROP

The drop statement is used to delete a table from the database.

drop table *tablename*

drop table contactlist

17.3 Chapter summary

- A database table contains fields and records of data about one entity
- SQL (Structured Query Language) can be used to manipulate and retrieve data in a database
- A SELECT query may be used to retrieve records which match certain criteria
- An INSERT query may be used to add new records to the database
- A delete query may be used to delete records from the database
- An UPDATE query may be used to modify records in the database
- A CREATE query may be used to create new tables in the database
- A DROP query may be used to remove tables from the database

Chapter 18: MySQL

In this chapter...

In this section we examine the popular database MySQL, which is available for free for many platforms. MySQL is just one of many database systems which can be accessed via Perl's DBI module.

18.1 MySQL features

18.1.1 General features

- Fast
- Lightweight
- Command-line and GUI tools
- Supports a fairly large subset of SQL, including indexing, binary objects (BLOBs), etc
- Allows changes to structure of tables while running
- Wide userbase
- Support contracts available

18.1.2 Cross-platform compatibility

- Available for most UNIX platforms
- Available for Windows NT/95/98 (there are license differences)
- Available for OS/2
- Programming libraries for C, Perl, Python, PHP, Java, Delphi, Tcl, Guile (a scheme interpreter), and probably more...
- Open-source ODBC

18.2 Comparisions with other popular DBMSs

18.2.1 PostgreSQL

MySQL and PostgreSQL are very similar in many ways. MySQL is driven by one company while PostgreSQL is an open source project with major contributions coming from a variety of companies and individuals.

More information: http://www.postgresql.org/

18.2.2 Oracle, Sybase, etc

MySQL will not give you the features of Oracle or other enterprise-level database management systems. In particular, MySQL lacks triggers and views. The price you pay for this is that Oracle costs a lot, and requires heavy hardware to run on and is much more maintenance intensive. MySQL is better suited to small-to-medium database applications such as web-based database applications, and will do so happily on a common PC.

More information: http://www.oracle.com/

18.3 Getting MySQL

MySQL can be downloaded from http://www.mysql.com/or mirror sites worldwide. It is also available in packaged binary format for various operating system distributions, including RedHat and Debian linux.

Installation instructions come with the software, but in brief:

18.3.1 Red Hat Linux

Download the appropriate RPM packages, and type rpm -i packagename.rpm

MySQL is included with Fedora, Red Hat Enterprise, CentOS, and any other current Red Hat-derived Linuxes. So the standard package installers should have no trouble installing this for you. For instance;

yum install mysql

18.3.2 Debian Linux

Use apt-get, dselect, or dpkg to install the .deb packages. For instance, apt-get install mysql.

18.3.3 Compiling from source

Download the tar.gz file from http://www.mysql.com/ and read the README file. Then type ./configure, make, and make install.

18.3.4 Binaries for other platforms

Binaries are available for many platforms, including Windows and some commercial UNIX platforms. Follow the installation instructions found in the README file.

18.4 Setting up MySQL databases

A tool called mysqladmin is distributed with MySQL. This tool allows the database administrator (DBA) to create, remove, or otherwise manage databases.

create databasename	Create a new database
drop databasename	Delete a database and all its tables
flush-hosts	Flush all cached hosts
flush-logs	Flush all logs
flush-tables	Flush all tables
kill id, id,	Kill mysql threads
password new-password	Change old password to new- password
processlist	Show list of active threads in server
reload	Reload grant tables
refresh	Flush all tables and close and open logfiles
shutdown	Take server down
status	Gives a short status message from the server
variables	Prints variables available
version	Get version info from server

Table 18-1. Mysqladmin commands:

More help for this command is available by typing mysqladmin --help from the command line or by reading the MySQL reference manual.

18.4.1 Creating the Acme inventory database

To create a database called inventory, we would perform the following steps as the user who has permission to run mysqladmin (eg root):

```
% mysqladmin create inventory
% mysqladmin reload
```

18.4.2 Setting up permissions

To set up security permissions for the inventory database, we would need to create appropriate records in the <code>mysql</code> database (that's right, it's a database which has the same name as the database server). This is the central repository for access control information for all databases served by your MySQL server.

Typically, you will want to:

- create an entry in the db table for the database
- set the default permissions for the database
- create an entry in the user table for any users who should be allowed to access the database
- · set default permissions for each user

All these are achieved by performing simple INSERT or UPDATE queries on the tables in question.

Select	May perform SELECT queries
Insert	May perform INSERT queries
Update	May perform UPDATE queries
Delete	May perform DELETE queries
Create	May create new tables
Drop	May drop (delete) tables
Reload	May reload the database
Shutdown	May shut down the database
Process	Has access to processes on the OS
File	Has access to files on the OS's file system

Table 18-2. Available permissions include ...

18.4.3 Creating tables

The SQL statements used to create tables are documented in the MySQL manual. CREATE statements are used to create each individual table by specifying the fields for each table, their data types and other options.

Below is an example --- these SQL statements create the Acme Widget Co. tables we will be working with throughout this session. The output you see is generated by the **mysqldump** program, and can be read back into a database via command line redirection, eg mysql database < filename.

```
#
# Table structure for table 'customer'
#
CREATE TABLE customer (
  id int(11) DEFAULT '0' NOT NULL auto_increment,
 name varchar(80),
  address varchar(255),
  suburb varchar(50),
  state char(3),
  postcode char(10),
 PRIMARY KEY (id)
);
#
# Table structure for table 'sales'
#
CREATE TABLE sales (
  id int(11) DEFAULT '0' NOT NULL auto_increment,
  sale_date date,
  customer_id int(11),
  salesperson_id int(11),
  stock_item_id int(11),
  quantity int(11),
  price float(4,2),
  PRIMARY KEY (id)
);
#
# Table structure for table 'salesperson'
#
CREATE TABLE salesperson (
  id int(11) DEFAULT '0' NOT NULL auto_increment,
  name varchar(80),
  PRIMARY KEY (id)
);
#
```

```
# Table structure for table 'stock_item'
#
CREATE TABLE stock_item (
    id int(11) DEFAULT '0' NOT NULL auto_increment,
    description varchar(80),
    price float(4,2),
    quantity int(11),
    PRIMARY KEY (id)
);
```
18.5 The MySQL client

To talk to any database server, you will need to use a client of some kind. MySQL comes with a text-based client by default, but there are graphical clients available, as well as ODBC drivers to allow you to interact with a MySQL database from Windows applications such as Microsoft Access.

The command line client can be invoked from the command line with the mysql command. The mysql command takes a database name as a required argument, as well as other optional arguments such as -p, which causes the client to ask for a password for access to the database if access controls have been set up.

You can see all the options available on the command line by typing mysql - help.

ADVANCED

You can set up access controls on a database by editing the data in the mysql database (i.e. type mysql mysql on the command line) or by using the mysqlaccess command. Type mysqlaccess --help for more information about this command.

\$ mysql -p databasename

Welcome to the MySQL monitor. Commands end with ; or $\g.$ Your MySQL connection id is 2 to server version: 3.21.33b

Type 'help' for help.

mysql>

The MySQL client allows you to type in commands on one or many lines. When you finish a statement, type *;* to end, same as for Perl.

To quit the client, type quit or q.

For a full outline of commands available in the client, type help or h. It will give you this message:

```
mysql> \h
MySQL commands:
help
                Display this text
        (\h)
?
        (\h)
                Synonym for `help'
clear
                Clear command
        (\c)
connect (\r)
                Reconnect to the server. Optional arguments are db
and host
edit
                Edit command with $EDITOR
        (\e)
                Exit mysql. Same as quit
exit
        ()
                Send command to mysql server
go
        (\g)
print
        (\p)
                print current command
quit
        (\q)
                Quit mysql
rehash (\#)
                Rebuild completion hash
status
       (\s)
                Get status information from the server
        (\u)
                Use another database. Takes database name as
use
argument
```

Connection id: 1 (Can be used with mysqladmin kill)

18.6 Understanding the MySQL client prompts

The prompt that shows when you are using the MySQL client tells you a lot about what's going on.

The normal prompt looks like this:

mysql>

This means it is waiting for you to enter an SQL query.

If you are in the middle of entering an SQL query, it will be waiting for a semicolon to terminate the query, and will look like this:

->

If you have opened a set of quotes but not closed them, you will see one of these prompts:



18.7 Exercises

- 1. Connect to a database which has the same name as your login (for instance, train01) by typing **mysql -p train01** (the -p flag causes it to ask you for your password, which in this case is the same as your login password). The database you are connecting to is your own personal copy of the Acme Widget Co. inventory and sales database mentioned in the previous section
- 2. Type show tables to show a list of tables in this database
- 3. Type describe customer to see a description of the fields in the table customer
- 4. Type select * from customer to perform a simple SQL query
- 5. Try selecting fields from other tables. Try both select * and select field1, field2 type queries.
- 6. Use the where clause to limit which records you select
- 7. Use the order by clause to change the order in which records are returned
- 8. Insert a record into the customer table which contains your own name and address details
- 9. Update the price of widgets in the stock_item table to change their price to \$19.95

When developing database applications, it is often useful to keep a client program such as this one open to test queries or check the state of your data. You can open multiple telnet sessions to our training system to do this if you wish.

18.8 Chapter summary

- MySQL is one of many database systems which can be used as the back-end to a web site
- MySQL can be downloaded from http://www.mysql.com/ or mirror sites
- The MySQL command line client can be used to interact with MySQL databases
- The MySQL client allows the user to type in SQL queries and prints results to the screen.

Chapter 19: The DBI and DBD modules

In this chapter...

In this section we look at the Perl module which can be used to interact with many database servers: DBI.

19.1 What is DBI?

Like the Perl modules discussed in last week's CGI programming course, the DBI and DBD modules are written by Perl people and distributed free via CPAN (the Comprehensive Perl Archive Network).

DBI stands for "Database Interface" while DBD stands for "Database Driver". You need both types of modules, working together, in order to access databases using Perl.

RTFM!				
Src	Chap	Pgs	#	
Nutshell 2 nd	12	411 - 423		
Camel 2 nd				
Camel 3 rd				
perldoc	DBI			
Cookbook 2 nd	14	562 - 578		
Learning 3 rd	В	291	light	
Learning 4 th				

19.2 Supported database types

Databases supported by Perl's DBI module include:

- Oracle
- Sybase
- Informix
- MySQL
- Msql
- Ingres
- Postgres
- Xbase
- DB2
- $\boldsymbol{\cdot}$... and more

19.3 How does DBI work?

DBI is a generic interface which acts as a "funnel" between the programmer and multiple databases.

DBI protects you from needing to know the minutiae of connecting to different databases by providing a consistent interface for the programmer. The only thing you need to vary is the connection string, to indicate what sort of database you wish to connect to.

To use DBI, you need to install the DBI module from CPAN, as well as any DBD modules for the databases you use. For instance, to use MySQL you need to install the DBD::Mysql module.

ADVANCED

To install DBI, download the DBI module from CPAN (http://www.perl.com/CPAN), unzip it using a command like **tar -xzvf DBI.tar.gz**, then follow the instructions in the **README** file distributed with the module.

19.4 DBI/DBD syntax

The syntax of the database modules is best found by using the **perldoc** command. **perldoc DBI** will give you general information applicable to all DBI scripts, while **perldoc DBD::***yourdatabase* will give information specific to your own database. In our case, we use **perldoc DBD::mysql**.

DBI is an object oriented Perl module, like the Text::Template and Mail::Mailer modules covered in the CGI Programming in Perl training module. This means that when we connect to the database we will be creating an object which is called a "database handle" which refers to a specific session with the database. Thus we can have multiple sessions open at once by creating multiple database handles.

We can also create statement handle objects, which are Perl objects which refer to a previously prepared SQL statement. Once we have a statement handle, we can use it to execute the underlying SQL as often as we want.

19.4.1 Variable name conventions

The following variable name conventions are used in the DBD/DBI documentation:

Variable name	Meaning	
\$dbh	database handle object	
\$sth	statement handle object	
\$rc	Return code (boolean: true=ok, false=error)	
\$rv	Return value (usually an integer)	
@ary	List of values returned from the database, typically a row of data	
\$rows	Number of rows processed (if available, else -1)	

Table 19-1. DBI module variable naming conventions

19.5 Connecting to the database

```
my $driver = 'mysql';
my $username = undef;
                                   # your database username
my $password = undef;
                                   # your database password
# note that username and password should be assigned to if your
database
# uses authentication (ie requires you to log in)
# we set up a connection string specific to this database
my $dsn = "DBI:$driver:database=$database";
# make the actual connection - this returns a database handle we can
use later
my $dbh = DBI->connect($dsn, $username, $password);
# when you're done (at the end of your script)
$dbh->disconnect();
```

use DBI;

19.6 Executing an SQL query

19.7 Doing useful things with the data

```
# get an array full of the next row of data that matches the query
# (the most common, and simplest, case)
while ( my @ary = $sth->fetchrow_array() ) {
        print "The first field is $ary[0]\n";
}
# get a hash reference instead
# (the more complicated, but more useful, version)
while ( my $hashref= $sth->fetchrow_hashref() ) {
        print "Name is $hashref->{'name'}\n";
}
# you can also get an arrayref
# (equally complicated and not quite as useful)
while ( my $ary_ref = $sth->fetchrow_arrayref() ) {
        print "The first field is $ary_ref->[0]\n";
}
```

ADVANCED

Of the above methods, fetchrow_array() is the only one that does not require an understanding of Perl references. References are not a beginner-level topic, but for those who are interested, they are documented in chapter 4 of the Camel. They are worth learning if only for the added benefit of being able to access fields by name when using the fetchrow_hashref method.

19.8 An easier way to execute non-SELECT queries

If you wish to execute a query such as INSERT, UPDATE, or DELETE, you may find it easier to use the do() method:

This method returns the number of rows affected, or undef if there is an error.

19.9 Quoting special characters in SQL

Sometimes you want to use a value in your SQL which may contain characters which have special behavior in SQL, such as a percent sign or a quote mark. Luckily, there is a method which can automatically escape all special characters:

```
my $string = "20% off all stock";
my $clean string = $dbh->quote($string);
```

19.10 Exercises

- 1. Use exercises/scripts/easyconnect.pl to connect to your Acme Widget Co. database. You will need to edit some of the lines at the top.
- 2. Use a while loop to output data a row at a time
- 3. Check all your statements for indications of failure, and output messages to the user using warn () if any of the steps fail.

19.10.1 Advanced exercises

- 1. If you wish, you can use a hash reference instead of an array
- 2. Change the SQL in easyconnect.pl to use a non-SELECT statement, and use the do method instead of the prepare and execute methods. Don't forget to check the return value!

19.11 Chapter summary

- The DBI module provides a consistent interface to a variety of database systems
- The DBI module can be downloaded from CPAN
- Documentation for the DBI module can be found by typing peridoc DBI

Chapter 20: Acme Widget Co. Exercises

In this chapter...

In the second half of this training module, we will be tying together what we have learned about SQL and DBI, and creating a simple application for Acme Widget Co. to assist them in inventory management, sales, and billing.

20.1 The Acme inventory application

In your exercises/ directory you will find a subdirectory called acme/ which contains the outline of the Acme inventory application which you will build upon for the rest of today.

20.2 Listing stock items

The shell of a stock-listing script is available in your exercises/acme/ directory as stocklist.pl.

```
#!/usr/bin/perl -w
use strict;
use DBI;
my $driver = 'mysql';
my $database = 'trainxx';
my $username = 'trainXX';
my $password = 'your_password_here';
my $dsn = "DBI:$driver:database=$database";
my $dbh = DBI->connect($dsn, $username, $password)
        || die $DBI::errstr;
my $sql_statement = "select * from stock_item";
my $sth = $dbh->prepare($sql_statement);
$sth->execute() or die ("Can't execute SQL: " . $dbh->errstr());
while (my @ary = $sth->fetchrow_array()) {
        print <<"END";</pre>
               $ary[0]
ID:
Description: $ary[1]
Price:
               $ary[2]
Quantity:
               $ary[3]
END
}
```

```
$dbh->disconnect();
```

- 1. Fill in the variables indicated (\$database, \$sql_statement, etc)
- 2. Test your script from the command line
- 3. Sort the output in alphabetical order by Description

20.2.1 Advanced exercises:

- 1. If you are familiar with Perl references, convert the script to use fetchrow_hashref()
- 2. Ask the user to specify a field to sort by, either as a command line argument or on STDIN. If the sort order parameter is given, use it to change the sort order in your SQL statement and re-output the result, otherwise default to something sensible such as ID

20.3 Adding new stock items

- 1. Write a script which prompts the user for input, asking for values for description, quantity and price. Remember that the stock item's ID will be automatically filled in by the database, as it is an "auto increment" field.
- 2. Next, create an SQL query to add a record to the database. Output a message to the user indicating the success (or failure) of the operation. A sample script to get you started is available in exercises/acme/addstock.pl

20.3.1 Advanced exercises

- 1. Check that the price is a number (use regular expressions for these checks)
- 2. Check that it has two decimal places
- 3. Check that the number of items in stock is a number

20.4 Entering a sale into the system

- 1. The program exercises/acme/sale.pl provides an interface which can be used to input data pertinent to the occurence of a sale
- 2. Write a script which records the sale in the sales table
- 3. Your script will also have to update the stock_item table to reduce the number of items still in stock.
- 4. What happens if you try to buy/sell more items than are available? Put in a check to stop this from happening.

20.5 Creating sales reports

- 1. Copy the code from the previous example's script to create a script that asks the user for a salesperson's ID number and a start and end date.
- 2. Use the script to output a sales report for the chosen salesperson for the period between the two dates.

20.5.1 Advanced exercises

1. Create an extra option for "all" sales people, which shows all the sales people in descending order of sales made. You may need to use an SQL group by clause to achieve this.

20.6 Searching for stock items

- 1. Create a script which asks a user for a string to search for in a stock item's description (eg "dynamite").
- 2. Allow the user to choose either "Full name", "Beginning of name" or "Part of name" as a search type.
- 3. Create different SQL queries using LIKE to search the data depending on their choices

20.6.1 Advanced exercises

Change the script so that people can use DOS/UNIX style wildcards (* and ?) then use their wildcard expression in your SQL query - convert the wildcards to SQL-style wildcards by using regular expressions

Chapter 21: Reference s

In this chapter...

This section is included as an optional topic. It is intended for those who have experience in C or other languages which use pointers and references.

RT FM!

References are covered at length in the first chapter of the O'Reilly book *Advanced Perl Programming* by Sriram Srinivasan (the "Panther" book). Lastly, **perldoc perlref** contains online documentation related to Perl references.

21.1 Uses for Perl references

- creating complex data structures, for example multi-dimensional arrays
- passing multiple arrays and hashes to subroutines and functions without them getting smushed together
- creating anonymous data structures

21.2 Creating and deferencing

To create a reference to a scalar, array or hash, we prefix its name with a backslash:

Note that all references are scalars, because they contain a single item of information - the memory address of the actual data.

Dereferencing (getting at the value that a reference points to) is achieved by prepending the appropriate variable-type punctuation to the name of the reference. For instance, if we have a hash reference <code>\$hash_reference</code> we can dereference it by looking for <code>%\$hash_reference</code>.

```
my $new_scalar = $$scalar_ref;
my @new_array = @$array_ref;
my %new_hash = %$hash_ref;
```

In other words, wherever you would normally put a variable name (like new_scalar) you can put a reference variable (like \$scalar_ref).

Here's how you access array elements or slices, and hash elements:

print	\$\$array_ref[0];	#	prints the first element of the
		#	array referenced by <pre>\$array_ref</pre>
print	\$\$array_ref[02];	#	prints an array slice
print	\$\$hash_ref{'sky'};	#	prints a hash element's value

The other way to access the value that a reference points to is using the "arrow" notation. This notation is usually considered to be better Perl style than the one shown above, which can have precedence problems and is less visually clean.

print \$array_ref->[0];
print \$hash_ref->{'sky'};

RT FM!

The Panther book describes a good way to visualise this method. Ask your instructor to demonstrate it or to loan you a copy of the book if you need a better understanding of the above syntax.

21.3 Complex data structures

We can use references to create complex data structures, such as this hash in which the values are arrays rather than scalars. Actually, they are scalars, since the array references are scalars, but they point to arrays.

```
my @fruits = qw(apple orange pear banana);
my @rodents = qw(mouse rat hamster gerbil rabbit);
my @books = qw(camel llama panther);
my %categories = (
          'fruits'
                                                  \ensuremath{\mathsf{Q}}fruits,
                              =>
          'rodents'
                                                  \ensuremath{\colored{cond}}
                             =>
          'books'
                                                  \ensuremath{\mathsf{Qbooks}},
                              =>
);
# to print out "gerbil"...
print $categories->{'rodents'}->[3];
```

21.4 Passing multiple arrays/hashes as arguments

If we were to attempt to pass two arrays together to a function or subroutine, they would be flattened out to form one large array:

```
mylist(@fruit, @rodents);
# print out all the fruits then all the rodents
sub mylist {
    my @list = @_;
    foreach (@list) {
        print "$_\n";
    }
}
```

If we want them kept separate, pass references:

```
myreflist(@fruit, @rodents);
sub myreflist {
    my ($firstref, $secondref) = @_;
    print "First list:\n";
    foreach (@$firstref) {
        print "$_\n";
    }
    print "Second list:\n";
    foreach (@$secondref) {
            print "$_\n";
    }
}
```

21.5 Anonymous data structures

Lastly, references can be used to create anonymous data structures which are destroyed once you're done with them. An anonymous array is created by using square brackets instead of round ones. An anonymous hash uses curly brackets instead of round ones.

```
# the old two-step way:
my @array = qw(a b c d);
my sarray_ref = \@array;
# if we get rid of $array_ref, @array will still hang round using
# up memory. Here's how we do it without the intermediate step:
my $array_ref = ['a', 'b', 'c', 'd'];
# look, we can still use qw() too...
my $array_ref = [qw(a b c d)];
# more useful yet:
my %transport = (
        'cars'
                                 [qw(toyota ford holden porsche)],
                        =>
        'planes'
                                 [qw(boeing harrier)],
                        =>
        'boats'
                                 [qw(clipper skiff dinghy)],
                        =>
);
```

21.6 Chapter summary

- References may be used to create complex data structures, pass multiple arrays and hashes to subroutines, and to create anonymous data structures
- References are created by prefixing the name of a variable with a backslash
- References are dereferenced by using the name of a reference (including the dollar sign) where we would usually use the alphanumeric name of a variable, or by using the arrow notation.
- References can be included in Perl data structures anywhere you might ordinarily find scalars.
- References to anonymous arrays may be created by initialising an array using square brackets instead of round ones.
- References to anonymous hashes may be created by initialising an hash using curly brackets instead of round ones.

Chapter 22: What is CGI?

In this chapter...

In this section we will define the term CGI and learn how web servers use CGI to provide dynamic and interactive material. We explore the Hypertext Transfer Protocol as it applies to both static and CGI-generated content, and examine raw HTTP requests and responses by telnetting to a web server.

22.1 Definition of CGI

CGI is the Common Gateway Interface, a standard for programs to interface with information servers such as HTTP (web) servers. CGI allows the HTTP server to run an executable program or script in response to a user request, and generate output on the fly. This allows web developers to create dynamic and interactive web pages.

CGI programs can be written in any language. Perl is a very common language for CGI programming as it is largely platform independent and the language's features make it very easy to write powerful applications. However, some CGI programs are written in C, shell script, or other languages.

It is important to remember that CGI is not a language in itself. CGI is merely a type of program which can be written in any language.
22.2 Introduction to HTTP

To understand how CGI works, you need some understanding of how HTTP works.

HTTP stands for HyperText Transfer Protocol, and (not very surprisingly) is the protocol used for transferring hypertext documents such as HTML pages on the World Wide Web.

For the purposes of this course, we will only be looking at HTTP version The current version, 1.1, is specified in RFC 2068 and contains many more features, but none of them are necessary for a basic understanding of CGI programming. An HTTP cheat-sheet, containing some common terminology and a table of status codes, appears in Appendix E.

RT FM!

RFCs, or "Request For Comment" documents, can be obtained from the Internet Engineering Task Force (IETF) website (http://www.ietf.org/) or from mirrors such as the RFC mirror at Monash University (<u>ftp://ftp.monash.edu.au/pub/rfc/</u>).

A simple HTTP transaction, such as a request for a static HTML page, works as follows:

- 1. The user types a URL into his or her browser, or specifies a web address by some other means such as clicking on a link, choosing a bookmark, etc
- 2. The user agent connects to port 80 of the HTTP server
- 3. The user agent sends a request such as GET /index.html
- 4. The user agent may also send other headers
- 5. The HTTP server receives the request and finds the requested file in its filesystem
- 6. The HTTP server sends back some HTTP headers, followed by the contents of the requested file
- 7. The HTTP server closes the connection

When a user requests a CGI program, however, the process changes slightly:

- 1. The user agent sends a request as above
- 2. The HTTP server receives the request as above
- 3. The HTTP server finds the requested CGI program in its file system
- 4. The HTTP server executes the program
- 5. The program produces output
- 6. The output includes HTTP headers
- 7. The HTTP server sends back the output of the program
- 8. The HTTP server closes the connection

22.3 Terminology

authentication

The process by which a client sends username and password information to the server, in an attempt to become authorized to view a restricted resource.

client

An application program that establishes connections for the purpose of sending requests.

Content-type

The media type of the body of the response, as given in the Content-type: header. Examples include text/html, text/plain, image/gif, etc.

method

Indicates what the server should do with a resource. Case sensitive. Valid methods include: GET, HEAD, POST

request

An HTTP request message sent by a client to a server

resource

A network data object or service which can be identified by a URI.

response

An HTTP response message sent by a server to a client

server

An application program that accepts connections in order to service requests by sending back responses.

status code

A 3-digit integer indicating the result of the server's attempt to understand and satisfy the request. A table of status codes and their meanings appears below.

Uniform Resource Identifier (URI)

URIs are formatted strings which identify - via name, location, or any other characteristic - a network resource.

Uniform Resource Locator (URL)

A web address. May be expressed absolutely (eg http://www.example.com/services/index.html) or in relation to a base

URI (eg ../index.html) See also URI.

user agent

The client which initiates a request. These are often browsers, editors, spiders (web-traversing robots) or other end-user tools.

22.4 HTTP status codes

Code	Meaning
200	ОК
201	Created
202	Accepted
204	No Content
301	Moved Permanently
302	Moved Temporarily
304	Not Modified
400	Bad Request
401	Unauthorized
403	Forbidden
404	Not Found
500	Internal Server Error
501	Not Implemented
502	Bad Gateway
503	Service Unavailable

Table 22-1. HTTP status codes

22.5 HTTP Methods

22.5.1.1 GET

The GET method means retrieve whatever information is identified by the request URI. If the request URI refers to a data-producing process (eg a CGI program), it is the produced data which is returned, and not the source text of the process.

22.5.1.2 HEAD

The HEAD method is identical to GET except that the server will only return the headers, not the body of the resource. The meta-information contained in the HTTP headers in response to a HEAD request should be identical to the information sent in response to a GET request. This method can be used to obtain meta-information about the resource without transferring the body itself.

22.5.1.3 POST

The POST method is used to request that the server use the information encoded in the request URI and use it to modify a resource such as:

- Annotation of an existing resource
- Posting a message to a bulletin board, newsgroup, mailing list, or similar group of articles
- Providing data {such as the result of submitting a form} to a data-handling process
- Updating a database

22.6 Exercises

The HTTP request/response process is usually transparent to the user. To see what's going on, let's connect directly to the web server and see what happens.

Login to the system as for the Introduction to Perl course:

- 1. Open the telnet program, TeraTerm
- 2. Connect to the training server (your instructor will give you the hostname or IP number)
- 3. Login using the username and password you were given
- 4. From the UNIX command line, type **telnet localhost 80** -- this connects to port 80 of the server, where the HTTP daemon (aka the web server) is listening. You should see something like this:

```
training:~> telnet localhost 80
Trying 1.2.3.4
Connected to training.netizen.com.au.
Escape character is '^]'.
```

- 5. Ask the web server for a static document by typing: GET /index.html HTTP/1.0 then press enter twice to send the request. Note that this command is *case sensitive*.
- 6. Look at the response that comes back. Do you see the headers? They should look something like this:

```
HTTP/1.1 200 OK
Date: Tue, 28 Mar 2000 02:42:37 GMT
Server: Apache/1.3.6 (UNIX)
Connection: close
Content-Type: text/html
```

This will be followed by a blank line, then the content of the file you asked for. Then you will see "Connection closed by foreign host", indicating that the HTTP server has closed the connection.

- If you miss seeing the headers because the body is too long, try using the HEAD method instead of GET.
- 7. Telnet to port 80 again and ask the web server for a CGI script's output by typing GET /cgi-bin/localtime.cgi HTTP/1.0
- 8. Now let's get some status codes other than 200 OK from the web server:

- GET /not_here.html HTTP/1.0 (a file which doesn't exist)
- GET /unreadable.html HTTP/1.0 (a file with the permissions set wrong)
- GET /protected.html HTTP/1.0 (a file protected by HTTP authentication we cover this later on today)
- GET /redirected.html HTTP/1.0 (a file which is redirected to a different URL)
- ENCRYPT /index.html HTTP/1.0 (a method which isn't known to our server)

22.7 What is needed to run CGI programs?

There are several things you need in order to create and run Perl CGI programs.

- a web server
- web server configuration which gives you permission to run CGI
- a Perl interpreter
- appropriate Perl modules, such as CGI.pm
- a shell account is extremely useful but not essential

Most of the above requirements will need your system administrator or ISP to set them up for you. Some will be wary of allowing users to run CGI programs, and may require you to obey certain security regulations or pay extra for the privilege. The most common security requirement is that CGI programs must run under cgiwrap. This is discussed later, in the section on security.

22.8 Chapter summary

- CGI stands for Common Gateway Interface
- HTTP stands for Hypertext Transfer Protocol. This is the protocol used for transferring documents and other files via the World Wide Web.
- HTTP clients (web browsers) send requests to HTTP (web) servers, which are answered with HTTP responses
- The request/response can be examined by telnetting to the appropriate port of a web server and typing in requests by hand.

Chapter 23: Generating web pages with Perl

In this chapter...

In this section, we will create a simple "Hello world" CGI program and run it, then extend upon that to integrate parts of Perl taught in previous modules. Alternative quoting mechanisms are briefly covered, and we also discuss debugging techniques for CGI programs.

23.1 Your public_html directory

The training server has been set up so that each user has their own web space underneath their home directory. All files which will be accessible via the web should be placed in the directory named public_html. This is common for most personal home pages.

The directory ~username/public_html on the UNIX file system maps to the URL http://hostname/~username/ via the web. So if your login name is stu03 and you are using the PerlClass.com training server at perlclass.fini.net, you can access your web pages at http://perlclass.fini.net/~sty03. Of course, you will need to replace both the hostname and username to match your specific setup.

23.2 The CGI directory

CGI scripts are usually kept in a separate directory from plain HTML files. This directory is most commonly called cgi-bin (the "bin" stands for "binary" but really just means "executable files", whether compiled binaries or interpreted scripts such as Perl programs). The web server is usually set up so that you only have permission to run CGI programs from the cgi-bin directory, for security reasons.

- 1. Change to your public_html directory
- 2. If you type **Is** to get a directory listing, you will see that you have several HTML files here, as well as a cgi-bin directory.
- 3. Change to your cgi-bin directory and type **ls**, and you will see that the example scripts for this course are already installed here.

If you were setting this up for yourself, you would need to be sure of the following:

- 1. That your home directory is world executable
- 2. That your public_html directory is world executable
- 3. That all your HTML files are world readable
- 4. That your cgi-bin directory is world executable note that it is not compulsory to have a cgi-bin directory some server configurations allow you to execute a CGI script from any directory.
- 5. That all your CGI scripts are world readable and executable

23.3 The HTTP headers

Every CGI script must output an HTTP header giving a MIME content type, such as Content-type: text/html, with a blank line after it:

```
print "Content-type: text/html\n\n";
```

Put this at the top of every CGI script, as the first thing that's printed.

Advanced

If your output is of another MIME type, you should print out the appropriate <code>content-type</code>: header - for instance, a CGI program which outputs a random GIF image would use <code>con-tent-type</code>: <code>image/gif</code>

23

23.4 HTML output

Any other output of your script will be sent back to the web browser just as you specify. Since we're outputting content of the type text/html we should make our scripts output HTML:

```
print "<h1>Hello, world!</h1>\n";
```

The above example is already in your cgi-bin directory as hello.cgi.

23.5 Running and debugging CGI programs

When writing CGI programs, there are many problems which may affect their execution. Since these will not always be easily understood by examining the web browser output, there are other ways to check how your program is running:

- 1. First, check that your program runs by running it from the command line. It may be that you've made a syntax error, or that your program has the wrong permissions
- 2. Second, try opening it in a browser. If your program runs on the command line but does not output content to the browser, you may have forgotten to print out the Content-type: text/html header, or forgotten to leave a blank line between the header and the body, or may have made an error in your HTML output.
- 3. Thirdly, check the web server's log files. Where these are will vary from system to system. On our system, they're in /var/log/apache, and you can check them using **cat**, **less**, **tail**, or any other tool of your choice. If you don't know what these commands do, check their manual pages by typing **man cat**, **man less**, etc.

23.5.1 Exercises

- 1. Look at the output of the hello.cgi script by pointing a web browser (such as Netscape) at http://hostname/~trainXX/cgi-bin/hello.cgi (replace hostname with the hostname or IP address of the training server, and XX with your number)
- 2. Modify hello.cgi to set a variable \$name and include that name in the greeting. (Don't forget to use strict;)
- 3. Run your modified hello.cgi from the command line to ensure that it runs.
- 4. Press the Reload button in your browser to see if your modifications worked correctly.

23.6 Quoting made easy

It can be annoying to output HTML using double quotes. You may find yourself doing things like this:

```
print "<img src=\"$img\" alt=\"$alttext\">\n";
print "<a href=\"$url\">A hypertext link</a>\n";
```

Escaping all those quotes with backslashes can get tedious and unreadable. Luckily, there are a couple of ways around it.

23.6.1 Here documents

"Here" documents allow you to print everything until a certain marker is found:

```
print <<"END";
<img src="$img" alt="$alttext">
<a href="$url">A hypertext link</a>
END
```

You can specify what end marker you want on in the print statement.

The fact that the marker is in double quotes means that the material up until the end marker is found will undergo interpolation in the same way as any doublequoted string. If you use single quotes, it'll act like a single-quoted string, and no interpolation will occur.

ADVANCED

If you use backticks, it will execute each line via the shell.

The end marker must be on a line by itself, at the very start of the line. Note also that the print statement has a semi-colon on the end.

23.7 Pick your own quotes

Another way of avoiding excessive backslashes in your code is to use the qq() or q() operators/functions.

RTFM!					
Src	Chap	Pgs	#		
Nutshell 2 nd	4	46			
Camel 2 nd	2	41			
Camel 3 rd	2	63 - 64			
perldoc	perlop				
Cookbook 2 nd	1	3			
Learning 3 rd	3	43 - 44	qw()		
Learning 4 th					

print qq(\n);
print qq(A hypertext link\n);

Like the matching and substitution operators m// and s///, the quoting operators can use just about any character as a delimiter:

```
print qq(<a href="$url">A hypertext link</a>\n);
print qq!<a href="$url">A hypertext link</a>\n!;
print qq[<a href="$url">A hypertext link</a>\n];
print qq#<a href="$url">A hypertext link</a>\n#;
```

If the opening delimiter is a bracket type character, the closing delimiter will be the matching bracket.

Always choose a delimiter that isn't likely to be found in your quoted text. A slash, while common in non-HTML uses of the function, is not very useful for quoting anything containing HTML closing tags like

23.8 Exercises

The following exercises practice using CGI to output different Perl data types (as taught in Introduction to Perl) such as arrays and hashes. You may use plain double quotes, ``here" documents, or the quoting operators as you see fit.

- 1. Write a CGI program which creates an array then outputs the items in an unordered list (HTML's element) using a foreach loop. If you need help with HTML, there's a cheat sheet in Appendix D.
- 2. Modify your program to print out the keys and values in a hash, like this:
 - Name is Fred
 - Sex is male
 - Favorite colour is blue
- 3. Change your CGI program so that you output a table instead of an unordered list, with the keys in one column and the values in another. An example of how this could be done is in cgi-bin/hashtable.cgi

23.9 Environment variables

In Perl, there is a special variable called <code>%ENV</code> which contains all the environment variables which are set.

When a web server runs a CGI program, certain environment variables are set to provide information about the web server, the request made by the user agent, and other pertinent information.

Examples of environment variables available to your CGI script include HTTP_USER_AGENT which describes the user agent or browser used to make the request, and HTTP_REFERER, which indicates the referring page (if any).

23.9.1 Exercises

- 1. Modify your table-printing script from the previous exercise to print out the hash %ENV.
- 2. The HTTP_USER_AGENT environment variable contains the type of browser used to request the CGI script.
 - Write a script which prints out the user agent string for the requesting browser
 - Take a look at what various browsers report themselves as -- try Netscape, Internet Explorer, or Lynx from the UNIX command line. You will note that Microsoft browsers purport to be "Mozilla compatible" (i.e. compatible with Netscape).
 - Use a regular expression to determine when a certain browser (for instance, Microsoft Internet Explorer) is being used, and output a message to the user.
- 3. The HTTP_REFERER (yes, it's spelt incorrectly in the protocol definition) environment variable contains the URL of the page from which the user followed a link to your CGI program. If you call up your CGI program by typing its URL straight into the browser, the HTTP_REFERER will be an empty string. Create an HTML page that points to your CGI program and see what the REFERER environment variable says.

23.10 Chapter summary

- CGI scripts are programs written in Perl or any other language that output web content such as HTML pages
- CGI scripts must output a Content-type header and a blank line before anything else
- Debugging techniques for CGI:
 - Run the script from the command line
 - Try opening it in the browser
 - Check the logs
- Various techniques are available for quoting text, including "here" documents and Perl quoting functions such as qq().
- The %ENV special variable can be used to access environment variables via CGI scripts, including such variables as HTTP_USER_AGENT and HTTP_REFERER

Chapter 24: Processing form input

In this chapter...

CGI programs are often used to accept and process data from HTML forms. In this section, we take a quick look at HTML forms and use the CGI module to parse form data.

24.1 A quick look at HTML forms

To be able to use CGI to accept user input, you will probably need to understand HTML forms. There's an HTML cheat-sheet in Appendix D of these notes, but here's a brief run-down of the major parts of HTML forms:

24.2 The FORM element

The FORM element is a block level element - that means that the browser will present it on a new line, like it does with headings and paragraphs.

The FORM element's attributes include:

Attribute	Example	Description
METHOD	METHOD="POST"	The HTTP method to use to send the form's contents back to the web server. It can be POST or GET the differences are explained the the HTTP cheat sheet appendix.
ACTION	ACTION="/cgi- bin/myscript.cgi"	The relative or absolute URL of the CGI program which is to process the form's data

 Table 24-1. FORM element attributes

Other attributes exist, but will not be used in this course.

24.3 Input fields

Some of the input fields you can use in your form include:

24.3.1 TEXT

A text input field <INPUT TYPE="TEXT" NAME="email_address">

24.3.2 CHECKBOX

Creates a yes/no checkbox. Saying CHECKED will make it checked by default.

<INPUT TYPE="CHECKBOX" NAME="send_email" CHECKED>

24.3.3 SELECT

Creates a drop-down list of items. Saying SELECT MULTIPLE will allow for multiple choices to be made.

```
<SELECT NAME="hobbies">
<OPTION VALUE="philately">Philately</OPTION>
<OPTION VALUE="gardening">Gardening</OPTION>
<OPTION VALUE="programming">Programming</OPTION>
<OPTION VALUE="cookery">Cookery</OPTION>
<OPTION VALUE="reading">Reading</OPTION>
<OPTION VALUE="reading">Reading</OPTION>
<OPTION VALUE="bushwalking">Bushwalking</OPTION>
</SELECT>
```

24.3.4 SUBMIT

Creates a button which, when pressed, will submit the form.

```
<INPUT TYPE="SUBMIT" VALUE="Press me!">
```

24.4 The CGI module

24.4.1 What is a module?

A module is a collection of useful functions which you can use in your programs. They are written by Perl people worldwide, and distributed mostly through CPAN, the Comprehensive Perl Archive Network.

Perl modules save you heaps of time - by using a module, you save yourself from "reinventing the wheel". Perl modules also tend to save you from making silly mistakes again and again while you try to figure out how to do a given task.

One common (but fiddly) task in CGI programming is taking the parameters given in an HTML form and turning them into variables that you can use.

The parameters from an HTML form are encoded in this "percent-encoded" format:

name=Kirrily&company=Netizen%20Pty.%20Ltd.

If you use the POST method, these parameters are passed via STDIN to the CGI script, whereas GET passes them via the environment variable QUERY_STRING. This means that as well as simply parsing the character string, you need to know where to look for it as well.

The easiest way to parse this parameter line is to use cgi module.

RTFM!					
Src	Chap	Pgs	#		
Nutshell 2 nd	10	376 - 398			
Camel 2 nd					
Camel 3 rd					
perldoc	CGI				
Cookbook 2 nd		756 - 791			
Learning 3 rd					
Learning 4 th					

24.4.2 Using the CGI module

To use the CGI module, simply put the statement use CGI; at the top of your script, thus:

```
#!/usr/bin/perl -w
use strict;
use CGI;
```

24.4.3 Accepting parameters with CGI

To accept form parameters into our CGI script as variables, we can say that we specifically want to use the params part of the CGI module:

```
#!/usr/bin/perl -w
use strict;
use CGI 'param';
```

This provides us with a new subroutine, param, which we can use to extract the value of the HTML form's fields.

```
#!/usr/bin/perl -w
use strict;
use CGI 'param';
my $name = param('name');
print "Content-type: text/html\n\n";
print "Hello, $name!";
```

24.4.4 Debugging with the CGI module's offline mode

When you run a CGI script from the command line, you will see a prompt like this:

(offline mode: enter name=value pairs on standard input)

This allows you to enter parameters in the form name=value for testing and debugging purposes. Use **CTRL-D** (the UNIX end-of-file character) to indicate that you are finished.

```
(offline mode: enter name=value pairs on standard input)
name=fred
age=40
^D
```

24.4.5 Exercises

- 1. Write a simple form to ask the user for their name. Type in the above script and see if it works.
- 2. Add some fields to your form, including a checkbox and a drop down menu, and print out their values. What are the default true/false values for a checkbox?
- 3. What happens if you use the SELECT MULTIPLE form functionality? Try assigning that field's parameters from it to an array instead of a scalar, and you will see that the data is handled smoothly by the CGI module. Print them out using a foreach loop, as in earlier exercises.

24.5 Practical Exercise: Data validation

Your trainer will now demonstrate and discuss the use of cgi for validation of data entered into a web form. An example form is in your public_html directory as validate.html and the validation CGI script is available in your cgi-bin directory as validate.cgi.

```
#!/usr/bin/perl -w
use strict;
use CGI 'param';
print "Content-type: text/html\n\n";
my @errors;
push (@errors, "Year must be numeric") if param('year') = / D/;
push (@errors, "You must fill in your name") if param('name') eq "";
push (@errors, "URL must begin with http://")
          if param('url') !~ m!^http://!;
if (@errors) {
       print "<h2>Errors</h2>\n";
       print "\n";
       foreach (@errors) {
               print "$_\n";
       }
       print "\n";
} else {
       print "Congratulations, no errors!\n";
}
```

24.5.1 Exercises

1. Open the form for the validation program in your browser. Try submitting the form with various inputs.

24.6 Practical Exercise: Multi-form "Wizard" interface

Your trainer will now demonstrate and discuss how you can use what you've just learned to create a multi-form "wizard" interface, where values are remembered from one form to the next and passed using hidden fields.

```
<INPUT TYPE="HIDDEN" VALUE="..." NAME="...">
```

Source code for this example is available as cgi-bin/wizard.cgi.

First, we print some headers and pick up the "step" parameter to see what step of the wizard interface we're up to. We have four subroutines, named step1 through step4, which do the actual work for each step.

```
#!/usr/bin/perl -w
use strict:
use CGI 'param';
print <<"END";</pre>
Content-type: text/html
<html>
<body>
<h1>Wizard interface</h1>
END
my $step = param('step') || 0;
step1() unless $step;
step2() if $step == 2;
step3() if $step == 3;
step4() if $step == 4;
print <<"END";</pre>
</body>
```

</html> END

Here are the subroutines. The first one is fairly straightforward, just printing out a form:

```
#
# Step 1 -- Name
#
sub step1 {
        print qq(
                <h2>Step 1: Name</h2>
                What is your name?
                <form method="POST" action="wizard.cgi">
                <input type="hidden" name="step" value="2">
                <input type="text" name="name">
                <input type="submit">
                </form>
       );
}
```

Steps 2 through 4 require us to pick up the CGI parameters for each field that's been filled in so far, and print them out again as hidden fields:

```
<form method="POST" action="wizard.cgi">
                <input type="hidden" name="step" value="3">
                <input type="hidden" name="name" value="$name">
                <input type="text" name="quest">
                <input type="submit">
                </form>
        );
}
#
# Step 3 -- favorite colour
#
sub step3 {
        my $name = param('name');
        my $quest = param('quest');
        print qq(
                <h2>Step 3: Silly Question</h2>
                what is the airspeed velocity of an unladen swallow?
                <form method="POST" action="wizard.cgi">
                <input type="hidden" name="step" value="4">
                <input type="hidden" name="name" value="$name">
                <input type="hidden" name="quest" value="$quest">
                <input type="text" name="swallow">
                <input type="submit">
                </form>
        );
}
```

Step 4 simply prints out the values that the user entered in the previous steps:

```
#
# Step 4 -- finish up
```

```
#
sub step4 {
       my $name = param('name');
       my $quest = param('quest');
       my $swallow = param('swallow');
       print qq(
               <h2>Step 4: Done!</h2>
               Thank you!
               Your name is $name. Your quest is $quest. The
airspeed
               velocity of an unladen swallow is $swallow.
               );
}
```

24.6.1 Exercises

1. Add another question to the wizard.cgi script.

24.7 Practical Exercise: File upload

cgi can also be used to allow users to upload files. Your trainer will demonstrate and discuss this. Source code for this example is available in your cgibin directory as upload.cgi

First off, you need to specify an encoding type in your form element. The attribute to set is ENCTYPE="multipart/form-data".

```
<html>
<head>
<title>Upload a file</title>
</head>
<body>
<hl>Upload a file</hl>
Please choose a file to upload:
<form action="upload.cgi" method="POST" enctype="multipart/form-
data">
<input type="file" name="filename">
<input type="file" name="filename">
</form>
</form>
</body>
</html>
```

cGI handles file uploads quite easily. Just use param() as usual. The value returned is special -- in a scalar context, it gives you the filename of the file uploaded, but you can also use it in a filehandle.

```
#!/usr/bin/perl -w
use strict;
use CGI 'param';
my $filename = param('filename');
my $outfile = "outputfile";
```

```
print "Content-type: text/html\n\n";
# There will probably be permission problems with this open
# statement unless you're running under cgiwrap, or your script
# is setuid, or $outfile is world writable. But let's not worry
# about that for now.
open (OUTFILE, ">$outfile") || die "Can't open output file: $!";
# This bit is taken straight from the CGI.pm documentation --
# you could also just use "while (<$filename>)" if you wanted
my ($buffer, $bytesread);
while ($bytesread=read($filename,$buffer,1024)) {
    print OUTFILE $buffer;
}
close OUTFILE || die "Can't close OUTFILE: $!";
print "Uploaded file and saved as $outfile\n";
print "</body></html>";
```
24.8 Chapter summary

- The CGI module can be used to parse data from HTML forms
- Its most common use is parameter parsing; other functions are also available
- To use it, type use CGI 'param'; at the top of your script
- Obtain each item of data using the param() function
- CGI can be used to implement web applications of any complexity, including data validation, multi-form wizards, file upload, and more

Chapter 25: Security issues

In this chapter...

In this section we examine some security issues arising from the use of CGI scripts, including authentication and access control, and the risk of tainted data and how to avoid it.

25.1 Authentication and access control for CGI scripts

A common question asked by new CGI programmers is "How do I protect my web site with a CGI script?" There are various ways to use CGI programs to ask for usernames and passwords and perform authentication, but in fact the best way to perform authentication and access control comes with your web server and doesn't require any programming at all.

The reason that password protection is often connected with CGI programs is that CGI programs are more likely to interact with the web server's underlying file system, backend databases, or other things which need to be kept secure. Many programmers assume that because CGI can be used for password protection, it is the right choice for the job. This is not necessarily true.

One of the best ways to password protect web pages is by using the web server's own authentication and access control mechanisms. Since we're using the Apache web server, we'll look at how to do it with that.

25.1.1 Why is CGI authentication a bad idea?

Authentication (i.e. username and password checking) is hard to do correctly in CGI. Some common pitfalls include:

• Username and password strings are sent as parameters in a GET query, and end up in the URL (eg

http://example.com/my.cgi?username=fred&password=secret). These details can then end up in peoples' bookmark files, other sites' referer logs, and so on.

• Sometimes username and password details are passed back and forth using "cookies". Many users choose to have cookies disabled due to privacy concerns, and the website will therefore be unusable to them. No such problem exists with HTTP authentication via the web server

On the other hand, the main disadvantage of HTTP authentication is that the authentication tokens remain active until the user shuts their browser down. This can be a problem in public computer labs and other locations where users may share PCs.

25.2 HTTP authentication

If a web page or CGI script requires a username and password to view it, the HTTP conversation between the client and the server goes like this:

- 1. The user specifies a URL
- 2. The user agent connects to port 80 of the HTTP server
- 3. The user agent sends a request such as GET /index.html
- 4. The user agent may also send other headers
- 5. The HTTP server realises that authentication must be performed {usually by looking up configuration files}
- 6. The HTTP server returns a status code 401, meaning "Unauthorized", and also a header saying www-Authenticate: and the name of the authentication domain, for instance "Acme Widget Co. Staff". This usually appears in the browser's dialog box as "Please provide a username and password for Acme Widget Co. Staff".
- 7. The browser presents a dialog box or other means by which the user can enter their username and password, which the user fills in then clicks "OK"
- 8. The browser sends a new request, this time including an extra header saying Authorization: and the appropriate credentials
- 9. If the HTTP server finds that the credentials are valid, it sends back the resource requested and closes the connection
- 10. Otherwise, it sends back another response with status code 401 (and probably a body containing an error message), which the user agent should recognise as meaning that the authentication failed, and display the body.

25.3 Access control

The way access control is handled varies from one web server to another. If your web server is not Apache, you will need to contact your web server administrator or read the documentation it came with, as only Apache is covered in this course.

Apache implements HTTP authentication with the use of a password file and either server configurations or a .htaccess file in the web directory, which contains server configuration directives. Our server has been set up to allow you to use the .htaccess file.

A password file has already been set up for your use. It's /etc/apache/training.passwd and uses the same usernames and passwords as your login accounts. You can look at it by typing cat /etc/apache/training.passwd

To use this password file, create a file in your public_html directory called .htaccess, containing the following text:

```
AuthType Basic
AuthName "Secret stuff"
AuthUserFile /etc/apache/training.passwd
require valid-user
```

This authentication will apply to the directory in which the .htaccess file is placed and any subdirectories.

25.3.1 Exercises

- 1. Create a .htaccess file in your public_html directory, as above
- 2. Use your web browser to request one of your HTML files or CGI scripts, and observe the authentication process
- 3. Why would it be a bad idea to put the password file in the same directory as the web pages or CGI scripts?

25.4 Tainted data

Sometimes you will want to write a CGI script which interacts with the system. This can result in major security risks if the commands executed on the system are based on user input. Consider the example of a finger program which asked the user who they wanted to finger.

```
#!/usr/bin/perl -w
use strict;
print "who do you want to finger? ";
my $username = <STDIN>;
print `finger $username`; # backticks execute shell command
```

Imagine if the user's input had been skud; cat /etc/passwd, or worse yet, skud; rm -rf / The system would perform both commands as though they had been entered into the shell one after the other.

Luckily, Perl's -T flag can be used to check for unsafe user inputs.

#!/usr/bin/perl -	wT
-------------------	----

RTFM!			
Src	Chap	Pgs	#
Nutshell 2 nd			
Camel 2 nd	6	356 - 360	
Camel 3 rd	23	557 - 566	
perldoc	perlsec		
Cookbook 2 nd	19	767 - 770	
Learning 3 rd	В	294	light
Learning 4 th			

-T stands for "taint checking". Data input by the user, either via the command line or an HTML form, is considered "tainted", and until it has been modified by the script, may not be used to perform shell commands or system interactions of any kind.

The only thing that will clear tainting is referencing substrings from a regexp match. **perldoc perlsec** contains a simple example of how to do this, about 7 pages down. Read it now, and use it to complete the following exercises.

Note that you'll also have to explicitly set \$ENV{'PATH'} to something safe (like /bin) as well.

25.4.1 Exercises

- 1. The HTML file finger.html asks the user for an account name about which to obtain information {using the UNIX system's finger command}. It calls the CGI script cgi-bin/finger.cgi which uses taint checking.
- 2. Why is the data input by the user tainted?
- 3. Add a -T flag to the shebang line of finger.cgi so that the script performs taint checking
- 4. Try re-submitting the form it should fail
- 5. To untain the data, you need to clean up any unwanted characters. Use some code similar to that in **perldoc perlsec** to remove anything other than alphanumeric characters and assign the valid part of the user input to a new variable.

25.5 cgiwrap

Many large sites, such as ISPs and educational institutions, require users to run their CGI scripts using a program called **cgiwrap**. This program causes the CGI script to execute as if being run by the owner, instead of the web server's user ID. What this means is that the script will have permission to read and write the user's files, and will not be able to cause any damage on the system that the user could not cause.

25.6 Secure HTTP

Another somewhat related topic is secure HTTP, which uses the HTTPS protocol to open a secure connection and encrypts all data between the web client and server. This is often used to make online credit card transactions more secure.

CGI scripts can be run on a secure server exactly as they would run on any other server.

25.7 Chapter summary

- HTTP authentication can be used to password protect web pages
- The Apache web server implements HTTP authentication. This can be configured via a .htaccess file
- There is a security risk from tainted data --- data entered by a user which is used for subsequent system interaction
- Perl has built-in checking for tainted data, which can be turned on my using the -T command line switch
- Data can be untainted by referencing a substring in a match, as shown in **perldoc perlsec**.
- Some web servers use **cgiwrap** to run CGI scripts under their owner's user ID.
- Secure HTTP can be used to provide an encrypted channel of communication between the web client and server.

Chapter 26: Other related Perl modules

In this chapter...

In this section we are briefly introduced to Perl modules which may be useful to us in developing CGI applications, including modules for failing gracefully, encoding and decoding URLS, and filling in templates.

26.1 Useful Perl modules

There are several common problems faced by CGI programmers: failing gracefully, creating valid URLs from any text, using a template to insert variables into HTML, sending email based on CGI parameters, et cetera. Since these problems are so common, people have written modules to solve them. This section explains some of the most useful modules to save you from having to re-invent the wheel.

Each of these modules can be downloaded from CPAN (the Comprehensive Perl Archive Network) (http://www.perl.com/CPAN) and installed either using the CPAN module distributed with Perl, or by following the steps described in the README file distributed with each module.

26.2 Failing gracefully with CGI::Carp

The errors given in the web server's error logs are not always easy to read and understand. To make life easier, we can use a Perl module called CGI::Carp to add timestamps and other handy information to the logs.

```
use CGI::Carp;
```

We can also make our errors go to a separate log, by using the carpout part of the module. This needs to be done inside a BEGIN block in order to catch compiler errors as well as ones which occur at the interpretation stage.

```
BEGIN {
    use CGI::Carp qw(carpout);
    open(LOG, ">>cgi-logs/mycgi-log") ||
        die("Unable to open mycgi-log: $!\n");
        carpout(LOG);
}
```

}

Lastly, we can cause any fatal errors to have their error messages and diagnostic information output directly to the browser:

```
use CGI::Carp 'fatalsToBrowser';
```

RT FM!			
Src	Chap	Pgs	#
Nutshell 2 nd	8	192	
Camel 2 nd	7	385	
Camel 3 rd	32	878	
perldoc	Carp		
Cookbook 2 nd	12	473 - 475	
Learning 3 rd			
Learning 4 th			

26.2.1 Exercise

- 1. Use the CGI::Carp module in one of your scripts
- 2. Deliberately cause a syntax error, for instance by removing a semi-colon or quote mark, or inserting a die ("Argh!"); statement, and see what happens

26.3 Encoding URIs with URI::Escape

Sometimes we want to output anchor tags referring to another CGI script, and pass parameters along with it, thus:

```
<A HREF="lookup.cgi?title=Programming Perl&publisher=O'Reilly">
O'Reilly's Programming Perl
</A>
```

However, spaces and apostrophes aren't allowed in URIs, so we have to encode them into the "percent-encoded" format. This format replaces most non-al-phanumeric characters with two hexadecimal digits. For instance, a space becomes \$20 and a tilde becomes \$7E.

The Perl module we use to encode URIs in this manner is URI::Escape. Its documentation is available by typing **perldoc URI::Escape**.

Use it as follows:

```
#!/usr/bin/perl -w
use strict;
use URI::Escape;
my $book_lookup =
"lookup.cgi?title=Programming Perl&publisher=O'Reilly";
my $encoded_url = uri_escape($address);
my $original url = uri unescape($encoded url);
```

26.3.1 Exercise

1. Try out the above script cgi-bin/escape.cgi you'll need to print out the values of \$encoded_url and \$original_url

26.4 Creating templates with Text::Template

By this stage in the day you have probably spent a great deal of time outputting HTML either via a long list of print statements or by using a "here document" or other shortcut. What if you wanted to have a template HTML output file which was filled in with the appropriate variables?

Luckily, there is a Perl module to do this, called Text::Template. Unluckily, it uses a concept we haven't covered yet, but which we will now explain.

Text::Template is different to the other modules we have used so far today, in that it is an *object oriented* module. Object oriented Perl modules can be very powerful, but require some background knowledge to understand how they work.

26.4.1 Introduction to object oriented modules

Before embarking on this task, we need to have an understanding of how Perl's object-oriented modules work. Not all modules are object oriented (URI::Escape, for example, is not), and some can be used either way (CGI is one of these), but some require us to work with them in this way.

A software object, like a real-life object, has attributes (things that describe the object) and methods (things you can do with, or to, the object). Consider the real-life example of a cup:

Object	Attributes	Methods
Cup	• colour	• drink from it
	• handle (does it have one?)	• fill it up
	• contents (water, coffee, etc)	• smash it
	• fullness	

Table 26-1. Attributes and Methods of a cup

Note that when you smash a cup, you aren't smashing the generic class of cups, but rather a specific instance - *this* cup, not "cups in general". This is what we call an *instance of a class* -- remember that, as we'll use it later.

26.4.2 Using the Text::Template module

Like the cup, our text template has attributes and methods.

		-
Text::Template	• TYPE - the type of template it is, eg a file, a string you created earlier, etc	• fill_in() - fill in the template
	• SOURCE - the filehandle or variable name in which the template can be found	

Table 26-2. Attrib	outes and Metho	ds of Text::Template
--------------------	-----------------	----------------------

Before we can actually use these attributes and methods in any useful way, we have to create a new instance of the class. This is the same as how we needed a specific cup, rather than the general class of cups.

```
# using the class in general
use Text::Template;
# instantiating the class and setting some attributes for the new
instance
my $letter = new Text::Template{'TYPE' => 'FILE', 'SOURCE' =>
'letter.tmpl'};
```

We can then perform a method on it, thus:

my \$finished_letter = \$letter->fill_in();

This will fill in any variables found in the template file.

26.4.3 Exercise

- 1. Type **perldoc Text::Template** and look at the documentation for this module
- 2. cgi-bin/letter.cgi implements the example above. Examine the source code.
- 3. Make some changes to the letter template and see if they work.

26.5 Sending email with Mail::Mailer

The Mail::Mailer module can be used to send email from a CGI script (or, for that matter, any script). Like Text::Template, it is an Object Oriented module. The object it creates is a "mailer" object, which can be opened and then printed to as if it were a filehandle.

```
#!/usr/bin/perl -w
use strict;
use Mail::Mailer;
my $mailer = new Mail::Mailer;
# the open() method takes a hash reference with keys which are mail
# header names and values which are the values of those mail headers
$mailer->open( {
       From =>
                        'fred@example.com',
        To =>
                        'barney@example.com',
        Subject =>
                        'Web form submission'
} );
# we can print to $mailer just as we would print to STDOUT or any
# other file handle...
print $mailer qq(
Dear Barney,
Here is a form submission from your website:
Name:
                $name
Email:
                $email
Comments:
                $comments
Love, Fred.
);
$mailer->close();
```

Advanced

You can also open a pipe to **sendmail** directly, but doing this correctly can be difficult. This is why we recommend Mail::Mailer to avoid re-inventing the wheel.

26.5.1 Exercises

- 1. Create an HTML form with fields for name, email and comment
- 2. Use the above script (cgi-bin/mail.cgi) to mail the results of the script to yourself. You will need to edit it to work fully:
 - Use CGI.pm to pick up the parameters
 - Change the email address to your own address
 - Print out a "thank you" page once the form has been submitted -- don't forget the Content-type header

26.6 Chapter Summary

- The CGI::Carp module can be used to help CGI programs fail gracefully
- The ${\tt uRI::Escape}$ module can be used to encode and decode percent-encoded URLs
- The Text::Template module can be used to easily fill in text templates, including HTML templates.
- The Mail::Mailer module can be used to send email based on the information entered in an HTML form
- All these modules can be downloaded from CPAN, the Comprehensive Perl Archive Network

Chapter 27: Conclusion

In the conclusion...

Summing up and various paths for further study.

27.1 Day 1: What you've learned

Now you've completed PerlClass.com's Introduction to Perl module, you should be confident in your knowledge of the following fields:

- What is Perl? Perl's features; Perl's main uses; where to find information about Perl online
- Creating Perl scripts and running them from the UNIX command line, including the use of the -w flag to enable warnings
- Perl's three main variable types: scalars, arrays and hashes
- The strict pragma, lexical scoping, and their benefits
- Perl's most common operators and functions, and their use
- Perl's concept of truth; existence and definedness of variables
- Conditional and looping constructs: if, while, foreach and others.
- Regular expressions: the matching and substitution operators; simple metacharacters; quantifiers; alternation and grouping

27.2 Day 2: What you've learned

Now you've completed PerlClass.com's *Intermediate Perl* module, you should be confident in your knowledge of the following fields:

- File I/O, including opening files and directories, opening pipes, finding information about files, recursing down directories, file locking, and handling binary data
- How to use advanced regular expression techniques such as multiline matching and backreferences
- The use of various Perl functions
- System interaction, including: system calls, the backtick operator, interacting with the file system, dealing with users and groups, dealing with processes, network communications, and security considerations
- · Advanced Perl data structures and references

27.3 Day 3: What you've learned

Now you've completed PerlClass.com's CGI Programming in Perl module, you should be confident in your knowledge of the following fields:

- What CGI is
- How HTTP allows web user agents (browsers) to communicate with web servers and retreive documents
- How to perform HTTP requests by using **telnet** to connect to the web server
- How to generate simple web pages using Perl
- How to access environment variables from CGI scripts
- Various methods of quoting text, including "here" documents and the qq() type functions
- How to process data from HTML forms using the CGI module
- How to use the CGI module for applications such as data validation, simple "wizard" interfaces, and file uploads
- Security issues related to CGI programming, including authentication and access control, dealing with tainted data, secure web servers, etc.
- The use of various Perl modules related to CGI programming, including CGI::Carp, URI::Escape, Text::Template, and Mail::Mailer
- · A basic understanding of object oriented Perl modules

27.4 Day 4: What you've learned

Now you've completed PerlClass.com's Database Programming with Perl module, you should be confident in your knowledge of the following fields:

- Database terminology, including tables and relationships, fields and records, etc
- · Flat file database manipulation including delimited and CSV text files
- Basic SQL queries, including select, insert, delete, and update queries
- Features of MySQL, where to get MySQL from, and how to set up MySQL databases
- Using the MySQL command line client to perform SQL queries
- Using Perl's DBI module to interact with databases
- Applying Perl skills from previous training modules to create database applications

27.5 Where to now?

To further extend your knowledge of Perl, you may like to:

- Borrow or purchase the books listed in our "Further Reading" section (below)
- Follow some of the URLs given throughout these course notes, especially the ones marked "Readme"
- Install Perl on your home or work computer
- Practice using Perl from day to day
- Install Perl and MySQL (or other database servers) on your home or work computer
- Install Perl and a web server such as Apache on your home or work computer
- · Practice using Perl for CGI programming on a daily basis
- Practice using Perl to interact with databases
- Join a Perl user group such as Perl Mongers (http://www.pm.org/)
 - Richmond Perl Mongers (http://richmond.pm.org/)
 - Hampton Roads Perl Mongers (http://norfolk.pm.org/)

27.6 Further reading

27.6.1 Books

- Alligator Descartes & Tim Bunce, "Programming the Perl DBI", O'Reilly and Associates, 2000
- Randy Jay Yarger, George Reese & Tim King, "mSQL and MySQL", O'Reilly and Associates, 1999
- Tom Christiansen and Nathan Torkington, *The Perl Cookbook*, O'Reilly and Associates, 1998. ISBN 1-56592-243-3.
- Jeffrey Friedl, *Mastering Regular Expressions*, O'Reilly and Associates, 1997. ISBN 1-56592-257-3.
- Joseph N. Hall and Randal L. Schwartz*Effective Perl Programming*, Addison-Wesley, 1997. ISBN 0-20141-975-0.

27.6.2 Online

- The Perl homepage (http://www.perl.com/)
- The Perl Journal (http://www.tpj.com/)
- Perlmonth (http://www.perlmonth.com/) (online journal)
- Perl Mongers Perl user groups (http://www.pm.org/)
- comp.lang.perl.announce newsgroup
- comp.lang.perl.moderated newsgroup
- comp.lang.perl.misc newsgroup

Chapter 28: Win32::-EventLog

In this chapter...

We will show how to use Win32::EventLog to derive various kinds of informatoin from the Windows Event Log. You will also see how to use Perl to backup your EventLog and create your own events.



28.1 Win32::EventLog Examples

The following example illustrates the way in which the Win32::EventLog module can be used. It opens the System Event Log and reads through it from oldest to newest. For each record from the source event log it extracts the full text of the entry and prints out the event log message text.

To backup and clear the event logs on a remote machine do the following:

```
);
my $dest;
for my $event_log (qw( Application System Security )) {
    $handle = Win32::EventLog-new($event_log, $my_server)
        or die "Can't open $event_log event log on $my_server";
    $dest = 'C:\BackupEventLogs\$event_log\' . $date . '.evt';
    $handle->Backup($dest) or warn "Could not backup and clear" .
        " the $event_log event log on \\\\$my_server ($^E)\n";
    $handle->Close;
```

}

28.2 Win32::EventLog Reference

This module implements most of the functionality available from the Win32 API for accessing and manipulating Win32 Event Logs. The access to the EventLog routines is divided into those that relate to an EventLog object and its associated methods and those that relate other EventLog tasks (like adding an EventLog record).

28.2.1 The EventLog Object and its Methods

The following methods are available to open, read, close and backup EventLogs.

win32::EventLog->new(SOURCENAME [,SERVERNAME]);

The new() method creates a new EventLog object and returns a handle to it. This hande is then used to call the methods below.

The method is overloaded in that if the supplied SOURCENAME argument contains one or more literal '\' characters (an illegal character in a SOURCENAME), it assumes that you are trying to open a backup eventlog and uses SOURCENAME as the backup eventlog to open. Note that when opening a backup eventlog, the SERVERNAME argument is ignored (as it is in the underlying Win32 API). For EventLogs on remote machines, the SOURCENAME parameter must therefore be specified as a UNC path.

\$handle->Backup(FILENAME);

The Backup() method backs up the EventLog represented by \$handle. It takes a single arguent, FILENAME. When \$handle represents an EventLog on a remote machine, FILENAME is filename on the remote machine and cannot be a UNC path (i.e you must use $C:\TEMP\App.EVT$). The method will fail if the log file already exists.

\$handle->Read(FLAGS, OFFSET, HASHREF);

The Read() method read an EventLog entry from the EventLog represented by \$handle.

\$handle->Close();

The Close() method closes the EventLog represented by \$handle. After Close() has been called, any further attempt to use the EventLog represented by \$handle will fail.

\$handle->GetOldest(SCALARREF);

The GetOldest() method number of the the oldest EventLog record in the EventLog represented by \$handle. This is required to correctly compute the OFFSET required by the Read() method.

\$handle->GetNumber(SCALARREF);

The GetNumber() method returns the number of EventLog records in the EventLog represented by \$handle. The number of the most recent record in the EventLog is therefore computed by

\$handle->GetOldest(\$oldest);
\$handle->GetNumber(\$lastRec);
\$lastRecOffset=\$oldest+\$lastRec;

\$handle->Clear(FILENAME);

The Clear() method clears the EventLog represented by \$handle. If you provide a non-null FILENAME, the EventLog will be backed up into FILENAME before the EventLog is cleared. The method will fail if FILENAME is specified and the file refered to exists. Note also that FILENAME specifies a file local to the machine on which the EventLog resides and cannot be specified as a UNC name.

\$handle->Report(HASHREF);

The Report() method generates an EventLog entry. The HASHREF should contain the following keys:

Computer

The Computer field specfies which computer you want the EventLog entry recorded. If this key doesn't exist, the server name used to create the \$handle is used.

Source

The Source field specifies the source that generated the EventLog entry. If this key doesn't exist, the source name used to create the \$handle is used.

EventType

The EventType field should be one of the constants

EVENTLOG ERROR TYPE = An Error event is being logged.

EVENTLOG_WARNING_TYPE = A Warning event is being logged.

EVENTLOG_INFORMATION_TYPE = An Information event is being logged.

EVENTLOG_AUDIT_SUCCESS = A Success Audit event is being logged (typically in the Security EventLog).
EVENTLOG_AUDIT_FAILURE = A Failure Audit event is being logged (typically in the Security EventLog).

These constants are exported into the main namespace by default.

Category = The Category field can have any value you want. It is specific to the particular Source.

EventID = The EventID field should contain the ID of the message that this event pertains too. This assumes that you have an associated message file (indirectly referenced by the field Source).

Data = The Data field contains raw data associated with this event.

Strings = The Strings field contains the single string that itself contains NUL terminated sub-strings. This are used with the EventID to generate the message as seen from (for example) the Event Viewer application.

28.2.2 Other Win32::EventLog functions

The following functions are part of the Win32::EventLog package but are not callable from an EventLog object.

GetMessageText(HASHREF);

The GetMessageText() function assumes that HASHREF was obtained by a call to \$handle->Read(). It returns the formatted string that represents the fully resolved text of the EventLog message (such as would be seen in the Windows NT Event Viewer). For convenience, the key 'Message' in the supplied HASHREF is also set to the return value of this function.

If you set the variable \$Win32::EventLog::GetMessageText to 1 then each call to \$handle->Read() will call this function automatically.

Chapter 29: Win32::Ne tAdmin

In this chapter...

You will learn how to manage Windows network groups and users in Perl.

The Win32::NetAdmin module offers control over the administratoin of Windows groups and user over a Windows network.

29.1 Example

```
# Simple script using Win32::NetAdmin to set the login script for
# all members of the NT group "Domain Users". Only works if you
# run it on the PDC. (From Robert Spier <rspier@seas.upenn.edu>)
#
# FILTER_TEMP_DUPLICATE_ACCOUNTS
    Enumerates local user account data on a domain controller.
#
#
# FILTER_NORMAL_ACCOUNT
    Enumerates global user account data on a computer.
#
#
# FILTER_INTERDOMAIN_TRUST_ACCOUNT
    Enumerates domain trust account data on a domain controller.
#
#
# FILTER_WORKSTATION_TRUST_ACCOUNT
#
    Enumerates workstation or member server account data on a domain
#
    controller.
#
# FILTER_SERVER_TRUST_ACCOUNT
#
    Enumerates domain controller account data on domain controller.
use Win32::NetAdmin qw(GetUsers GroupIsMember
                       UserGetAttributes UserSetAttributes);
my %hash;
GetUsers("", FILTER_NORMAL_ACCOUNT , \%hash)
    or die "GetUsers() failed: $^E";
foreach ( keys %hash ) {
    my ($password, $passwordAge, $privilege,
        $homeDir, $comment, $flags, $scriptPath);
    if ( GroupIsMember("", "Domain Users", $_) ) {
        print "Updating $_ ($hash{$_})\n";
        UserGetAttributes("", $_, $password, $passwordAge,
                          $privilege, $homeDir, $comment,
                          $flags, $scriptPath)
```

```
or die "UserGetAttributes() failed: $^E";
$scriptPath = "dnx_login.bat"; # the new login script
UserSetAttributes("", $_, $password, $passwordAge,
$privilege, $homeDir, $comment, $flags, $scriptPath)
or die "UserSetAttributes() failed: $^E";
}
```

29.2 Win32::NetAdmin provided functions

Note: All of the functions return false if they fail, unless otherwise noted. When a function fails call Win32::NetAdmin::GetError() rather than GetLastError() or \$^E to retrieve the error code.

server is optional for all the calls below. If not given the local machine is assumed.

GetError()

Returns the error code of the last call to this module.

GetDomainController(server, domain, returnedName)

Returns the name of the domain controller for server.

GetAnyDomainController(server, domain, returnedName)

Returns the name of any domain controller for a domain that is directly trusted by the server.

UserCreate(server, userName, password, passwordAge, privilege, homeDir, comment, flags, scriptPath)

Creates a user on server with password, passwordAge, privilege, homeDir, comment, flags, and scriptPath.

UserDelete(server, user)

Deletes a user from server.

UserGetAttributes(server, userName, password, passwordAge, privilege, homeDir, comment, flags, scriptPath)

Gets password, passwordAge, privilege, homeDir, comment, flags, and

scriptPath for user.

UserSetAttributes(server, userName, password, passwordAge, privilege, homeDir, comment, flags, scriptPath)

Sets password, passwordAge, privilege, homeDir, comment, flags, and scriptPath for user.

UserChangePassword(domainname, username, oldpassword, newpassword) Changes a users password. Can be run under any account.

UsersExist(server, userName)

Checks if a user exists.

GetUsers(server, filter, userRef)

Fills userRef with user names if it is an array reference and with the user names and the full names if it is a hash reference.

GroupCreate(server, group, comment)

Creates a group.

GroupDelete(server, group)

Deletes a group.

GroupGetAttributes(server, groupName, comment)

Gets the comment.

GroupSetAttributes(server, groupName, comment) Sets the comment. GroupAddUsers(server, groupName, users) Adds a user to a group.

GroupDeleteUsers(server, groupName, users) Deletes a users from a group.

GroupIsMember(server, groupName, user) Returns TRUE if user is a member of groupName.

GroupGetMembers(server, groupName, userArrayRef) Fills userArrayRef with the members of groupName.

LocalGroupCreate(server, group, comment) Creates a local group.

LocalGroupDelete(server, group) Deletes a local group.

LocalGroupGetAttributes(server, groupName, comment) Gets the comment.

LocalGroupSetAttributes(server, groupName, comment) Sets the comment.

LocalGroupIsMember(server, groupName, user) Returns TRUE if user is a member of groupName.

```
LocalGroupGetMembers(server, groupName, userArrayRef)
```

Fills userArrayRef with the members of groupName.

```
LocalGroupGetMembersWithDomain(server, groupName, userRef)
```

This function is similar LocalGroupGetMembers but accepts an array or a hash reference. Unlike LocalGroupGetMembers it returns each user name as DOMAIN\USERNAME. If a hash reference is given, the function returns to each user or group name the type (group, user, alias etc.). The possible types are as follows:

```
$SidTypeUser = 1;
$SidTypeGroup = 2;
$SidTypeDomain = 3;
$SidTypeAlias = 4;
$SidTypeWellKnownGroup = 5;
$SidTypeDeletedAccount = 6;
$SidTypeInvalid = 7;
$SidTypeUnknown = 8;
```

LocalGroupAddUsers(server, groupName, users)

Adds a user to a group.

LocalGroupDeleteUsers(server, groupName, users)

Deletes a users from a group.

GetServers(server, domain, flags, serverRef)

Gets an array of server names or an hash with the server names and the comments as seen in the Network Neighborhood or the server manager. For flags, see SV_TYPE_* constants.

```
GetTransports(server, transportRef)
```

Enumerates the network transports of a computer. If transportRef is an array reference, it is filled with the transport names. If transportRef is a

hash reference then a hash of hashes is filled with the data for the transports.

```
LoggedOnUsers(server, userRef)
```

Gets an array or hash with the users logged on at the specified computer. If userRef is a hash reference, the value is a semikolon separated string of username, logon domain and logon server.

```
GetAliasFromRID(server, RID, returnedName)
GetUserGroupFromRID(server, RID, returnedName)
```

Retrieves the name of an alias (i.e local group) or a user group for a RID from the specified server. These functions can be used for example to get the account name for the administrator account if it is renamed or localized.

Possible values for RID:

```
DOMAIN_ALIAS_RID_ACCOUNT_OPS
DOMAIN_ALIAS_RID_ADMINS
DOMAIN_ALIAS_RID_BACKUP_OPS
DOMAIN_ALIAS_RID_GUESTS
DOMAIN_ALIAS_RID_POWER_USERS
DOMAIN_ALIAS_RID_PRINT_OPS
DOMAIN_ALIAS_RID_REPLICATOR
DOMAIN_ALIAS_RID_SYSTEM_OPS
DOMAIN_ALIAS_RID_USERS
DOMAIN_GROUP_RID_ADMINS
DOMAIN_GROUP_RID_GUESTS
DOMAIN_GROUP_RID_USERS
DOMAIN_USER_RID_ADMIN
DOMAIN_USER_RID_GUEST
```

GetServerDisks(server, arrayRef)

Returns an array with the disk drives of the specified server. The array contains two-character strings (drive letter followed by a colon).

Chapter 30: Other Perl Win32 Modules

In this chapter...

This section documents three other modules that are useful for Windows NT administration.

30.1 Win32::NetResource

This module offers control over the network resources of Win32.Disks, printers etc can be shared over a network.

30.1.1 Examples

Enumerating all resources on the network

```
#
# This example displays all the share points in the entire
# visible part of the network.
#
use strict;
use Win32::NetResource qw(:DEFAULT GetSharedResources GetError);
my $resources = [];
unless(GetSharedResources($resources, RESOURCETYPE_ANY)) {
    my $err;
    GetError($err);
    warn Win32::FormatMessage($err);
}
foreach my $href (@$resources) {
    next if ($$href{DisplayType} != RESOURCEDISPLAYTYPE_SHARE);
    print "----\n";
    foreach( keys %$href){
        print "$_: $href->{$_}\n";
    }
}
```

Enumerating all resources on a particular host

#
This example displays all the share points exported by the
local host.
#
use strict;

30.1.2 Data Types

There are two main data types required to control network resources. In Perl these are represented by hash types.

30.1.2.1 %NETRESOURCE

Key	Value	
Scope	Scope of an Enumeration: RESOURCE_CONNECTED, RESOURCE_GLOBALNET, RESOURCE_REMEMBERED.	
Туре	The type of resource to Enum:	
	RESOURCETYPE_ANY All resources	
	RESOURCETYPE_DISK Disk resources	
	RESOURCETYPE_PRINT Print resources	
DisplayType	The way the resource should be displayed.	
	RESOURCEDISPLAYTYPE_DOMAIN	
	The object should be displayed as a domain.	
	RESOURCEDISPLAYTYPE_GENERIC	
	The method used to display the object does not matter.	
	RESOURCEDISPLAYTYPE_SERVER	
	The object should be displayed as a server.	

Key	Value
	RESOURCEDISPLAYTYPE_SHARE
	The object should be displayed as a sharepoint.
Usage	Specifies the Resources usage: RESOURCEUSAGE_CONNECTABLE, RESOURCEUSAGE_CONTAINER.
LocalName	Name of the local device the resource is connected to.
RemoteName	The network name of the resource.
Comment	A string comment.
Provider	Name of the provider of the resource

30.1.2.2 %SHARE_INFO

This hash represents the SHARE_INFO_502 struct.

Key	Value
netname	Name of the share.
type	type of share.
remark	A string comment.
permissions	Permissions value
maxusers	the max # of users.
current-users	the current # of users.
path	The path of the share.
passwd	A password if one is req'd

30.1.3 Functions

Note: All of the functions return false if they fail.

GetSharedResources(\@Resources,dwType,\%NetResource = NULL)

Creates a list in @Resources of %NETRESOURCE hash references.

The return value indicates whether there was an error in accessing any of the shared resources. All the shared resources that were encountered (until the point of an error, if any) are pushed into @Resources as references to %NETRESOURCE hashes. See example below. The \%NetResource argument is optional. If it is not supplied, the root (that is, the topmost container) of the network is assumed, and all network resources available from the toplevel container will be enumerated.

AddConnection(\%NETRESOURCE, \$Password, \$UserName, \$Connection)

Makes a connection to a network resource specified by %NETRESOURCE

CancelConnection(\$Name,\$Connection,\$Force)

Cancels a connection to a network resource connected to local device \$name.\$Connection is either 1 - persistent connection or 0, non-persistent.

WNetGetLastError(\$ErrorCode,\$Description,\$Name)

Gets the Extended Network Error.

GetError(\$ErrorCode)

Gets the last Error for a Win32::NetResource call.

GetUNCName(\$UNCName, \$LocalPath);

Returns the UNC name of the disk share connected to \$LocalPath in \$UNCName. \$LocalPath should be a drive based path. e.g. "C:\\share\\subdir"

Note: \$servername is optional for all the calls below. (if not given the local machine is assumed.)

NetShareAdd(\%SHARE,\$parm_err,\$servername = NULL)

Add a share for sharing.

```
NetShareCheck($device,$type,$servername = NULL )
```

Check if a directory or a device is available for connection from the network through a share. This includes all directories that are reachable through a shared directory or device, meaning that if C:\foo is shared, C:\foo\bar is also available for sharing. This means that this function is pretty useless, given that by default every disk volume has an administrative share such as "C\$" associated with its root directory.

\$device must be a drive name, directory, or a device. For example, "C:", "C:\dir", "LPT1", "D\$", "IPC\$" are all valid as the \$device argument. \$type is an output argument that will be set to one of the following constants that describe the type of share:

STYPE_DISKTREE	Disk drive
STYPE_PRINTQ	Print queue
STYPE_DEVICE	Communication device
STYPE_IPC	Interprocess communication (IPC)
STYPE_SPECIAL	Special share reserved for interprocess communication (IPC\$) or remote administration of the server (ADMIN\$). Can also refer to administrative shares such as C\$, D\$, etc.

NetShareDel(\$netname, \$servername = NULL)

Remove a share from a machines list of shares.

```
NetShareGetInfo( $netname, \%SHARE,$servername=NULL )
```

Get the %SHARE_INFO information about the share \$netname on the server \$servername.

NetShareSetInfo(\$netname,\%SHARE,\$parm_err,\$servername=NULL) Set the information for share \$netname.

30.2 Win32::Service

30.2.1 Examples

The first script gets a hashref that contains information about all of the services on the current host. It then retrieves status information for each of those into another hashref.

```
use Win32::Service;
my (%service, %status);
Win32::Service::GetServices('',\%services);
foreach my $key (sort keys %services) {
    print "Display Name\t: $key, $services{$key}\n";
    Win32::Service::GetStatus('', $sercices{$key}, \%status);
    foreach my $part (keys %status) {
        print "\t$part : $status{$part}\n";
    }
}
```

The next script checks the status of NetDDE. If it's already running, it dies with an error. Otherwise, it tries to start it.

```
use Win32::Service;
use Win32;
my %status;
Win32::Service::GetStatus('', 'NetDDE', \%status);
die "service is already started\n"
    if ($status{CurrentState} == 4); # running
Win32::Service::StartService(Win32::NodeName(), 'NetDDE')
    or die "can't start service\n";
```

```
print "Service started\n";
```

30.2.2 Functoins

Note: All of the functions return false if they fail, unless otherwise noted. If hostName is an empty string, the local machine is assumed.

StartService(hostName, serviceName)

Start the service serviceName on machine hostName.

StopService(hostName, serviceName)

Stop the service serviceName on the machine hostName.

GetStatus(hostName, serviceName, status)

Get the status of a service. The third argument must be a hash reference that will be populated with entries corresponding to the SERVICE_STATUS structure of the Win32 API. See the Win32 Platform SDK documentation for details of this structure.

PauseService(hostName, serviceName)
ResumeService(hostName, serviceName)
GetServices(hostName, hashref)

Enumerates both active and inactive Win32 services at the specified host. The hashref is populated with the descriptive service names as keys and the short names as the values.

30.3 Win32::Sound

30.3.1 Quick Sample

A sampling of Perl playing sounds and adjusting the volume:

```
use Win32::Sound;
Win32::Sound::Volume('50%');
# set volume for left and right seperately
Win32::Sound::Volume('100%','50%');
($left,$right) = Win32::Sound::Volume();
Win32::Sound::Volume(0); # mute
Win32::Sound::Volume($left,$right); # restore prior values
Win32::Sound::Play("example.wav") # arbitrary
Win32::Sound::Play("systemQuestion"); # symbolic
Win32::Sound::Stop();
```

Chapter 31: *NIX cheat sheet

31.1 Some UNIX commands

A brief run-down for those whose UNIX skills are rusty:

Action	Command
Change to home directory	cd
Change to directory	cd directory
Change to directory above current directory	cd
Show current directory	pwd
Directory listing	ls
Wide directory listing, showing hidden files	ls -al
Showing file permissions	ls -al
Making a file executable	chmod +x filename
Printing a long file a screenful at a time	more filename or less filename
Getting help for command	man command
dddd	

 Table 31-1. Simple UNIX commands

ddd

Chapter 32: Editor cheat sheet

In this chapter...

you will find an editor summary which is laid out as follows:

Running	Recommended command line for starting it.
Using	Really basic howto. This is not even an attempt at a detailed howto.
Exiting	How to quit.
Gotchas	Oddities to watch for.

 Table 32-1. Layout of editor cheat sheets

32.1 vi

vi is the classic UNIX editor. It is strange but beautiful. It is very powerful in educated hands and is universally available in the UNIX world.

A version of vi known as vim is available that can esaily be installed in Windows and many other strange operating systems. Check out <u>http://www.vim.org/</u> for more information.

32.1.1 Running

% vi filename

32.1.2 Using

- i to enter insert mode, then type text, press **ESC** to leave insert mode.
- \times to delete character below cursor.
- dd to delete the current line
- Cursor keys should move the cursor while *not* in insert mode.
- If not, try hjkl, h = left, l = right, j = down, k = up.
- /, then a string, then **ENTER** to search for text.
- :w then **ENTER** to save.

32.1.3 Exiting

- Press ESC if necessary to leave insert mode.
- :q then ENTER to exit.
- :q! ENTER to exit without saving.
- :wq to exit with save.

32.1.4 Gotchas

vi has an insert mode and a command mode. Text entry only works in insert mode, and cursor motion only works in command mode. If you get confused about what mode you are in, pressing ESC twice is guaranteed to get you back to command mode (from where you press i to insert text, etc).

32.1.5 Help

:help ENTER might work. If not, then see the man page.

32.2 pico

pico is the editor from pine turned into an external command. pine is no longer supported by some Linux distributions so you may have to type "nano" to get "pico", but you can always make an alias.

32.2.1 Running

% pico -w filename

32.2.2 Using

- Cursor keys should work to move the cursor.
- Type to insert text under the cursor.
- The menu bar has ^x commands listed. This means hold down **CTRL** and press the letter involved, eg **CTRL-W** to search for text.
- CTRL-Oto save.

32.2.3 Exiting

Follow the menu bar, if you are in the midst of a command. Use **CTRL-X** from the main menu.

32.2.4 Gotchas

Line wraps are automatically inserted unless the -w flag is given on the command line. This often causes problems when strings are wrapped in the middle of code and similar. $\$ hline

32.2.5 Help

CTRL-G from the main menu, or just read the menu bar.

386

32.3 joe

32.3.1 Running

% joe filename

32.3.2 Using

- Cursor keys to move the cursor.
- Type to insert text under the cursor.
- CTRL-K then S to save.

32.3.3 Exiting

- **CTRL-C** to exit without save.
- CTRL-K then X to save and exit.

32.3.4 Gotchas

Nothing in particular.

32.3.5 Help

CTRL-K then H.

32.4 jed

32.4.1 Running

% jed

32.4.2 Using

- Defaults to the emacs emulation mode.
- Cursor keys to move the cursor.
- Type to insert text under the cursor.
- CTRL-X then S to save.

32.4.3 Exiting

CTRL-X then CTRL-C to exit.

32.4.4 Gotchas

Nothing in particular.

32.4.5 Help

- Read the menu bar at the top.
- Press ESC then ? then H from the main menu.

Chapter 33: ASCII Pronunciation Guide

In this chapter...

It is widely recognized that speaking about computing topics requires some common set of terms for communications, so computerese or technobabble describe this dialect. But it is less widely recognized that a dialect is necessary for unambiguously communicating about individual characters.

Character	Pronunciation
!	bang, exlamation
*	star, asterisk
Ş	dollar
Ø	at
8	percent
æ	ampersand
Π	double quote
1	single quote, tick, or forward quote
()	open/close bracket, parentheses
<	less than, left angle bracket
>	greater than, right angle bracket
-	dash, hyphen, n-dash
	dot, period
,	comma
/	slash, forward slash
\backslash	backslash
:	colon
;	semicolon
=	equals
?	question mark
^	caret (pron. "carrot")
_	underscore
[]	open/close square bracket
{ }	open/close curly brackets, brace, squigglies, or squiggly brackets
	pipe, bar, or vertical bar
~	tilde (pron."til-duh"), wiggle
`	backtick, backquote (below ~)

Table 33-1. ASCII Pronunciation Guide

Chapter 34: HTML Cheat Sheet

In this chapter....

The following table outlines a few HTML elements which may be useful to you. For more detail or for information about elements which are not listed here, consult one of the references listed below.

Type of information	Markup								
Paragraph									
Heading level 1	<h1>This is a level 1 heading</h1>								
Heading level 2	<h2>This is a level 2 heading</h2>								
Heading level 3	<h3>This is a level 3 heading</h3>								
Heading level 4	<h4>This is a level 4 heading</h4>								
Unordered (bulleted) list	 List item 1 List item 2 List item 3 								
Ordered (numbered) list	 List item 1 List item 2 List item 3 								
Table	<table border=""> <tr> < "table row" > <th>Heading column 1</th> <th>Heading column 2</th> <th>Heading column 3</th> </tr> <tr> < "table row" > <td>row 1, column 1</td> <td>row 1, column 2</td> <td>row 1, column 3</td> </tr> <tr> < "table row" > <td>row 2, column 1</td> <td>row 2, column 1</td> row 2, column 3 row 2, column 3 row 2, column 3</tr></table>	Heading column 1	Heading column 2	Heading column 3	row 1, column 1	row 1, column 2	row 1, column 3	row 2, column 1	row 2, column 1
Heading column 1	Heading column 2	Heading column 3							
row 1, column 1	row 1, column 2	row 1, column 3							
row 2, column 1	row 2, column 1								
Horizontal rule	<hr/>								
Anchor tag (hypertext link)	<pre>Descriptive text</pre>								

Table D-1. Basic HTML elements

For more information...

- HTMLhelp.org (http://htmlhelp.org/)
- The World Wide Web Consortium (W3C) (<u>http://w3.org/</u>)

Chapter 35: Acknowledgements

In this section...

I will try to thank a few of the folks and projects that made this possible

35.1 Folks

First and foremost my wife, Cynthia Manuel has been an able and fun companion in life and work for years. Nothing would be possible without her.

Thanks to John Lundin for vast contriutions of systems administration, content comments, and wonderful stir fries.

Thanks to Stephen Johnson for supporting my instruction and content creation efforts for many years now. If it weren't for Stephen I would never have taught this course for US News & World Report, Circuit City, or a lot of other folks.

Thanks to all of the folks who have survived my instruction of this course and others. Your ideas, comments, complaints, and foolishness have all helped make this class what it is.

Thanks to Mark Whittington for automotive wisdom and other random surprises.

Thanks to Kirrily "skud" Robert for creating the DocBook version of this conent and sharing it with the world. If only DocBook weren't such a pain. (Writing LISP to make style sheets? Ick.)

Thanks to Carl Hicks, Thomas St. Jacques, Buffy Boke, and Jonathan Collie for varied non-technical contributions.
35.2 Projects

OpenOffice.org for providing a nice free word processor.

dia for easy ERD editing.

Fedora for a damn fine desktop Linux.

CentOS and Red Hat for a damn fine server Linux.

TWiki for a mighty fine wiki. Written in Perl naturally.

Perl for being there to teach. Larry, Randal, and a cast of thousands work together to produce art and technology that looks less like a committee product than most geeks would expect.